

Contents

LSW Design Concept2

R-1 Radial.....	2
R-1W Radial	3
R-2 Radial	3

Bias & Radial R-1, R-1W4

Goodyear UltraTorque Plus R-1.....	4
Goodyear OptiTorque R-1.....	4
Goodyear Ultra Sprayer R-1.....	4
Goodyear Dyna Torque Radial R-1	5
Goodyear Dyna Torque Radial II R-1	6
Goodyear DT710/DT730 R-1.....	6
Goodyear Versa Torque R-1	6
Goodyear Dura Torque R-1.....	7
Goodyear Power Torque R-1.....	7
Goodyear Traction Torque R-1.....	7
Goodyear Traction Sure Grip R-1.....	7
Goodyear Dyna Torque II R-1.....	8
Goodyear Dyna Torque III R-1.....	8
Goodyear Harvest Torque R-1.....	9
Goodyear Traction Irrigation 3 R-1.....	9
Goodyear Super Traction R-1W.....	10
Goodyear Optitrac R-1W.....	11
Goodyear Optiterra Radial R-1W.....	13
Goodyear DT900 R-1W.....	13
Goodyear DT924 R-1W.....	13

Radial R-2.....14

Goodyear Custom Flo Grip Radial R-2.....	14
Goodyear Special Sure Grip TD8 Radial R-2	14

Bias R-2.....15

Goodyear Special Sure Grip TD8 R-2.....	15
Goodyear Special Sure Grip.....	15

Bias & Radial R-3.....16

Goodyear All Weather Radial R-3	16
Goodyear All Weather Radial II R-3	16
Goodyear All Weather R-3.....	16
Goodyear SFT105 R-3.....	16
Goodyear Smooth R-3.....	16
Goodyear Softrac II R-3.....	16

Radial R-418

Goodyear IT510 Radial R-4.....	18
Goodyear IT520 Radial R-4.....	18
Goodyear IT525 Radial R-4.....	18
Goodyear IT530 Radial R-4.....	18

Bias R-419

Goodyear Industrial Sure Grip R-4.....	19
Goodyear Sure Grip Lug R-4.....	19
Goodyear IT515 HS R-4.....	19
Goodyear IT525 R-4.....	19

Bias F-1, F-2, F-2M..... 20

Goodyear Single Rib F-1.....	20
Goodyear Triple Rib RS F-2.....	20
Goodyear Triple Rib HD F-2.....	20
Goodyear Super Rib F-2.....	20
Goodyear Hi Rib F-2.....	20
Goodyear Four Rib F-2M.....	20
Goodyear Dyna Rib F-2M.....	20

Bias F-3.....21

Goodyear Laborer F-3.....	21
Goodyear Multi Rib F-3.....	21

Radial I-1 22

Goodyear FS24.....	22
--------------------	----

Bias I-1 22

Goodyear Rib Implement I-1	22
Goodyear Farm Utility I-1.....	22
Goodyear Pneumatic Drive I-1.....	22
Goodyear Drill Rib I-1.....	22

Bias FI 24

Goodyear Farm Highway Service I-1.....	24
Goodyear Farm Highway Service II I-1.....	24

Radial I-3..... 24

Goodyear Super Flot Radial	24
Goodyear Muck Master Radial.....	25

Bias I-3..... 25

Goodyear Sure Grip Traction I-3	25
Goodyear Traction Implement I-3.....	25
Goodyear Sure Grip Implement I-3.....	25
Goodyear Sure Grip Lug I-3.....	25
Goodyear Contractor I-3.....	25

Bias HF-1, HF-2 26

Goodyear SofTrac HF-1.....	26
Goodyear SofTrac II HF-1	26
Goodyear Tundra Grip LF HF-1.....	26
Goodyear Rib Terra HF-1.....	26
Goodyear Smooth Terra HF-1.....	26
Goodyear SoftTurf HF-1.....	26
Goodyear Xtra Traction HF-1.....	26
Goodyear SFT105 HF-1.....	26
Goodyear SFT115 HF-1.....	27
Goodyear Terra Rib HF-1.....	27
Goodyear Super Terra Grip HF-2.....	27
Goodyear Xtra Trac HF-2.....	27

Radial HF-1, HF-2, HF-3 29

Goodyear Tundra Grip Radial HF-1	29
Goodyear Super Terra Rib Radial HF-1.....	29
Goodyear Super Terra Grip Radial HF-2	29
Goodyear Super Terra Grip XT Radial HF-3	29

Skid Steer 30

Goodyear IT323 SS.....	30
Goodyear Sure Grip Lug SS.....	30
Goodyear Industrial Xtra Grip SS	30
Goodyear Smooth.....	31
Goodyear Smooth Implement.....	31
Goodyear Smooth Industrial.....	31
Goodyear Snow Plow.....	31
Goodyear Smooth Mono Rail.....	31
Goodyear Glass Polisher.....	31
Goodyear Compactor.....	31

Logger Lug 32

Goodyear Logger Lug III LS-2.....	32
Goodyear Logger Lug III HD LS-2.....	32
Goodyear Logger Lug III Flotation HF-4	33

ATV Tracker 34

ATV Wrangler..... 35

ATV Rawhide..... 36

ATV ATT 37

ATV Runamuck 37

ATV Compass Terra 38

Middle of the Book

Tire Information Section1-120

Industry Standards/Tire Selection Chart.....	1
Things You Should Know About Farm Tires.....	2
High Flexion Tires Description.....	7
LSW Description	8
Radial Sizes by Rolling Circumference.....	9
Int'l Load Index/Speed Symbols	13
Rolling Circumference	14
Optimum Tractor Tire Performance.....	15
LSW & Metric Conversion Tables	19
Load & Inflation Tables.....	20
Horse Power Capability.....	95
Liquid Fill Procedures.....	104
Approved Rim Contours.....	111
RCI Chart.....	120

Safety SectionS:1-22

Goodyear

Radial LSW

WHAT IS LSW® TECHNOLOGY?



Low Sidewall (LSW®) technology features a larger rim diameter and smaller sidewall than a conventional tire, while maintaining the same outside diameter and weight load capacity. The larger rim and smaller sidewall of LSW® provides much greater stability for equipment.

LOW SIDEWALL



STANDARD



Same
outside
diameter



REDUCED SOIL COMPACTION

with ability to carry up to 40% more load at same inflation pressures.



IMPROVED TRACTION

with greater stability and footprint, providing more power to the ground



REDUCE ROAD LOPE

faster, smoother transport speeds between fields



REDUCED POWER HOP

with larger wheel diameter that dampens recoil in high draw-bar applications

R-1 RADIAL

Catalog #	Tire Size	Conventional Size Replaced	Design	TL/TT	Load Rating	Inflation Pressure (psi)	Max Load mph	Max Load (lbs)	Recom'd Rim Width* (in)	Tire Width (in)	Overall Diameter (in)	Static Loaded Radius (in)	Rolling Circ. (in)	Flat Plate Area (in²)	Weight (lbs)	Tread Depth 32nd in.	No. of Lugs
GOTFTL	LSW680/55R42	680/65R38	Optitorque	TL	171D	29	40	13,600	23	25.9	72.5	32.5	217	524	604	50	44
GSS916	LSW1100/45R46	None	Muck Master	TL	190D	35	40	23,400	38	41.3	85.4	39.6	264	na	na	67	38
GSS917	LSW1250/40R46	None	Muck Master	TL	201D	52	40	32,000	44	49.2	85.0	39.5	264	na	na	67	38

*See Approved Rim Contours section
**Release 2nd Quarter

Radial LSW

Goodyear

Radial R-1W

Catalog #	Tire Size	Conventional Size Replaced	Design	TL/TT	Load Rating	Inflation Pressure (psi)	Max Load mph	Max Load (lbs)	Recom'd Rim Width* (in)	Tire Width (in)	Overall Diameter (in)	Static Loaded Radius (in)	Rolling Circ. (in)	Flat Plate Area (in ²)	Weight (lbs)	Tread Depth 32nd in.	No. of Lugs
GTRHM3	LSW380/65R42	380/80R38	Super Traction Radial	TL	149D	35	40	7,150	12	13.8	62.6	28.9	193	252	242	60	40
GOPD79	LSW420/75R34	420/90R30	Optitrac	TL	150D	23	40	7,400	13	16	57.8	25.7	171	304	270	62	38
GOPHM4	LSW420/75R38	420/85R34	Optitrac	TL	157D	35	40	9,100	14	16.2	62.5	28.0	186	300	319	62	42
GTRD51	LSW480/70R54	480/80R50	Super Traction Radial	TL	163D	23	40	10,700	16	18	80.1	36.4	242	419	497	64	50
GTRT51	LSW480/70R54	480/80R50	Super Traction Radial	TL	181D	64	40	18,200	16	18	80.8	36.9	246	407	547	64	50
GOPD52	LSW520/75R46	520/85R42	Optitrac	TL	166D	23	40	11,700	18	20.4E	76.3E	34.3E	229E	423E	560	72	42
GOPK52	LSW520/75R46	520/85R42	Optitrac	TL	175D	41	40	15,200	18	20.4E	76.3E	34.3E	229E	423E	598	72	42
GOPDD4	LSW580/75R46	580/85R42	Optitrac	TL	172D	23	40	13,900	18	24.0E	79.7E	35.4E	236E	500E	641	68	44
GOPKD4	LSW580/75R46	580/85R42	Optitrac	TL	180D	41	40	17,600	18	24.0E	79.7E	35.4E	236E	500E	684	68	44
GOPDD4	LSW650/60R42	650/65R38	Optitrac	TL	168D	23	40	12,300	20	25.1	72.1	32.3	215	506	605	72	44
GOPHHA	LSW650/70R46	650/85R38	Optitrac	TL	181D	35	40	18,200	21	24.5	81.8	36.6	244	657	763	76	42
GTRK98	LSW710/60R30	28LR26	Super Traction Radial	TL	177D	41	40	16,100	25	27	63.8	28.6	191	531	541	78	34
GOPD91	LSW710/60R46	710/70R42	Optitrac	TL	174D	23	40	14,800	25	28.2	80.3	36.2	241	704	796	78	42
GOPM91	LSW710/60R46	710/70R42	Optitrac	TL	186D	46	40	20,900	25	28.2	80.3	36.2	241	704	810	78	42
GOPKN6	LSW750/60R30	750/65R26	Optitrac	TL	180D	41	40	17,600	25	29.6E	66.1E	28.5E	194E	452E	628	65	34
GTRH96	LSW800/50R42	800/65R32	Super Traction Radial	TL	180D	35	40	17,600	28	29.4	71.7	32.5	217	634	710	75	40
GOPDM8	LSW800/55R46	800/70R38	Optitrac	TL	178D	23	40	16,500	28	30.7	81.5	36.2	241	756	900	77	44
GOPMM8	LSW800/55R46	800/70R38	Optitrac	TL	190D	46	40	23,400	28	30.9	81.4	36.9	246	728	963	77	44
GOPMT3	LSW850/55R30	850/60R26	Optitrac	TL	186D	46	40	20,900	30	33.4E	66.1E	28.0E	193E	700E	774	69	36
GOPDB1	LSW900/50R46	900/70R32	Optitrac	TL	181D	23	40	18,200	30	32.5E	81.9E	36.3E	243E	870E	883	71	44
GOPKB1	LSW900/50R46	900/70R32	Optitrac	TL	191D	41	40	24,000	30	32.5E	81.9E	36.3E	243E	870E	971	71	44
GOPPC4	LSW900/60R42	900/75R32	Optitrac	TL	200D	52	40	30,900	30	35.5	85.3	38.1	254	868	1158	71	50
GOPBF3	LSW1000/40R32	1000/50R25	Optitrac	TL	167D	17	40	12,000	36	38.8	66.4	29.1	194	772	864	79	36
GOPHF3	LSW1000/40R32	1000/50R25	Optitrac	TL	180D	35	40	17,600	36	38.8E	66.4E	29.1E	194E	772E	884	79	36
G8MB16GY	LSW1100/45R46	None	DT930	TL	181D	17	40	18,200	38	39.5	83.7	36.8	245	972	1204	77	40
G8MH16GY	LSW1100/45R46	None	DT930	TL	195D	35	40	26,800	38	40.5	84.0	37.4	249	1011	1295	77	40
GOPHR6	LSW1250/35R46	1250/50R32	Optitrac	TL	195D	35	40	26,800	44	48.2	81.8	37.5	250	1129	1439	83	48
GOPMS6	LSW1400/30R46	None	Optitrac	TL	201D	46	40	32,000	50	52.5	83.2	38.5	257	1125	1572	83	48

*See Approved Rim Contours section
 **Release 2nd Quarter

R-2 RADIAL

Catalog #	Tire Size	Conventional Size Replaced	Design	TL/TT	Load Rating	Inflation Pressure (psi)	Max Load mph	Max Load (lbs)	Recom'd Rim Width* (in)	Tire Width (in)	Overall Diameter (in)	Static Loaded Radius (in)	Rolling Circ. (in)	Flat Plate Area (in ²)	Weight (lbs)	Tread Depth 32nd in.	No. of Lugs
GFGMT3	LSW850/55R30	850/60R26	Custom Flo Grip	TL	186B	46	30	20,900	30	34.1	65.3	29.1	194	779	887	111	28
GTDY1	LSW900/50R42	900/65R32	SSG TD8 Radial	TL	192B	46	30	24,700	30	33.3	79.9	35.7	238	780	1079	126	28
GFGHR6	LSW1250/35R46	1250/50R32	Custom Flo Grip	TL	195B	35	30	26,800	44	47.5	84.2	37.6	250	1121	1688	116	32

*See Approved Rim Contours section

Goodyear

Radial R-1



Goodyear UltraTorque Plus R-1

- Same great design features as UltraTorque Radial
- Extra tall metric version equivalent to standard conventional sizes in overall diameter
- Excellent for applications where vehicle field clearance is maximized

Catalog #	Tire Size	Design	TL/ TT	Load Rating	Inflation Pressure (psi)	Max Load mph	Max Load (lbs)	Recom'd Rim Width* (in)	Tire Width (in)	Overall Diameter (in)	Static Loaded Radius (in)	Rolling Circ. (in)	Flat Plate Area (in ²)	Weight (lbs)	Tread Depth 32nd in.	No. of Lugs
4UT438	380/85R28	UltraTorque	TL	133A8/B	23	30	4,540	13	15	53.4	23.9	160	207	202	48	44
4UT430	380/85R30	UltraTorque	TL	135A8/B	23	30	4,800	13	15.6	55.1	24.8	165	234	194	48	44
4UT435	380/85R34	UltraTorque	TL	137A8/B	23	30	5,080	13	14.7	58.5	26.3	175	263	206	48	48
4UT435	380/85R34	UltraTorque	TL	145A8/B	41	30	6,400	13	14.7	58.5	26.3	175	263	206	48	48
4UTD32	380/90R46	UltraTorque	TL	149A8/B	35	30	7,150	13	15	72.5	33.3	219	281	321	52	56
4UTJ32	380/90R46	UltraTorque	TL	159A8/B	58	30	9,650	13	15	72.5	33.3	219	281	368	52	56
4UT032	380/90R46	UltraTorque	TL	168A8/B	78	30	12,300	13	15	72.5	33.3	219	281	370	52	56
4UT4G7	420/80R46	UltraTorque	TL	151A8/B	35	30	7,600	15	16.5	72.5	33.8	218	310	309	50	56
4UT448	420/85R28	UltraTorque	TL	139A8/B	23	30	5,360	15	17	56.2	25	168	243	204	50	44
4UT479	420/90R30	UltraTorque	TL	142A8/B	23	30	5,840	15	17.5	58.1	26.1	174	292	238	52	46
4UT4CC	420/95R50	UltraTorque	TL	157A8/B	35	30	9,100	15	17.6	80.6	36.4	243	357	398	50	64
4UT477	480/80R38	UltraTorque	TL	149A8/B	23	30	7,150	16	19.8	68.3	30.2	201	323	325	52	52
4UT777	480/80R38	UltraTorque	TL	155A8/B	35	30	8,550	16	19.8	68.3	30.2	201	323	328	52	52
4UT442	480/80R42	UltraTorque	TL	151A8/B	23	30	7,600	16	19.3	71.2	31.9	213	340	342	52	52
4UT547	480/80R46	UltraTorque	TL	158A8/B	35	30	9,350	16	18.9	76.4	34.8	230	354	404	52	56
4UT5H4	480/85R34	UltraTorque	TL	149A8/B	23	30	7,150	15	18.9	65.6	29.3	197	323	303	53	50
4UT589	520/85R38	UltraTorque	TL	155A8/B	23	30	8,550	16	20.3	72.8	32.5	219	384	427	54	52
4UT452	520/85R42	UltraTorque	TL	157A8/B	23	30	9,100	16	20.3	76.5	34.3	230	409	445	54	54
4UT652	520/85R42	UltraTorque	TL	162A8/B	35	30	10,500	16	20.3	76.5	34.3	230	409	469	54	54
4UT752	520/85R42	UltraTorque	TL	170A8/B	52	30	13,200	16	20.3	76.5	34.3	230	409	502	54	54
UFT752	IF520/85R42CF0	UltraTorque	TL	169A8	35	25	12,800	18	21.5	75.1	33.8	225	453	552	54	54
4UP442	480/80R42	UltraTorque Plus	TL	151A8/B	23	30	7,600	16	19.1	72.7	32.6	217	340	368	52	54
4UP542	480/80R42	UltraTorque Plus	TL	154A8/B	29	30	8,250	16	19.1	72.7	32.6	217	340	371	52	54
4UP547	480/80R46	UltraTorque Plus	TL	158A8/B	35	30	9,350	16	18.6	77.2	34.5	230	354	420	52	56

*See Approved Rim Contours section



Goodyear OptiTorque R-1

- Ideal for front position on four-wheel spreaders, flotation options on sprayers and tractors
- Wider lug base promotes longer life and smoother roading
- Wider footprint reduces ground pressure and soil compaction
- Large nose and shoulder design reduce vibration and promote stability

Catalog #	Tire Size	Design	TL/ TT	Load Rating	Inflation Pressure (psi)	Max Load mph	Max Load (lbs)	Recom'd Rim Width* (in)	Tire Width (in)	Overall Diameter (in)	Static Loaded Radius (in)	Rolling Circ. (in)	Flat Plate Area (in ²)	Weight (lbs)	Tread Depth 32nd in.	No. of Lugs
40T451	750/50R26	Optitorque	TL	157D	35	40	9,100	25	28.8	55.3	25	166	415	402	40	36
40T751	750/50R26	Optitorque	TL	165D	52	40	11,400	25	28.8E	55.3E	25E	166E	415E	425	40	36
V0T2TL	VF680/65R38	Optitorque	TL	171D	23	40	13,600	23	26E	72.5E	32.5E	217E	520E	600E	50	44

*See Approved Rim Contours section



Goodyear Ultra Sprayer R-1

- High flex carcass technology/ 20 percent more load at same pressure
- Significant increase in lug surface area for improved lug durability
- Will handle speeds to 40 mph
- Design for sprayers to reduce ground pressure
- Increased lug bracing for high load durability

Catalog #	Tire Size	Design	TL/ TT	Load Rating	Inflation Pressure (psi)	Max Load mph	Max Load (lbs)	Recom'd Rim Width* (in)	Tire Width (in)	Overall Diameter (in)	Static Loaded Radius (in)	Rolling Circ. (in)	Flat Plate Area (in ²)	Weight (lbs)	Tread Depth 32nd in.	No. of Lugs
4US6JM	320/90R42	Ultra Sprayer	TL	150A8/B	61	30	7,400	10	12.8	65.4	29.5	198	184	258	47	54
FUSDJM	IF320/90R42	Ultra Sprayer	TL	157D	64	40	9,100	11	13.3	65.8	29.7	198	235	262	47	54
4US7T5	320/90R46	Ultra Sprayer	TL	156A8/B	70	30	8,800	10	12.5	69.9	30.9	206	200	312	47	56
FUSD75	IF320/90R46	Ultra Sprayer	TL	159D	64	40	9,650	11	12.5	70.1	31.7	211	237	319	47	56
4US8V6	320/90R50	Ultra Sprayer	TL	161A8/B	78	30	10,200	10	12.4	73.6	33	220	235	326	47	60
FUSDV6	IF320/90R50	Ultra Sprayer	TL	161D	64	40	10,200	11	12.4	73.6	32.9	219	248	339	47	60

Radial R-1

Goodyear

Catalog #	Tire Size	Design	TL/TT	Load Rating	Inflation Pressure (psi)	Max Load mph	Max Load (lbs)	Recom'd Rim Width* (in)	Tire Width (in)	Overall Diameter (in)	Static Loaded Radius (in)	Rolling Circ. (in)	Flat Plate Area (in ²)	Weight (lbs)	Tread Depth 32nd in.	No. of Lugs
4US443	320/90R54	Ultra Sprayer	TL	149A8/B	46	30	7,150	10	12.8	77.6	34.5	230	246	316	47	62
FUSD43	IF320/90R54	Ultra Sprayer	TL	162D	64	40	10,500	11	12.7	77.9	35.3	236	259	366	47	62
4US7MN	320/105R54	Ultra Sprayer	TL	166A8/B	75	30	11,700	10	13.2	80.6	35.6	238	282	359	47	64
FUSDMN	IF320/105R54	Ultra Sprayer	TL	167D	64	40	12,000	11	12.9	80.1	35.4	236	270	385	47	64
4US6UT	320/125R54	Ultra Sprayer	TL	168A8/B	70	30	12,300	10	13.1	84	37.6	251	270	484	47	64
4US4M3	380/80R38	Ultra Sprayer	TL	155A8/B	64	30	8,550	12	14.6	62.4	28.2	188	243	267	49	42
FUSDM3	IF380/80R38	Ultra Sprayer	TL	161D	64	40	10,200	13	14.4	62.5	28.1	187	219	222	49	42
4US4RZ	380/80R42	Ultra Sprayer	TL	150A8/B	46	30	7,400	12	14.4	66.6	29.7	198	247	294	49	44
FUSDRZ	IF380/80R42	Ultra Sprayer	TL	163D	64	40	10,700	13	14.4E	66.6E	29.7E	198E	247E	294E	49	44
4USH32	380/90R46	Ultra Sprayer	TL	156A8/B	49	30	8,800	13	15	72.7	32.8	219	280	358	49	50
4US032	380/90R46	Ultra Sprayer	TL	168A8/B	78	30	12,300	13	15	72.7	32.8	219	280	370	49	50
FUSD32	IF380/90R46	Ultra Sprayer	TL	168D	64	40	12,300	13	14.2	72.6	32.7	219	310	376	49	50
VUSD32	VF380/90R46	Ultra Sprayer	TL	173D	64	40	14,300	13	14.2	73	32.7	219	310	376	49	50
GUSV32	VF380/75R50	Ultra Sprayer	TL	170D	64	40	13,200	13	14.6	73	33	220	299	372	49	50
4US7JR	380/90R50	Ultra Sprayer	TL	169A8/B	75	30	12,800	12	14.3	77.1	34.6	230	305	383	49	52
FUSDJR	IF380/90R50	Ultra Sprayer	TL	170D	64	40	13,200	13	14.3	76.9	34.5	230	312	395	49	52
4US9V9	380/90R54	Ultra Sprayer	TL	170A8/B	75	30	13,200	12	14.3	80.9	36	240	280	433	49	56
FUSDV9	IF380/90R54	Ultra Sprayer	TL	171D	64	40	13,600	13	14.4	80.6	36.5	243	321	448	49	56
4US9DT	380/105R50	Ultra Sprayer	TL	170A8/B	70	30	13,200	12	14.3	80.9	36	240	280	458	49	56
FUSDDT	IF380/105R50	Ultra Sprayer	TL	177D	70	40	16,100	13	14.9	80.7	36.1	241	325	470	49	56
VUSDDT	VF380/105R50	Ultra Sprayer	TL	179D	64	40	17,100	13	14.9E	80.7E	36.1E	241E	340E	505	49	56

*See Approved Rim Contours section



Goodyear Dyna Torque Radial R-1

- Reduced vibration in field and road service
- Improved traction from its three-pitch tread design
- Longer body life provided by its natural shape casing

Catalog #	Tire Size	Design	TL/TT	Load Rating	Inflation Pressure (psi)	Max Load mph	Max Load (lbs)	Recom'd Rim Width* (in)	Tire Width (in)	Overall Diameter (in)	Static Loaded Radius (in)	Rolling Circ. (in)	Flat Plate Area (in ²)	Weight (lbs)	Tread Depth 32nd in.	No. of Lugs
4DT4H5	320/85R34	Dyna Torque Radial	TL	132D	46	40	4,400	10	12.6	55.4	25.8	167	90	170	46	60
4DT5H5	320/85R34	Dyna Torque Radial	TL	133A8/B	35	30	4,540	10	12.6	55.4	25.8	167	90	158	46	60
4DT424	340/90R28	Dyna Torque Radial	TL	129A8/B	23	30	4,080	12	14	51.8	23.7	155	158	156	47	54
4DT438	380/85R28	Dyna Torque Radial	TL	133A8/B	23	30	4,540	13	15.2	53.8	23.9	161	184	202	49	54
4DT430	380/85R30	Dyna Torque Radial	TL	135A8/B	23	30	4,800	13	15.2	55.8	24.9	167	191	210	49	54
4DT435	380/85R34	Dyna Torque Radial	TL	137A8/B	23	30	5,080	13	15.2	59.8	26.9	180	203	229	49	60
4DT4H6	385/85R34MPT#	Dyna Torque Radial	TL	141G	36	55	5,680	13	15.2	59.8	26.9	180	158	236	49	60
4DT4H2	380/85R46	Dyna Torque Radial	TL	146D	46	40	6,600	13	15.2	71.8	32.9	217	135	355	49	72
4DT7H2	380/85R46	Dyna Torque Radial	TL	165A8/B	75	30	11,400	13	15.2	71.8	32.9	217	240	370	49	72
4DT5H2	380/85R46	Dyna Torque Radial	TL	147A8/B	35	30	6,800	13	15.2	71.8	32.9	217	240	332	49	72
4DT446	420/85R26	Dyna Torque Radial	TL	138A8/B	23	30	5,200	15	17	54.6	24.3	163	221	225	50	54
4DT448	420/85R28	Dyna Torque Radial	TL	139A8/B	23	30	5,360	15	17.2	56.4	25.4	168	228	243	50	54
4DT479	420/90R30	Dyna Torque Radial	TL	142A8/B	23	30	5,840	15	17.2	58.5	26.2	175	233	255	50	54
4DT5G7	420/80R46	Dyna Torque Radial	TL	159A8/B	52	30	9,650	13	16.5	72.5	33.8	218	310	415	50	80
4DT7G7	420/80R46	Dyna Torque Radial	TL	170A8/B	78	30	13,200	13	16.5	72.5	33.8	218	310	458	50	80
4DT456	480/85R26	Dyna Torque Radial	TL	145A8/B	23	30	6,400	16	19	57.5	25.4	171	262	260	52	48
4DT477	480/80R38	Dyna Torque Radial	TL	149A8/B	23	30	7,150	16	19	69.1	31	208	318	333	52	60
4DT442	480/80R42	Dyna Torque Radial	TL	151A8/B	23	30	7,600	16	18.7	73.3	33.3	221	335	363	52	66
4DT942	480/80R42	Dyna Torque Radial	TL	166A8/B	58	30	11,700	16	18.7	73.3	33.3	221	335	422	52	66
4DT547	480/80R46	Dyna Torque Radial	TL	158A8/B	35	30	9,350	16	18.9	77.1	35	232	344	452	52	72
4DT847	480/80R46	Dyna Torque Radial	TL	174A8/B	73	30	14,800	16	18.9	77.1	35	232	344	499	52	72
4DT489	520/85R38	Dyna Torque Radial	TL	148A8/B	17	30	6,950	18	21.2	72.2	32.4	217	380	403	53	60
4DT589	520/85R38	Dyna Torque Radial	TL	155A8/B	23	30	8,550	18	21.2	72.2	32.4	217	380	422	53	60
4DT889	520/85R38	Dyna Torque Radial	TL	170A8/B	58	30	13,200	18	21.2	72.2	32.4	217	380	478	53	60
4DT452	520/85R42	Dyna Torque Radial	TL	157A8/B	23	30	9,100	18	21.2	76.2	34.2	229	399	433	53	66
4DT6F9	650/75R32	Dyna Torque Radial	TL	172A8/B	46	30	13,900	21	24.9	70.9	30.9	212	461	577	55	54
4DT596	800/65R32	Dyna Torque Radial	TL	172A8/B	35	30	13,900	27	29.8	71.5	31	214	539	647	56	54
4DT796	800/65R32	Dyna Torque Radial	TL	178A8/B	46	30	16,500	27	29.8E	71.5E	31E	214E	539E	672	56	54

*See Approved Rim Contours section

Goodyear

Radial R-1



Goodyear Dyna Torque Radial II R-1

- Minimizes ground disturbance with its wide, flat footprint and deep grooves
- Performance proven as an original equipment tire

Catalog #	Tire Size	Design	TL/TT	Load Rating	Inflation Pressure (psi)	Max Load mph	Max Load (lbs)	Recom'd Rim Width* (in)	Tire Width (in)	Overall Diameter (in)	Static Loaded Radius (in)	Rolling Circ. (in)	Flat Plate Area (in ²)	Weight (lbs)	Tread Depth 32nd in.	No. of Lugs
4RD414	12.4R24	Dyna Torque Radial II	TL	122A8/B	36	30	3,300	11	12.5	45.5	20.9	138	138	118	44	44
48E256	18.4R26	Dyna Torque Radial II	TL	140A8/B	24	30	5,520	16	19.4	57.1	25.1	170	225	287	53	48
48E456	18.4R26	Dyna Torque Radial II	TL	152A8/B	42	30	7,850	16	19.4	57.1	25.1	170	225	314	53	48
4RD450	18.4R30	Dyna Torque Radial II	TL	143A8/B	24	30	6,000	16	19.1	61.1	28.1	183	255	277	50	52
4RD586	23.1R26	Dyna Torque Radial II	TL	156A8/B	28	30	8,800	20	24.1	64.3	28.9	187	380	441	52	48

*See Approved Rim Contours section



DT710



DT730

Goodyear DT710/DT730 R-1

- Smooth riding rear farm tire
- Patented tread design of interlocking center lugs reduces ride disturbance
- Provides unmatched performance in dry land conditions where R-1 tires are recommended
- Better traction, improved ride, longer wear and less fuel consumption than any bias ply tire



VERSA TORQUE R-1

Goodyear Versa Torque R-1

- Bi-directional design for optimal performance in either direction
- Excellent ride and handling supplied by the high center contact area tread pattern
- Multiple lug pattern offers large increase in traction edges for excellent traction
- Also known as Versa Torque DT717

Catalog #	Tire Size	Design	TL/TT	Load Rating	Inflation Pressure (psi)	Max Load mph	Max Load (lbs)	Recom'd Rim Width* (in)	Tire Width (in)	Overall Diameter (in)	Static Loaded Radius (in)	Rolling Circ. (in)	Flat Plate Area (in ²)	Weight (lbs)	Tread Depth 32nd in.	No. of Lugs
4T7405	290/95R34	DT730	TL	131A8/B	35	30	4,300	10	11.1	55.4	25.4	167	153	132	37	64
471AF4	320/75R24	DT710	TL	118A8/B	23	30	2910	10	12.3	43.4	19.3	130	134	126	37	40
471124	13.6R28#	DT710	TL	1*	18	30	2,830	12	14	51.8	23.7	155	158	171	40	42
471324	13.6R28#	DT710	TL	3*	30	30	3,740	12	14	51.8	23.7	155	158	178	40	42
471334	14.9R24	DT710	TL	3*	30	30	4,180	13	15.7	49.8	22.2	149	172	196	41	38
471341	16.9R38	DT710	TL	3*	30	30	6400	15	18.1	66.5	29.9	200	262	189	45	40
4VT4G0	440/80R28#	Versa Torque	TL	140A8/B	23	30	5,520	15	18.1	56.5	24.9	169	128	278	45	40
471154	18.4R34	DT710	TL	1*	18	30	5360	16	19.4	65.2	28.6	196	300	274	46	46
4VT5H4	480/85R34	Versa Torque	TL	149A8/B	23	30	7,150	15	19.5	65.7	29.3	197	300	313	52	46
471350	18.4R30#	DT710	TL	1*	18	30	4,940	16	19.4	61.2	26.6	171	262	253	46	44
471177	18.4R38	DT710	TL	1*	18	30	5680	16	19.4	69.2	30.6	208	318	308	46	48

*See Approved Rim Contours section
#Minimum Quantity Order

Bias R-1

Goodyear



Goodyear Dura Torque R-1

- Excellent roadability provided by the overlapping center lugs
- Traction in a wide range of sizes due to its long bar design
- Long wear and durability from its braced lug design
- Easy lug cleanability



Goodyear Power Torque R-1

- Established tread design for tough service



Goodyear Traction Sure Grip R-1

- Straight 45 degree lugs for even, steady pull
- Open center permits deep sharp bite assuring efficient self-cleaning action



Goodyear Traction Torque R-1

- Zig zag lugs for strength
- Large lug head for wear

Catalog #	Tire Size	Design	TL/TT	Load Rating	Inflation Pressure (psi)	Max Load mph	Max Load (lbs)	Recom'd Rim Width* (in)	Tire Width (in)	Overall Diameter (in)	Static Loaded Radius (in)	Rolling Circ. (in)	Flat Plate Area (in ²)	Weight (lbs)	Tread Depth 32nd in.	No. of Lugs
42P3C3	6-12	Power Torque	TL	4	28	20	600	5	6	22.8	10.7	68	24	18	19	30
42P833	7.2-16	Power Torque	TL	8	52	25	1,230	6	7.3	29.5	12.9	86	23	30	34	30
4TG611	7.2-30	Traction Sure Grip	TL	6	38	25	1,430	6	7.2	42	20.3	126	64	61	34	42
4DQ665	7-14	Dura Torque	TL	6	36	20	990	6	7	27.1	12.5	81	43	28	32	30
4DQ666	7-16	Dura Torque	TL	6	36	20	1,100	6	7.4	29.1	13.5	87	49	32	32	32
4DQ667	8-16	Dura Torque	TL	6	28	20	1,360	6	7.9	31.3	14.1	91	80	39	35	30
42P651	8.3-16	Power Torque	TL	6	34	25	1,200	7	8.1	31.5	14.1	94	54	36	34	30
47Q684	8.3-24	Dura Torque	TT	6	34	25	1,610	7	8.4	39	18.4	117	56	47	35	38
4DQ684	8.3-24	Dura Torque	TL	6	34	25	1,610	7	8.4	39	18.4	117	56	52	35	38
4DQ695	9.5-16	Dura Torque	TL	6	30	25	1,390	8	9.4	33.2	15.3	99	55	50	36	30
42P695	9.5-16	Power Torque	TL	6	30	25	1,390	8	9.4	33.3	15.3	100	56	51	40	30
47Q694	9.5-24	Dura Torque	TT	6	30	25	1,870	8	9.4	41.2	19.2	123	73	56	36	38
4DQ694	9.5-24	Dura Torque	TL	6	30	25	1,870	8	9.4	41.2	19.2	123	73	69	36	38
4DQ633	9.5-42	Dura Torque	TL	6	30	25	2,400	8	9.4	59.2	28.1	176	96	110	36	54
4DQ404	11.2-24	Dura Torque	TL	4	18	25	1,650	10	11.3	43.2	20.2	129	93	88	38	34
4DQ604	11.2-24	Dura Torque	TL	6	26	25	2,090	10	11.3	43.2	20.2	129	93	86	38	34
47Q410	11.2-28	Dura Torque	TT	4	18	25	1,760	10	11.3	47.4	22.3	141	99	79	38	38
4Q2408	11.2-38	Dura Torque I	TL	4	18	25	2,090	10	11.3	57.4	27.3	171	115	115	38	46
4DQ408	11.2-38	Dura Torque	TL	4	18	25	2,090	10	11.3	57.4	27.3	171	115	118	36	46
4DQ608	11.2-38	Dura Torque	TL	6	26	25	2,540	10	11.3	57.4	27.3	171	115	131	38	46
4TT408	11.2-38	Traction Torque	TL	4	18	25	2,090	10	11.5	57.7	25.8	172	132	112	36	44
4DQ414	12.4-24	Dura Torque	TL	4	16	25	1,870	11	12.4	45.5	21.1	136	117	109	40	34
47Q414	12.4-24	Dura Torque	TT	4	16	25	1,870	11	12.4	45.5	21.1	136	117	106	40	34
4DQ814	12.4-24	Dura Torque	TL	8	32	25	2,830	11	12.4	45.5	21.1	136	117	115	40	34
4Q2814	12.4-24	Dura Torque I	TL	8	32	25	2,830	11	12.4	45.5	21.1	136	117	115	40	34
47Q814	12.4-24	Dura Torque	TT	8	32	25	2,830	11	12.4	45.5	21.1	136	117	110	40	34
47Q412	12.4-28	Dura Torque	TT	4	16	25	1,980	11	12.4	49.5	23.2	148	125	103	40	38
4DQ812	12.4-28	Dura Torque	TL	8	32	25	3,000	11	12.4	49.5	23.2	148	148	116	40	38
47Q618	12.4-38	Dura Torque	TT	6	24	25	2,910	11	12.4	59.5	28.2	177	145	125	40	46
4DQ018	12.4-38	Dura Torque	TL	10	40	25	3,960	11	12.4	59.5	28.2	177	145	151	40	46
4DQ619	12.4-42	Dura Torque	TL	6	24	25	3,080	10	11.9	63.5	29.8	189	152	161	39	50

Goodyear

Bias R-1

Catalog #	Tire Size	Design	TL/TT	Load Rating	Inflation Pressure (psi)	Max Load mph	Max Load (lbs)	Recom'd Rim Width* (in)	Tire Width (in)	Overall Diameter (in)	Static Loaded Radius (in)	Rolling Circ. (in)	Flat Plate Area (in ²)	Weight (lbs)	Tread Depth 32nd in.	No. of Lugs
4DQ019	12.4-42	Dura Torque	TL	10	40	25	4,180	10	11.9	63.5	29.8	189	152	176	39	50
47Q624	13.6-28	Dura Torque	TT	6	22	25	2,830	12	13.5	51.5	24	154	156	114	42	38
4DQ624	13.6-28	Dura Torque	TL	6	22	25	2,830	12	13.5	51.5	24	154	156	123	42	38
4DQ628	13.6-38	Dura Torque	TL	6	22	25	3,300	12	13.5	61.5	29	183	181	156	42	46
47Q628	13.6-38	Dura Torque	TT	6	22	25	3,300	12	13.5	61.5	29	183	181	155	42	46
4DQ434	14.9-24#	Dura Torque	TL	4	12	25	2,200	13	14.9	49.7	22.7	148	150	143	44	38
47Q634	14.9-24	Dura Torque	TT	6	20	25	3,000	13	14.9	49.7	22.7	148	150	140	44	38
4DQ634	14.9-24	Dura Torque	TL	6	20	25	3,000	13	14.9	49.7	22.7	148	150	143	44	38
4DQ834	14.9-24	Dura Torque	TL	8	26	25	3,520	13	14.9	49.7	22.7	148	150	150	44	38
47Q638	14.9-28	Dura Torque	TT	6	20	25	3,200	13	14.9	54.3	25	162	160	129	44	38
4DQ638	14.9-28	Dura Torque	TL	6	20	25	3,200	13	14.9	54.3	25	162	160	148	44	38
47Q674	15.5-38	Dura Torque	TT	6	20	25	3,520	14	15.6	62.2	28.8	186	175	183	47	44
47Q874	15.5-38	Dura Torque	TT	8	26	25	4,080	14	15.6	62.2	28.8	186	175	178	47	44
4DQ874	15.5-38	Dura Torque	TL	8	26	25	4,080	14	15.6	62.2	28.8	186	175	180	47	44
4DQ874	15.5-38	Dura Torque	TL	8	26	25	4,080	14	15.6	62.2	28.8	186	175	180	47	44
4DQ645	16.9-24	Dura Torque	TL	6	18	25	3,420	15	17.2	52.4	23.8	156	190	173	50	38
47Q645	16.9-24	Dura Torque	TT	6	18	25	3,420	15	17.2	52.4	23.8	156	190	165	50	38
4DQ648	16.9-28	Dura Torque	TL	6	18	25	3,640	15	17.2	56.4	25.7	168	202	199	50	40
4DQ679	16.9-30	Dura Torque	TL	6	18	25	3,740	15	17.2	58.4	26.8	175	209	203	50	42
47Q679	16.9-30	Dura Torque	TT	6	18	25	3,740	15	17.2	58.4	26.8	175	209	183	50	42
4TG690	18.4-16.1	Traction Sure Grip	TL	6	16	25	2,540	16	19.1	45	19.9	132	158	150	50	32
4DQ650	18.4-30	Dura Torque	TL	6	16	25	4,180	16	18.8	61.1	27.6	182	263	253	52	42
47Q850	18.4-30	Dura Torque	TT	8	20	25	4,800	16	18.8	61.1	27.6	182	263	218	52	42
4DQ850	18.4-30	Dura Torque	TL	8	20	25	4,800	16	18.8	61.1	27.6	182	263	235	52	42
47Q854	18.4-34	Dura Torque	TT	8	20	25	5,080	16	18.8	65.1	29.6	194	279	239	52	44
47Q877	18.4-38	Dura Torque	TT	8	20	25	5,360	16	18.8	69.1	32.1	205	295	266	52	46

*See Approved Rim Contours section
#Minimum Quantity Order



Goodyear Dyna Torque II R-1

- Reduce vibration in the field from its long bar/short bar design
- Excellent roadability
- Maximum traction provided by the increased lug count



Goodyear Dyna Torque III R-1

- Long bar/short bar for reduced vibration
- Excellent roadability
- Maximum traction

Catalog #	Tire Size	Design	TL/TT	Load Rating	Inflation Pressure (psi)	Max Load mph	Max Load (lbs)	Recom'd Rim Width* (in)	Tire Width (in)	Overall Diameter (in)	Static Loaded Radius (in)	Rolling Circ. (in)	Flat Plate Area (in ²)	Weight (lbs)	Tread Depth 32nd in.	No. of Lugs
42D382	7-12	Dyna Torque II	TL	4	24	20	715	6	6.8	24	11.3	73	33	20	23	40
42D682	7-12	Dyna Torque II	TL	6	36	20	910	6	6.8	24	11.3	73	33	20	23	40
42D385	11.2-16	Dyna Torque II	TL	4	18	25	1,280	10	11.8	35.5	16.2	106	71	60	44	40
427604	11.2-24	Dyna Torque II	TT	6	26	25	2,090	10	11.4	43.2	20.2	129	98	85	44	48
427412	12.4-28	Dyna Torque II	TT	4	16	25	1,980	11	12.4	49.5	23.2	148	125	96	40	52
4D3318	12.4-38	Dyna Torque III	TL	14	56	25	4,800	11	12.4	59.5	28.2	177	145	180	40	60
427822	13.6-24	Dyna Torque II	TT	8	28	25	3,080	12	13.9	47.9	22	143	146	106	47	48
42D822	13.6-24	Dyna Torque II	TL	8	28	25	3,080	12	13.9	47.9	22	143	146	118	47	48
42D024	13.6-28	Dyna Torque II	TL	10	36	25	3,740	12	13.8	51.9	24.2	155	156	153	47	52
42D634	14.9-24	Dyna Torque II	TL	6	20	25	3,000	13	14.9	49.8	22.5	149	150	136	49	48
42D834	14.9-24	Dyna Torque II	TL	8	26	25	3,520	13	14.9	49.8	22.5	149	150	140	49	48
42D031	14.9-26	Dyna Torque II	TL	10	32	25	4,080	13	14.8	52.5	24.2	156	155	187	49	52
427438	14.9-28#	Dyna Torque II	TT	4	12	25	2,340	13	14.9	54.3	25	162	160	129	49	52
42D038	14.9-28	Dyna Torque II	TL	10	32	25	4,180	13	14.9	54.3	25	162	160	169	49	52
427674	15.5-38	Dyna Torque II	TT	6	20	25	3,520	14	15.6	62.2	28.8	186	175	162	47	56
427645	16.9-24	Dyna Torque II	TT	6	18	25	3,420	15	17.5	52.7	24.3	157	190	145	50	44
42D645	16.9-24	Dyna Torque II	TL	6	18	25	3,420	15	17.5	52.7	24.3	157	190	176	50	44
42D046	16.9-26	Dyna Torque II	TL	10	28	25	4,540	15	17.4	54.8	25.2	163	196	214	49	52

#Minimum Quantity Order

Bias R-1

Goodyear

Catalog #	Tire Size	Design	TL/TT	Load Rating	Inflation Pressure (psi)	Max Load mph	Max Load (lbs)	Recom'd Rim Width* (in)	Tire Width (in)	Overall Diameter (in)	Static Loaded Radius (in)	Rolling Circ. (in)	Flat Plate Area (in ²)	Weight (lbs)	Tread Depth 32nd in.	No. of Lugs
427648	16.9-28	Dyna Torque II	TT	6	18	25	3,640	15	17.4	56.8	26.2	169	202	168	50	52
42D048	16.9-28	Dyna Torque II	TL	10	28	25	4,680	15	17.4	56.8	26.2	169	202	214	50	52
427679	16.9-30	Dyna Torque II	TT	6	18	25	3,740	15	16.9	58.8	26.8	174	209	173	50	48
427644	16.9-34	Dyna Torque II	TT	6	18	25	3,960	15	16.9	62.5	28.2	186	222	197	50	52
427820	16.9-38	Dyna Torque II	TT	8	24	25	4,940	15	17.1	66.6	30.7	198	235	232	50	56
427320	16.9-38	Dyna Torque II	TL	14	40	25	6,800	15	17.1	66.6	30.7	198	235	266	50	56
42D656	18.4-26	Dyna Torque II	TL	6	16	25	3,960	16	19	57.1	26.1	170	246	228	52	44
42D056	18.4-26	Dyna Torque II	TL	10	26	25	5,200	16	19	57.1	26.1	170	246	247	52	44
4DQ156	18.4-26	Dyna Torque II	TL	12	32	25	5,840	16	19	57.1	26.1	170	246	249	52	44
427850	18.4-30	Dyna Torque II	TT	8	20	25	4,800	16	18.9	61.7	27.9	184	263	215	52	48
427654	18.4-34#	Dyna Torque II	TT	6	16	25	4,400	16	18.8	65.4	29.7	195	279	236	52	52
427854	18.4-34	Dyna Torque II	TT	8	20	25	5,080	16	18.8	65.4	29.7	195	279	250	52	52
427054	18.4-34#	Dyna Torque II	TT	10	26	25	6,000	16	18.8	65.4	29.7	195	279	261	52	52
427877	18.4-38	Dyna Torque II	TT	8	20	25	5,360	16	18.9	69.7	32.3	207	295	256	52	56
427377	18.4-38	Dyna Torque II	TL	14	36	25	7,600	16	18.9	69.7	32.3	207	295	311	52	56
427077	18.4-38	Dyna Torque II	TT	10	26	25	6,400	16	18.9	69.7	32.3	207	295	278	52	56
427042	18.4-42	Dyna Torque II	TT	10	26	25	6,600	16	18.9	73.7	34.3	216	310	317	52	64
427801	20.8-34	Dyna Torque II	TT	8	18	25	5,840	18	21.3	68.6	31	204	322	290	53	52
427889	20.8-38	Dyna Torque II	TT	8	18	25	6,150	18	21.1	72.3	32.8	215	341	315	53	56
42D389	20.8-38	Dyna Torque II	TL	14	32	25	8,550	18	21.1	72.3	32.8	215	341	398	53	56
427089	20.8-38	Dyna Torque II	TT	10	22	25	6,950	18	21.1	72.3	32.8	215	341	332	53	56
42D052	20.8-42	Dyna Torque II	TL	10	22	25	7,400	18	21.4	76.4	35.1	227	359	419	53	60
42D352	20.8-42	Dyna Torque II	TL	14	32	25	9,100	18	21.4	76.4	35.1	227	359	419	53	60
42D186	23.1-26	Dyna Torque II	TL	12	24	25	7,150	20	23.7	64.5	28.7	191	359	374	54	44
427182	23.1-30#	Dyna Torque II	TT	12	24	25	7,600	20	23.7	67.8	30.5	201	343	335	54	44
427888	23.1-34	Dyna Torque II	TT	8	16	25	6,400	20	23.7	70.8	32.1	211	364	367	54	48
42D199	24.5-32	Dyna Torque II	TL	12	24	25	8,800	21	25.3	71.8	32.4	213	363	456	55	48
42D198	28L-26	Dyna Torque II	TL	12	20	25	7,400	25	28.5	64	28.3	190	373	429	58	40
42D398	28L-26	Dyna Torque II	TL	14	24	25	8,250	25	28.5	64	28.3	190	373	448	58	40
42D398	28L-26	Dyna Torque II	TL	14	24	25	8,250	25	28.5	64	28.3	190	373	448	58	40
42D196	30.5L-32	Dyna Torque II	TL	12	20	25	9,350	27	31.1	71.4	32.3	212	468	585	56	48
42D396	30.5L-32	Dyna Torque II	TL	14	22	25	9,900	27	31.1	71.4	32.3	212	468	619	56	48
42D596	30.5L-32#	Dyna Torque II	TL	16	26	25	11,000	27	31.1	71.4	32.3	212	468	628	56	48

*See Approved Rim Contours section
#Minimum Quantity Order



Goodyear Harvest Torque R-1

- Premium design specifically for combines
- Increased lugs give excellent roadability

Catalog #	Tire Size	Design	TL/TT	Load Rating	Inflation Pressure (psi)	Max Load mph	Max Load (lbs)	Recom'd Rim Width* (in)	Tire Width (in)	Overall Diameter (in)	Static Loaded Radius (in)	Rolling Circ. (in)	Flat Plate Area (in ²)	Weight (lbs)	Tread Depth 32nd in.	No. of Lugs
4HB396#	30.5L-32	Harvest Torque	TL	14	22	25	9,900	27	30.5	71.6	32.3	212	468	619	56	50

*See Approved Rim Contours section
#Minimum Quantity Order



Goodyear Traction Irrigation 3 R-1

- Wrap around lug shape for full tire gripping action
- Open tread for cleaning
- Round tire shape to reduce crop and soil damage

Catalog #	Tire Size	Design	TL/TT	Load Rating	Inflation Pressure (psi)	Max Load mph	Max Load (lbs)	Recom'd Rim Width* (in)	Tire Width (in)	Overall Diameter (in)	Static Loaded Radius (in)	Rolling Circ. (in)	Flat Plate Area (in ²)	Weight (lbs)	Tread Depth 32nd in.	No. of Lugs
4TS404	11.2-24	Traction Irrigation 3	TL	4	18	25	1,650	10	11	41.5	19.2	124	93	55	31	34
4TS434	14.9-24#	Traction Irrigation 3	TL	4	12	25	2,200	13	14.7	48.5	22	144	150	98	39	38

*See Approved Rim Contours section
#Minimum Quantity Order

Goodyear

Radial R-1W

Super Traction Radial



Goodyear Super Traction R-1W

- Self-cleaning tread action promoted by 45 degree tread lug angles
- Up to 25% deeper than conventional R-1 tires
- For applications in heavy, wet soil conditions

Catalog #	Tire Size	Design	TL/ TT	Load Rating	Inflation Pressure (psi)	Max Load mph	Max Load (lbs)	Recom'd Rim Width* (in)	Tire Width (in)	Overall Diameter (in)	Static Loaded Radius (in)	Rolling Circ. (in)	Flat Plate Area (in ²)	Weight (lbs)	Tread Depth 32nd in.	No. of Lugs
4T04JE	250/90R38	Super Traction Radial	TL	132A8/B	52	30	4,400	8	9.9	55.7	26	168	138	139	52	44
4T04KF	250/95R34**	Super Traction Radial	TL	119A8/B	23	30	3,000	8	9.9	53.1	24.4	160	133	126	55	42
4T04KG	250/95R50**	Super Traction Radial	TL	137A8/B	46	30	5,080	8	9.9	68.5	32.4	207	167	162	55	54
4T04KH	250/95R54	Super Traction Radial	TL	141A8/B	52	30	5,680	8	9.9	72.3	34.2	219	172	209	55	56
4T07V1	290/90R38	Super Traction Radial	TL	138A8/B	46	30	5,200	9	11.4	58.9	27.2	177	153	181	57	44
4T04J1	290/90R42	Super Traction Radial	TL	140A8/B	46	30	5,520	9	11.4	61.9	28.8	187	162	192	57	46
4T08V2	320/80R42	Super Traction Radial	TL	141A8/B	46	30	5,680	10	12.6	61.9	28.8	187	177	214	55	44
FT09V2	IF320/80R42	Super Traction Radial	TL	149D	49	40	7,150	10	11.7	62.4	28.2	188	205	223	55	44
4T04HL	320/85R34	Super Traction Radial	TL	133A8/B	35	30	4,540	10	12.6	55.9	25.8	168	177	183	57	38
4T0545	320/85R38	Super Traction Radial	TL	143A8/B	52	30	6,000	10	12.6	58.8	27.2	177	162	193	57	42
4T0645	320/85R38	Super Traction Radial	TL	152A8/B	73	30	7,850	10	12.6	58.8	27.2	177	162	219	57	42
4T04T5	320/90R46	Super Traction Radial	TL	148A8/B	52	30	6,950	10	12.6	68.6	31.8	207	190	264	52	52
4T05T5	320/90R46	Super Traction Radial	TL	153A8/B	64	30	8,050	10	12.6	68.6	31.8	207	190	282	52	52
4T07T5	320/90R46	Super Traction Radial	TL	156A8/B	70	30	8,800	10	12.6	68.6	31.8	207	190	290	55	52
4T0443	320/90R54	Super Traction Radial	TL	149A8/B	46	30	7,150	10	12.6	76.2	35.7	230	213	287	58	56
4T0HC1	320/90R72.5	Super Traction Radial	TL	162A8/B	64	30	10,500	10	12.6	94.7	44.9	286	162	456	58	70
4T07MN	320/105R54	Super Traction Radial	TL	166A8/B	75	30	11,700	10	13.6	80.3	37.7	242	239	343	58	60
FT07MN	IF320/105R54	Super Traction Radial	TL	167D	64	40	12,000	10	13.6E	80.3E	37.7E	242E	239E	350E	58	60
4T07M3	380/80R38	Super Traction Radial	TL	142A8/B	35	30	5,840	12	15	62.2	28.6	187	231	243	60	40
FT08M3	IF380/80R38	Super Traction Radial	TL	149D	35	40	7,150	12	15E	62.2E	28.6E	187E	231E	282	60	40
4T04HP	380/85R34	Super Traction Radial	TL	137A8/B	23	30	5,080	13	15	58.9	26.9	177	226	229	60	38
4T06HP	380/85R34	Super Traction Radial	TL	155A8/B	64	30	8,550	13	15	58.9	26.9	177	226	279	60	38
4T07V9	380/90R54	Super Traction Radial	TL	152A8/B	35	30	7,850	12	15	80.4	37.3	243	305	378	61	50
4T09V9	380/90R54	Super Traction Radial	TL	170A8/B	75	30	13,200	12	15	80.4	37.3	243	305	429	61	50
4TRB30	14.9R30	Super Traction Radial	TL	134A8/B	30	30	4,680	13	15.2	54.9	25	165	191	209	61	36
4TR445	16.9R24	Super Traction Radial	TL	134A8/B	24	30	4,680	15	17.7	51.8	22	154	206	203	62	34
4TR748	16.9R28	Super Traction Radial	TL	136A8/B	24	30	4,940	15	17.6	56.1	25.2	168	228	251	62	38
4TR479	16.9R30	Super Traction Radial	TL	144A8/B	35	30	6,150	15	17.6	57.9	26.2	173	233	264	62	40
4TR7M4	420/85R34	Super Traction Radial	TL	147A8/B	35	30	6,800	15	16.6	62	28.1	186	183	306	62	40
4TR256	18.4R26	Super Traction Radial	TL	140A8/B	24	30	5,520	16	19.2	56.8	25.1	170	262	264	64	38
4T1440	480/70R30	Super Traction Radial	TL	152A8/B	46	30	7,850	15	18.9	58.4	26	175	264	294	62	36
4T15M5	480/70R34	Super Traction Radial	TL	146A8/B	29	30	6,600	15	19.2	62.2	27.9	187	273	346	62	38
4T16M5	480/70R34	Super Traction Radial	TL	155A8/B	46	30	8,550	15	19.2	62.2	27.9	187	273	363	62	38
4TR777	18.4R38	Super Traction Radial	TL	146A8/B	24	30	6,600	16	19.2	68.7	31.1	205	318	333	64	42
4TR742	18.4R42	Super Traction Radial	TL	148A8/B	24	30	6,950	16	18.4	72.1	32.9	217	335	389	64	46
4TR842	18.4R42	Super Traction Radial	TL	153A8/B	30	30	8,050	16	18.4	72.1	32.9	217	335	401	64	46
4TR547	480/80R46	Super Traction Radial	TL	158A8/B	35	30	9,350	16	18.9	76.5	34.8	230	354	446	64	48
4TR647	480/80R46	Super Traction Radial	TL	168A8/B	58	30	12,300	16	18.9	76.5	34.8	230	354	355	64	48
4TR751	480/80R50	Super Traction Radial	TL	159A8/B	35	30	9,650	15	19	80.7	37.1	243	361	481	64	50
4TR851	480/80R50	Super Traction Radial	TL	165A8/B	46	30	11,400	15	19	80.7	37.1	243	361	506	64	50
4TR951	480/80R50	Super Traction Radial	TL	176A8/B	73	30	15,700	15	19	80.7	37.1	243	361	530	64	50
FTR951	IF480/80R50	Super Traction Radial	TL	178D	64	40	16,500	16	18.2	80.8	36.5	243	404	590	64	50
4TR789	20.8R38	Super Traction Radial	TL	153A8/B	24	30	8,050	18	21.6	72.2	32.5	216	380	467	72	40
4TR452	520/85R42	Super Traction Radial	TL	157A8/B	23	30	9,100	18	21.6	76.2	34.5	228	399	501	72	42
4TR652	520/85R42	Super Traction Radial	TL	162A8/B	35	30	10,500	18	21.6	76.2	34.5	228	399	530	72	42
4TR771	520/85R46	Super Traction Radial	TL	158A8/B	23	30	9,350	16	21.3	80.6	36.3	242	439	538	72	44
4TR971	520/85R46	Super Traction Radial	TL	169A8/B	46	30	12,800	16	21.3	80.6	36.3	242	439	600	72	44
4TR698	28LR26	Super Traction Radial	TL	169A8/B	42	30	12,800	25	28.2	63.2	28.6	189	500	532	78	34
4T24D8	540/65R30	Super Traction Radial	TL	150A8/B	35	30	7,400	16	20.9	57.6	25.4	173	281	330	58	42

**Minimum Quantity Order

Radial R-1W

Goodyear

Catalog #	Tire Size	Design	TL/ TT	Load Rating	Inflation Pressure (psi)	Max Load mph	Max Load (lbs)	Recom'd Rim Width* (in)	Tire Width (in)	Overall Diameter (in)	Static Loaded Radius (in)	Rolling Circ. (in)	Flat Plate Area (in ²)	Weight (lbs)	Tread Depth 32nd in.	No. of Lugs
4T2865	600/65R28	Super Traction Radial	TL	154A8/B	35	30	8,250	18	23.3	58.7	26.5	175	325	379	64	38
4T27M6	600/70R30	Super Traction Radial	TL	152A8/B	23	30	7,850	20	24.1	63.1	27.7	188	357	426	59	40
4T2770	620/70R42	Super Traction Radial	TL	160A8/B	23	30	9,900	20	24.6	76.7	34.5	230	465	587	66	42
4H2770	620/70R42	Super Traction Radial HD	TL	166A8/B	35	30	11,700	20	24.6	76.7	34.5	230	465	628	66	42
4H2970	620/70R42	Super Traction Radial HD	TL	172A8/B	46	30	13,900	20	24.6	76.7	34.5	230	465	613	66	42
4T2781	620/70R46	Super Traction Radial	TL	162A8/B	23	30	10,500	20	24.6	80.7	36.4	243	473	595	71	44
4T2881	620/70R46	Super Traction Radial	TL	167A8/B	35	30	12,000	20	24.6	80.7	36.4	243	473	611	71	44
4T2981	620/70R46	Super Traction Radial	TL	176A8/B	55	30	15,700	20	24.6	80.7	36.4	243	473	659	71	44
4T25FB	620/75R26	Super Traction Radial	TL	166A8/B	46	30	11,700	20	23.9	62.8	28	188	374	460	72	34
4T26FT	620/75R34	Super Traction Radial	TL	170A8/B	46	30	13,200	20	24.6	70.6	31.2	211	400	520	71	40
4T27DT	650/65R42	Super Traction Radial	TL	170A8/B	46	30	13,200	20	23.8	75.3	33.7	225	375	640	68	46
4T27FU	650/75R32	Super Traction Radial	TL	172A8/B	46	30	13,900	21	24.9	70.9	30.9	212	461	638	74	38
4T26FV	650/75R34	Super Traction Radial	TL	162A8/B	23	30	10,500	20	26.8	72.6	31.5	217	473	536	68	40
4T27HA	650/85R38	Super Traction Radial	TL	173A8/B	35	30	14,300	20	25.6	80.7	35.5	241	490	578	71	44
4T2769	710/70R38	Super Traction Radial	TL	166A8/B	23	30	11,700	23	28	76	33.7	228	490	695	73	38
4H2869	710/70R38	Super Traction Radial HD	TL	171A8/B	35	30	13,600	23	28	76	33.7	228	490	725	73	38
4T2791	710/70R42	Super Traction Radial	TL	168A8/B	23	30	12,300	23	28	81	36.2	243	572	703	73	40
4H2491	710/70R42	Super Traction Radial HD	TL	173A8/B	35	30	14,300	23	28.2	81.1	36.2	243	572	800	73	40
4TR596	800/65R32	Super Traction Radial	TL	172A8/B	35	30	13,900	27	30.1	71.5	31.8	214	539	741	75	36
4TR696	800/65R32	Super Traction Radial	TL	175A8/B	41	30	15,200	27	30.1	71.5	31.8	214	539	684	75	36
4T27M8	800/70R38	Super Traction Radial	TL	173A8/B	23	30	14,300	25	31.4	81.1	35.7	242	647	945	77	38
4H29M8	800/70R38	Super Traction Radial HD	TL	181A8/B	41	30	18,200	25	31.4	81.1	35.7	242	647	980	77	38
4T27G1	850/80R38	Super Traction Radial	TL	180A8/B	23	30	17,600	28	32.6	89.4	39.1	265	785	1232	87	38
GT28G1	#850/75R42	Super Traction Radial	TL	185A8/B	35	30	20,400	28	32.6	89.4	39.1	265	785	1232	87	38

*See Approved Rim Contours section



Goodyear Optitrac R-1W

- Self-cleaning tread action promoted by 45 degree tread lug angles
- Up to 25% deeper than conventional R-1 tires
- For applications in heavy, wet soil conditions
- New lug and carcass shape for better durability and ride

Catalog #	Tire Size	Design	TL/TT	Load Rating	Inflation Pressure (psi)	Max Load mph	Max Load (lbs)	Recom'd Rim Width* (in)	Tire Width (in)	Overall Diameter (in)	Static Loaded Radius (in)	Rolling Circ. (in)	Flat Plate Area (in ²)	Weight (lbs)	Tread Depth 32nd in.	No. of Lugs
40P214	320/85R24	Optitrac	TL	122A8/B	23	30	3,300	10	12.5	45.3	20.4	136	153	112	48	36
4T04JM	320/90R42	Optitrac	TL	139A8/B	35	30	5,360	10	12.9	65.3	30.3	202	192	205	58	46
4T05JM	320/90R42	Optitrac	TL	147A8/B	52	30	6,800	10	12.6	65.4	30.1	197	187	236	58	46
4T07V6	320/90R50	Optitrac	TL	148A8/B	46	30	6,950	10	12.6	72.6	33.8	219	195	284	52	56
4T08V6	320/90R50	Optitrac	TL	161A8/B	78	30	10,200	10	12.6	72.6	33.8	219	195	313	52	56
4T04UT	320/125R54	Optitrac	TL	155A8/B	41	30	8,550	10	13.4	83.6	37.4	250	331	na	58	62
4T04RZ	380/80R42	Optitrac	TL	150A8/B	46	30	7,400	12	14.2	66.1	29.7	198	277	295	59	42
FT04JW	IF380/90R42	Optitrac	TL	154D	35	40	8,250	12	14.8	69.1	31.1	208	331	304	60	46
4T04JQ	380/90R46	Optitrac	TL	149A8/B	35	30	7,150	13	15	72.7	33.5	219	281	300	61	46
4T06JQ	380/90R46**	Optitrac	TL	159A8/B	58	30	9,650	13	15	72.7	33.5	219	281	332	61	46
4T04JR	380/90R50	Optitrac	TL	151A8/B	35	30	7,600	12	15	76.3	35.4	230	288	349	62	48
4T06JR	380/90R50	Optitrac	TL	166A8/B	70	30	11,700	12	15	76.3	35.4	230	288	398	62	48
FT06JR	IF380/90R50	Optitrac	TL	166D	55	40	11,700	12	15E	76.3E	35.4E	230E	288E	410E	62	48
VT04AZ	VF380/95R38	Optitrac	TL	154D	23	40	8,250	13	14.5	65.8	30.1	201	324	298	59	42
D12445	420/70R24#	Optitrac	TL	130A8/B	23	30	4,180	13	16.5	49	22	147	201	185	56	36
40P251	460/85R30	Optitrac	TL	145A8/B	23	30	6,400	15	18.7	60.7	27	180	320	273	58	38
D12440	480/70R30	Optitrac	TL	152A8/B	46	30	7,850	15	18.9	58.4	26	175	264	321	64	40
D125M5	480/70R34	Optitrac	TL	146A8/B	29	30	6,600	15	19.2	62.2	27.9	187	273	316	64	42
D126M5	480/70R34	Optitrac	TL	155A8/B	46	30	8,550	15	19.2	62.2	27.9	187	273	334	64	42
4T04C1	420/90R30	Optitrac	TL	147A8/B	35	30	6,800	13	16.6	57.9	26.1	174	279	272	62	38
D067M4	420/85R34	Optitrac	TL	147A8/B	35	30	6,800	13	17.4	62.3	27.9	186	262	306	62	42

**Minimum Quantity Order

Goodyear

Radial R-1W

Catalog #	Tire Size	Design	TL/TT	Load Rating	Inflation Pressure (psi)	Max Load mph	Max Load (lbs)	Recom'd Rim Width* (in)	Tire Width (in)	Overall Diameter (in)	Static Loaded Radius (in)	Rolling Circ. (in)	Flat Plate Area (in ²)	Weight (lbs)	Tread Depth 32nd in.	No. of Lugs
D06568	420/85R38	Optitrac	TL	149A8/B	35	30	7,150	13	16.9	66.5	29.9	199	300	299	63	44
4T0562	480/95R50	Optitrac	TL	164A8/B	35	30	11,000	15	19.6	84.6	37.9	252	396	592	64	54
4T05PJ	480/95R54	Optitrac	TL	166A8/B	35	30	11,700	16	19.8	89.4	39.7	265	496	587	64	56
FT05PJ	IF480/95R54	Optitrac	TL	167D	23	40	12,000	16	19.4	89.1	39.6	264	500	601	64	56
D12589	520/70R38	Optitrac	TL	150A8/B	23	30	7,400	16	20.4	68.9	30.8	207	190E	395	64	42
D06652	520/85R42	Optitrac	TL	162A8/B	35	30	10,500	16	21.6E	76.2E	34.5E	228E	399E	515E	72	42
4HP752	IF520/85R42CF0	Optitrac	TL	169A8	35	25	12,800	18	21.1	75.9	34.1	227	475	595	72	42
D064RB	520/85R50	Optitrac	TL	165A8/B	35	30	11,400	16	20.3	83	37.4	250	453	611	65	46
D18475	540/65R24	Optitrac	TL	146A8/B	35	30	6,600	16	20.9	51.8	22.8	154	280	271	63	38
D185DA	540/65R34	Optitrac	TL	152A8/B	35	30	7,850	16	20.9	61.7	27	185	305	360	63	42
D245FA	540/75R34	Optitrac	TL	157A8/B	35	30	9,100	18	22.6	65.2	29.3	195	370	416	66	42
D064D4	580/85R42	Optitrac	TL	166A8/B	29	30	11,700	18	24	79.7	35.4	236	487	601	68	44
4HP6D4	IF580/85R42CF0	Optitrac	TL	178A8	41	25	16,500	18	23.4	80.8	36.1	241	615	717	68	44
D24865	600/65R28	Optitrac	TL	154A8/B	35	30	8,250	20	23.5	59.8	27.1	181	304	373	64	38
D24965	600/65R28	Optitrac	TL	160A8/B	46	30	9,900	20	24.3	58.8	26	175	298	378	64	38
D247C3	600/70R28	Optitrac	TL	161A8/B	41	30	10,200	18	23.5	61.5	27.9	186	320	434	64	36
VOPKC3	VF600/70R28CF0	Optitrac	TL	173D	41	30	14,300	18	22.8	60.7	27.1	181	591	485	64	36
D247M6	600/70R30	Optitrac	TL	152A8/B	23	30	7,850	20	23.4	63.6	28.5	190	521	423	66	38
D245FB	620/75R26	Optitrac	TL	166A8/B	46	30	11,700	20	23.8	65.2	28.0	187	419	460	72	36
D247FC	620/75R30	Optitrac	TL	163A8/B	35	30	10,700	20	23.4	67.3	30.4	200	313	596	74	38
D248FC	620/75R30	Optitrac	TL	169A8/B	46	30	12,800	20	23.4	67.3	30.4	200	313	601	74	38
D12770	620/70R42	Optitrac	TL	166A8/B	35	30	11,700	20	23.9	76.1	35.6	230	441	603	66	44
D12881	620/70R46	Optitrac	TL	167A8/B	35	30	12,000	20	24.6	80.7	36.4	243	470	640	71	46
40P5DD	650/65R38	Optitrac	TL	166D	41	40	11,700	20	25.7E	72.4E	32.4E	217E	450E	509E	72	44
D246FW	650/75R38	Optitrac	TL	169A8/B	35	30	12,800	21	25.8	76.4	34	228	437	678	76	38
D247HA	650/85R38	Optitrac	TL	173A8/B	35	30	14,300	21	25.8	81.2	35.8	242	490	739	76	40
D247DA	650/85R42	Optitrac	TL	174A8/B	35	30	14,800	20	27.5	84.2	38	251	550	800	76	42
40P269	710/70R38	Optitrac	TL	166D	23	40	11,700	23	28.2	76.5	34.3	228	464	749	78	40
40P469	710/70R38	Optitrac	TL	171D	35	40	13,600	23	28.2	76.5	34.3	228	464	778	78	40
D24969	710/70R38	Optitrac	TL	179A8/B	52	30	17,100	23	28.2	76.5	34.3	228	464	836	78	40
D24491	710/70R42	Optitrac	TL	173A8/B	35	30	14,300	23	28.2	80.4	36	241	490	774	78	42
D24891	710/70R42	Optitrac	TL	179A8/B	46	30	17,100	23	28.2	80.4	36	241	490	795	78	42
4HP891	IF710/70R42CF0	Optitrac	TL	179A8	35	25	17,100	25	28.5	81.1	34.6	242	838	871	78	42
4T36N6	750/65R26	Optitrac	TL	166A8/B	35	30	11,700	25	30	64	29	191	510	681	65	34
VT36N6	VF750/65R26	Optitrac	TL	177D	35	40	16,100	25	29.6	66.1	28.5	194	452	658	65	34
4T30M8	800/70R38	Optitrac	TL	173A8/B	23	30	14,300	25	32.5	80.2	36.6	238	728	916	77	44
4HP9M8	IF800/70R38CF0	Optitrac	TL	184A8	35	25	19,800	27	32.1	81.5	36.5	227	765	930E	77	44
4HP5M8	IF800/70R38CF0	Optitrac	TL	190A8	46	25	23,400	27	32.1	81.5	36.5	227	765	992	77	44
4T37R7	800/70R42	Optitrac	TL	179A8/B	35	30	17,100	25	32.6	85.7	39.1	258	606	995	77	46
4HP5T3	IF850/60R26CF0	Optitrac	TL	179A8	41	25	17,100	30	33.4E	66.1E	28.0E	193E	700E	890E	69	36
4T37G1	850/80R38	Optitrac	TL	180A8/B	23	30	17,600	28	33.5	89	40.9	269	775	1158	87	42
GT38G1	850/75R42	Optitrac	TL	185A8/B	35	30	20,400	28	33.5	89	40.9	269	775	1158	87	42
GHP8G1	IF850/75R42CF0	Optitrac	TL	186A8	23	25	20,900	28	33.5	90.6	38.7	269	1064	1232	87	42
4T34A2	900/50R42	Optitrac	TL	168A8/B	23	30	12,300	27	34.9	76.6	34.4	230	564	948	61	36
4T34C2	900/60R32	Optitrac	TL	176A8/B	35	30	15,700	30	36.2	76.1	33.4	226	709	809	71	44
4T36C2	900/60R32	Optitrac	TL	185A8/B	58	30	20,400	30	36.2	76.1	33.4	226	709	837	71	44
4HP7C2	IF900/60R32CF0	Optitrac	TL	188A8	46	25	22,000	30	36.4	75.9	33.7	225	914	913	71	44

**Minimum Quantity Order

Radial R-1W

Goodyear

Catalog #	Tire Size	Design	TL/TT	Load Rating	Inflation Pressure (psi)	Max Load mph	Max Load (lbs)	Recom'd Rim Width* (in)	Tire Width (in)	Overall Diameter (in)	Static Loaded Radius (in)	Rolling Circ. (in)	Flat Plate Area (in ²)	Weight (lbs)	Tread Depth 32nd in.	No. of Lugs
4T3BB1	900/70R32	Optitrac	TL	182A8/B	35	30	18,700	27	34.8E	81.6E	35.1E	243	659E	NA	71	44
4T37C4	900/75R32	Optitrac	TL	184A8/B	35	30	19,800	30	36.3	85.2	38.5	253	840	1062	71	50

**Minimum Quantity Order



Goodyear Optiterra Radial R-1W

- New Radial shape to improved performance
- New Tread design for better wear and traction
- All the lug features of the Goodyear OPTITRAC
- Increased lug bracing for high load durability

Catalog #	Tire Size	Design	TL/TT	Load Rating	Inflation Pressure (psi)	Max Load mph	Max Load (lbs)	Recom'd Rim Width* (in)	Tire Width (in)	Overall Diameter (in)	Static Loaded Radius (in)	Rolling Circ. (in)	Flat Plate Area (in ²)	Weight (lbs)	Tread Depth 32nd in.	No. of Lugs
XPT5F3	1000/50R25	OPTITERRA	TL	172A8/B	35	30	13,900	36	40.9	65.1	30	195	694	910	79	36
XPT543	1050/50R32	OPTITERRA	TL	178A8/B	35	30	16,500	36	42	74.8	33.9	223	866	900	85	40

*See Approved Rim Contours section




Goodyear DT900 R-1W

- Developed for high clearance with the row crop market in mind and features a deeper tread than an R-1 tire for improved traction

Catalog #	Tire Size	Design	TL/TT	Load Rating	Inflation Pressure (psi)	Max Load mph	Max Load (lbs)	Recom'd Rim Width* (in)	Tire Width (in)	Overall Diameter (in)	Static Loaded Radius (in)	Rolling Circ. (in)	Flat Plate Area (in ²)	Weight (lbs)	Tread Depth 32nd in.	No. of Lugs
49V7N3	230/95R32	DT900	TL	140A8/B	84	30	5,520	7	9.1	50.2	23.2	150	97	117	54	54

*See Approved Rim Contours section



Goodyear DT924 R-1W

- Self-cleaning tread action promoted by 45 degree tread lug angles
- Up to 25% deeper than conventional R-1 tires
- Extra wide flotation sizes for super traction

Catalog #	Tire Size	Design	TL/TT	Load Rating	Inflation Pressure (psi)	Max Load mph	Max Load (lbs)	Recom'd Rim Width* (in)	Tire Width (in)	Overall Diameter (in)	Static Loaded Radius (in)	Rolling Circ. (in)	Flat Plate Area (in ²)	Weight (lbs)	Tread Depth 32nd in.	No. of Lugs
4D4765	600/65R28	DT924	TL	147A8/B	23	30	6,800	18	22.4	59.2	26.6	177	340	390	69	36
49M7M8	800/70R38	DT924	TL	173A8/B	23	30	14,300	25	31	82.1	36.9	246	647E	901	74	42

*See Approved Rim Contours section

Goodyear

Radial R-2



Goodyear Custom Flo Grip Radial R-2

- New Radial shape to improved performance
- New Deep Tread design for better wear and traction in mud
- Will handle speeds to 30 mph
- All the lug features of the Goodyear original Custom Flo Grip for cleaning
- Increased lug bracing for high load durability

Catalog #	Tire Size	Design	TL/ TT	Load Rating	Inflation Pressure (psi)	Max Load mph	Max Load (lbs)	Recom'd Rim Width* (in)	Tire Width (in)	Overall Diameter (in)	Static Loaded Radius (in)	Rolling Circ. (in)	Flat Plate Area (in ²)	Weight (lbs)	Tread Depth 32nd in.	No. of Lugs
XFG5T3	IF850/60R26CF0	Custom Flo Grip	TL	179A8	41	25	17,100	30	33.9	65.5	29.2	190	713	891	111	28

*See Approved Rim Contours section



Goodyear Special Sure Grip Radial TD8 R-2

- Twice the tread depth of conventional R-1 tires
- Extra bite in soft, moist soil provided by open-faced tread design
- Extra lug bracing provides durability and strength

Catalog #	Tire Size	Design	TL/TT	Load Rating	Inflation Pressure (psi)	Max Load mph	Max Load (lbs)	Recom'd Rim Width* (in)	Tire Width (in)	Overall Diameter (in)	Static Loaded Radius (in)	Rolling Circ. (in)	Flat Plate Area (in ²)	Weight (lbs)	Tread Depth 32nd in.	No. of Lugs
4TD7V8	320/90R46	Special Sure Grip TD8 Radial	TL	148A8/B	52	30	6,950	10	12.6	70.8	32.6	213	190	296	86	48
4TD4H1	340/85R46	Special Sure Grip TD8 Radial	TL	140A8/B	29	30	5,520	12	13.6	70.8	32.8	213	203	260	84	44
4TD448	420/85R28	Special Sure Grip TD8 Radial	TL	139A8/B	23	30	5,360	15	16.9	58.2	26.5	173	228	270	86	34
4TD479	420/90R30	Special Sure Grip TD8 Radial	TL	142A8/B	23	30	5,840	15	17.2	58.9	26.6	177	273	308	86	36
4TD4M5	480/70R34	Special Sure Grip TD8 Radial	TL	146A8/B	29	30	6,600	15	18.9	63.9	29	190	273	376	91	32
4TD6M5	480/70R34	Special Sure Grip TD8 Radial	TL	155A8/B	46	30	8,550	15	18.9	63.9	29	190	273	400	91	32
4TD450	480/85R30	Special Sure Grip TD8 Radial	TL	147A8/B	23	30	6,800	15	18.9	63.9	29	190	305	373	91	32
4TD650	480/85R30#	Special Sure Grip TD8 Radial	TL	156A8/B	41	30	8,800	15	18.9	63.9	29	190	305	396	91	32
4TD477	480/80R38	Special Sure Grip TD8 Radial	TL	149A8/B	23	30	7,150	16	18.4	71.2	32.3	212	318	400	99	36
4TD442	480/80R42	Special Sure Grip TD8 Radial	TL	151A8/B	23	30	7,600	16	18.4	75	34.4	225	335	425	92	38
4TD547	480/80R46	Special Sure Grip TD8 Radial	TL	158A8/B	35	30	9,350	16	18.4	77.9	36	238	344	468	92	40
4TD751	480/80R50	Special Sure Grip TD8 Radial	TL	159A8/B	35	30	9,650	16	18.2	80.7	36.2	241	375	532	92	36
4TD589	520/85R38	Special Sure Grip TD8 Radial	TL	155A8/B	23	30	8,550	18	21.7	74.5	33.6	222	380	510	108	36
4TD452	520/85R42	Special Sure Grip TD8 Radial	TL	157A8/B	23	30	9,100	16	20.8	77.9	36	234	399	571	98	36
4TD652	520/85R42	Special Sure Grip TD8 Radial	TL	162A8/B	35	30	10,700	16	20.8	77.9	36	234	399	591	98	36
4TD752	520/85R42#	Special Sure Grip TD8 Radial	TL	165A8/B	41	30	11,400	16	20.8	77.9	36	234	399	607	98	36
FTD752	IF520/85R42CF0	Special Sure Grip TD8 Radial	TL	169A8	35	25	12,800	18	20.6	77.4	34.6	231	490	663	98	36
4TD771	520/85R46	Special Sure Grip TD8 Radial	TL	158A8/B	23	30	9,350	16	20.3	83.3	37.4	249	439	617	108	36
4TD971	520/85R46	Special Sure Grip TD8 Radial	TL	169A8/B	46	30	12,800	16	20.3	83.3	37.4	249	439	656	108	36
4TD698	710/65R26	Special Sure Grip TD8 Radial	TL	169A8/B	49	30	12,800	25	28.5	64.9	29	193	563	592	98	28
VTD798	VF710/65R26	Special Sure Grip TD 8 Radial	TL	177D	41	40	16,100	25	27.9	66.0	29.2	192	629	625	91	28
FTD7Y1	IF900/65R32CF0	Special Sure Grip TD8 Radial	TL	185A8	35	25	20,400	30	35	79.8	35.8E	238E	806E	1201	126	28
FTD8Y1	IF900/65R32CF0	Special Sure Grip TD8 Radial	TL	191A8	46	25	24,000	30	35.6	79.6	35.8	238	806	1245	126	28

Minimum Quantity Order

Bias R-2

Goodyear



Goodyear Special Sure Grip TD8 R-2

- Designed for cotton pickers

Catalog #	Tire Size	Design	TL/TT	Load Rating	Inflation Pressure (psi)	Max Load mph	Max Load (lbs)	Recom'd Rim Width* (in)	Tire Width (in)	Overall Diameter (in)	Static Loaded Radius (in)	Rolling Circ. (in)	Flat Plate Area (in ²)	Weight (lbs)	Tread Depth 32nd in.	No. of Lugs
4D8634	14.9-24	Special Sure Grip TD8	TL	6	20	25	3,000	13	15.5	51.4	23.1	154	173	197	88	32
48D134	14.9-24	Special Sure Grip TD8	TL	12	38	25	4,400	13	15.5	51.4	23.1	154	173	219	88	32
4D7874	15.5-38#	Special Sure Grip TD8	TT	8	26	25	4,080	14	15.8	64.8	30	194	172	192	85	36
4D8656	18.4-26	Special Sure Grip TD8	TL	6	16	25	3,960	16	18.4	58.6	26.2	175	236	246	99	30
4D8056	18.4-26	Special Sure Grip TD8	TL	10	26	25	5,200	16	18.4	58.6	26.2	175	236	284	99	30
4D8650	18.4-30#	Special Sure Grip TD8	TL	6	16	25	4,180	16	18.4	62.6	28.2	187	277	290	99	32
4D8050	18.4-30	Special Sure Grip TD8	TL	10	26	25	5,520	16	18.4	62.6	28.2	187	277	331	99	32
4D8877	18.4-38	Special Sure Grip TD8	TL	8	20	25	5,360	16	18.4	70.6	32.2	211	300	348	99	36
4D8889	20.8-38	Special Sure Grip TD8	TL	8	18	25	6,150	18	20.8	73.8	33.5	220	385	417	108	36
4D8352	20.8-42#	Special Sure Grip TD8	TL	14	32	25	9,100	18	20.8	78.2	35.7	233	395	478	98	36
4D8086	23.1-26	Special Sure Grip TD8	TL	10	20	25	6,400	20	23	64.6	28.4	192	291	403	108	28
4D8186	23.1-26	Special Sure Grip TD8	TL	12	24	25	7,100	20	23	64.6	28.4	192	291	427	108	28
4D8198	28L-26	Special Sure Grip TD8	TL	12	20	25	7,400	25	27.9	64.7	28.5	193	408	521	112	28
4D8598	28L-26#	Special Sure Grip TD8	TL	16	28	25	9,100	25	27.9	64.7	28.5	193	408	544	112	28
4D8396	30.5L-32	Special Sure Grip TD8	TL	14	22	25	9,900	27	30.4	72.7	32.9	216	500	765	118	32

*See Approved Rim Contours section



Goodyear Special Sure Grip

- Designed for cotton pickers

Catalog #	Tire Size	Design	TL/TT	Load Rating	Inflation Pressure (psi)	Max Load mph	Max Load (lbs)	Recom'd Rim Width* (in)	Tire Width (in)	Overall Diameter (in)	Static Loaded Radius (in)	Rolling Circ. (in)	Flat Plate Area (in ²)	Weight (lbs)	Tread Depth 32nd in.	No. of Lugs
4D8173	380/95D38	Special Sure Grip	TL	12	45	25	11,400	13	14.5	66.4	30.9	198	241	261	62	42
4DW7KR	DW500/95D32	Special Sure Grip	TL	169A5/162A8	25	15	12,800	13	19.6	72.4	32.3	216	415	448	67	40
4VA7KT	VA500/95D32	Special Sure Grip	TL	186A5/179A8	60	15	20,900	13	19.6	72.4	32.3	216	415	514	67	40
FKW4BB	IF580/80R34CFO	Special Sure Grip Radial	TL	175A8	46	25	15,200	20	23.2	69.9	31.3	209	480	552	71	38

Goodyear

Radial R-3



Goodyear All Weather Radial R-3

- Longer wearing, increased fuel efficiencies
- Increased hillside stability
- Diamond tread design for minimal soil disruption
- High traction in loose, sandy soil provided by the large tread area
- Ideal for golf courses, parks, citrus groves and highway mowing



Goodyear All Weather Radial II R-3

- This rugged tire minimizes ground disturbance with a button tread pattern that offers good performance on vibratory rollers and combine applications

Catalog #	Tire Size	Design	TL/TT	Load Rating	Inflation Pressure (psi)	Max Load mph	Max Load (lbs)	Recom'd Rim Width* (in)	Tire Width (in)	Overall Diameter (in)	Static Loaded Radius (in)	Rolling Circ. (in)	Flat Plate Area (in ²)	Weight (lbs)	Tread Depth 32nd in.
4AW456	480/80R26	All Weather Radial	TL	149A8/B	35	30	7,150	16	19	56.7	24.7	170	276	235	28
AW2677	480/80R38	All Weather Radial II	TL	152A8/B	29	30	7,850	16	19.3	68.3	30.7	203	442	330	31
AW2877	480/80R38#	All Weather Radial II	TL	164A8/B	58	30	11,000	16	19.3	68.3	30.7	203	442	376	31
4AW486	580/70R26	All Weather Radial	TL	149A8/B	23	30	7,150	20	22.7	58.7	25.4	176	335	276	21
4AW586	580/70R26#	All Weather Radial	TL	155A8/B	35	30	8,550	20	22.7	58.7	25.4	176	335	303	21
4AWA86	580/70R26	All Weather Radial	TL	160A8/B	46	30	9,900	20	22.7	58.7	25.4	176	335	315	21
4R5286	23.1R26	All Weather Radial II	TL	153A8/B	24	30	8,050	20	24.6	60.6	27.3	179	245	410	35

*See Approved Rim Contours section
Minimum Quantity Order

Goodyear

Bias R-3



ALL WEATHER



SFT105

Goodyear All Weather R-3

- Longer wearing, increased fuel efficiencies
- Increased hillside stability
- Diamond tread design for minimal soil disruption
- High traction in loose, sandy soil provided by the large tread area
- Ideal for golf courses, parks, citrus groves and highway mowing

Goodyear SFT105 R-3

- Minimum soil disturbance
- Lower ground pressures
- Specially designed for turf applications



SMOOTH



SOFTTRAC II

Goodyear Smooth R-3

- Specialty service tire used on paving equipment and rollers
- Compounded to reduce material sticking

Goodyear Softrac II R-3

- Good flotation due to the wide, flat tread
- Minimal ground disruption provided by its button tread design
- Dependable traction on or off the road

Catalog #	Tire Size	Design	TL/TT	Load Rating	Inflation Pressure (psi)	Max Load mph	Max Load (lbs)	Recom'd Rim Width* (in)	Tire Width (in)	Overall Diameter (in)	Static Loaded Radius (in)	Rolling Circ. (in)	Flat Plate Area (in ²)	Weight (lbs)	Tread Depth 32nd in.
4A7495	9.5-16#	All Weather	TT	4	20	25	1,100	8	9.7	31.9	14.6	95	53	39	15
4AW695	9.5-16	All Weather	TL	6	30	25	1,390	8	9.7	31.9	14.6	95	53	40	15
4AW895	9.5-16	All Weather	TL	8	40	25	1,650	8	9.7	31.9	14.6	95	53	45	15
4A7494	9.5-24	All Weather	TT	4	20	25	1,480	8	9.3	39.5	18.2	117	74	48	18
4AW494	9.5-24	All Weather	TL	4	20	25	1,480	8	9.3	39.5	18.2	117	74	52	18

Bias R-3

Goodyear

Catalog #	Tire Size	Design	TL/TT	Load Rating	Inflation Pressure (psi)	Max Load mph	Max Load (lbs)	Recom'd Rim Width* (in)	Tire Width (in)	Overall Diameter (in)	Static Loaded Radius (in)	Rolling Circ. (in)	Flat Plate Area (in ²)	Weight (lbs)	Tread Depth 32nd in.
4SF604	11.2-24	SFT105	TL	6	26	25	2,090	10	11.3	42.5	19.9	126	93	75	20
4AW381	13.6-16.1	All Weather	TL	8	28	25	2,340	11	14.1	39	17.5	115	100	85	23
4A7624	13.6-28	All Weather	TT	6	22	25	2,830	12	13.9	51.5	23.1	152	160	101	23
4AW634	14.9-24	All Weather	TL	6	20	25	3,000	13	15.5	49.3	22.1	145	157	119	23
4AW834	14.9-24	All Weather	TL	8	26	25	3,520	13	15.4	49.7	22.6	151	153	127	23
4FS3M2	16.5L-16.1SL	SofTrac II	TL	6	18	30	2,340	14	16.6	40.3	17.1	109	176	119	20
4FS3L1	16.5L-16.1	SofTrac II	TL	14	48	30	6,400	14	16.6	40.3	17.1	109	176	135	20
4AW645	16.9-24	All Weather	TL	6	18	25	3,420	15	17.4	51.1	22.9	151	196	131	26
4SF679	16.9-30	SFT105	TL	6	18	25	3,740	15	17.2	57.5	26.1	170	213	179	26
3SC679	16.9-30	Smooth	TL	6	18	25	3,740	15	18	57.6	26.1	169	213	178	0
4AW890	18.4-16.1	All Weather	TL	8	20	25	2,910	16	18.7	43.5	19.4	128	135	134	29
4AW156	18.4-26	All Weather	TL	12	32	25	5,840	16	19.1	55.7	24.5	164	224	203	28
4FS061	19.5L-24	SofTrac II	TL	10	24	25	4,680	16	19.3	51.7	23.1	153	206	177	27
4FS349	21.5L-16.1SL	SofTrac II	TL	10	22	30	3,860	18	20.9	44.5	18.7	119	211	196	30
4FS3A9	21.5L-16.1SL	SofTrac II	TL	6	12	30	2,760	18	20.9	44.5	18.7	119	211	187	30
4FS362	21.5L-16.1SL	SofTrac II	TL	14	30	30	4,680	18	20.9	44.5	18.7	119	220	196	30
4AW886	23.1-26	All Weather	TL	8	16	25	5,680	20	22.9	58.8	26	173	394	272	21
4AW086	23.1-26	All Weather	TL	10	20	25	6,400	20	22.9	58.8	26	173	394	297	21
4AW186	23.1-26	All Weather	TL	12	24	25	7,150	20	22.9	58.8	26	173	394	299	21
4AWD86	23.1-26	All Weather	TL	16	34	25	8,800	20	22.9	58.8	26	173	394	324	21
4FS2J3	24x13.00-12NHS	SofTrac II	TL	4	18	30	1,755	10.5	12.8	23.3	10.5	66	122	25	8
4AW199	24.5-32	All Weather	TL	12	24	25	8,800	21	24.4	67.4	30.1	199	327	428	32
4AW598	28L-26	All Weather	TL	16	28	25	9,100	25	29.1	62.2	27.7	184	443	441	30
4FS4D9	560/65D24	SofTrac II	TL	140A8/B	23	30	5,520	18	22.3	52	23.1	153	228	254	27
4AW396	30.5L-32	All Weather	TL	14	22	25	9,900	27	30.1	69.7	30.5	206	564	487	37
4AW196	30.5L-32	All Weather	TL	12	20	25	9,350	27	30.1	69.7	30.5	206	564	492	37
4VA596	VA30.5L32#	All Weather	TL	16	26	25	11,000	27	30.1	69.7	30.5	206	564	538	37
4VAC96	VA30.5L32	All Weather	TL	24	38	25	13,600	27	30.1	69.7	30.5	206	564	585	37

*See Approved Rim Contours section
Minimum Quantity Order

Goodyear

Radial R-4



IT510



IT520



IT525



IT530

Goodyear IT510 Radial R-4

- Maximum traction supplied by additional biting edges from the overlapping lug/block pattern
- Flotation and traction provided by a larger contact patch
- Industrial use applications

Goodyear IT520 Radial R-4

- Outstanding soft soil traction
- Reinforced lugs for deeper grip and extended wear
- Industrial use applications

Goodyear IT525 Radial R-4

- Solid performance on rock-hard ground
- Increased wear and performance on hard surfaces
- Excellent traction in soft soils

Goodyear IT530 Radial R-4

- Excellent hard soil traction
- High puncture resistance
- Refined road comfort

Catalog #	Tire Size	Design	TL/TT	Load Rating	Inflation Pressure (psi)	Max Load mph	Max Load (lbs)	Recom'd Rim Width* (in)	Tire Width (in)	Overall Diameter (in)	Static Loaded Radius (in)	Rolling Circ. (in)	Flat Plate Area (in ²)	Weight (lbs)	Tread Depth 32nd in.	No. of Lugs
451461	19.5LR24**	IT510	TL	152A8/B	38	30	7,850	16	18.7	51.9	22.8	156	225	218	33	34
452661	500/70R24	IT520	TL	157A8/B	46	30	9,100	16	19.2	51.3	22.9	155	297	251	44	38
4L2661GY#	500/70R24	IT520	TL	157A8/B	46	30	9,100	16	19.2	51.3	22.9	155	297	247	44	38
453661	500/70R24	IT530	TL	157A8/B	46	30	9,100	16	19.5	51.6	23	154	227	241	34	50
45R464	500/85R24**	IT525	TL	171A8/B	61	30	13,600	16	18.4	54	24.5	163	273	300	34	38
452464	500/85R24	IT520	TL	171A8/B	61	30	13,600	16	19.5	55.8	25	166	288	304	44	38
453675	540/70R24**	IT530	TL	161A8/B	46	30	10,200	18	21.7	53.8	23.9	161	235	296	36	36

*See Approved Rim Contours section

** Minimum Quantity Order

Bias R-4

Goodyear



INDUSTRIAL SURE GRIP



SURE GRIP LUG



IT515



IT525

Goodyear Industrial Sure Grip R-4

- Reinforced lugs for industrial use
- Aggressive tread design

Goodyear Sure Grip Lug R-4

- Good choice for industrial equipment
- Good traction and long wear provided by the wide, sturdy overlapping lugs

Goodyear IT515 HS R-4

- Designed for backhoe/loader operations
- More lugs for improved puncture resistance
- Better durability provided by the natural shaped carcass

Goodyear IT525 R-4

- Solid performance on rock-hard ground
- Increased wear and performance on hard surfaces

Catalog #	Tire Size	Design	TL/TT	Load Rating	Inflation Pressure (psi)	Max Load mph	Max Load (lbs)	Recom'd Rim Width* (in)	Tire Width (in)	Overall Diameter (in)	Static Loaded Radius (in)	Rolling Circ. (in)	Flat Plate Area (in ²)	Weight (lbs)	Tread Depth 32nd in.	No. of Lugs
4GL483	12.4-16	Sure Grip Lug	TL	4	20	25	2,070	11	12.8	36.9	16.7	110	95	84	30	46
5G1634	14.9-24	Industrial Sure Grip	TL	6	20	25	3,000	13	15	48.9	22.4	145	140	130	32	44
45T834	14.9-24	IT525	TL	8	30	25	5,080	13	15	48.9	22.4	145	140	133	32	44
45T134	14.9-24	IT525	TL	12	42	25	6,400	13	15	48.9	22.4	145	140	145	32	44
45T845	16.9-24	IT525	TL	8	28	25	5,840	15	16.9	51	23	151	194	149	33	40
45T045	16.9-24	IT525	TL	10	32	25	6,400	15	16.9	51	23	151	194	162	33	40
45T145	16.9-24	IT525	TL	12	38	25	7,150	15	16.9	51	23	151	194	163	33	40
45T848	16.9-28	IT525	TL	8	28	25	6,150	15	16.9	55.5	25.1	165	223	177	33	44
45T048	16.9-28	IT525	TL	10	32	25	6,800	15	16.9	55.6	24.5	163	216	192	33	44
45T148	16.9-28	IT525	TL	12	38	25	7,600	15	16.9	55.5	25.1	165	223	193	33	44
45T803	17.5L-24	IT525	TL	8	26	25	5,360	15	17.4	48.6	21.9	144	192	151	32	40
45T003	17.5L-24	IT525	TL	10	32	25	6,150	15	17.4	48.6	21.9	144	192	165	32	40
45T164	18.4-24	IT525	TL	12	36	25	8,250	16	18.4	54.1	24.2	160	246	194	34	40
5G1158	18.4-28	Industrial Sure Grip	TL	12	36	25	8,800	16	18.8	58.1	26.2	172	256	231	35	40
45T061	19.5L-24	IT525	TL	10	28	25	6,600	16	19	52	23.7	154	206	202	34	38
45T161	19.5L-24	IT525	TL	12	34	25	7,600	16	19	52	23.7	154	206	209	34	38
45T361	19.5L-24#	IT525	TL	14	38	25	8,250	16	19	52	23.7	154	238	221	34	38
4H5161	19.5L-24	IT515 Hard Surface	TL	12	34	25	7,600	16	20.2	52.5	23.7	156	208	232	34	38
45T075	21L-24	IT525	TL	10	26	25	7,400	18	20.8	54.2	24.3	160	238	255	34	36
45T175	21L-24	IT525	TL	12	32	25	8,550	18	20.8	54.2	24.3	160	238	257	34	36
45T575	21L-24	IT525	TL	16	40	25	9,900	18	20.8	54.2	24.3	160	238	277	34	36
45T376	21L-28	IT525	TL	14	36	25	9,900	18	21	58.2	26.4	172	260	310	34	38

*See Approved Rim Contours section
Minimum Quantity Order

Goodyear

Bias F-1



Goodyear Single Rib F-1

- Easy steering in soft soil
- Designed for use in soggy/moist areas

Catalog #	Tire Size	Design	TL/TT	Load Rating	Inflation Pressure (psi)	Max Load mph	Max Load (lbs)	Recom'd Rim Width* (in)	Tire Width (in)	Overall Diameter (in)	Static Loaded Radius (in)	Rolling Circ. (in)	Flat Plate Area (in ²)	Weight (lbs)	Tread Depth 32nd in.
SRT274	6.00-16SL	Single Rib	TT	4	36	25	910	4	6.7	29.7	13.6	89	14	21	NA

*See Approved Rim Contours section

Goodyear

Bias F-2/F-2M



TRIPLE RIB RS



TRIPLE RIB HD

Goodyear Triple Rib RS F-2

- 3 rib design provides excellent steering capabilities

Goodyear Triple Rib HD F-2

- Improved steering in loose, cultivated soil provided by the deep, wide center ribs
- 3 rib design provides excellent steering capabilities
- Excellent wear characteristics from the even load distribution on the center and shoulder ribs



SUPER RIB



HI RIB

Goodyear Super Rib F-2

- Wide center and shoulder ribs
- Increased resistance to puncture from thorns and stubble
- Resists stubble and bruise damage
- Improved steering control in the field

Goodyear Hi Rib F-2

- Wide center and shoulder ribs
- Increased resistance to puncture from thorns and stubble
- Improved steering control



FOUR RIB



DYNA RIB

Goodyear Four Rib F-2M

- Four rib design
- Improved performance at an economical price

Goodyear Dyna Rib F-2M

- Excellent flotation and mobility from four-rib design
- Excellent roadability
- Tubeless construction

Catalog #	Tire Size	Design	TL/TT	Load Rating	Inflation Pressure (psi)	Max Load mph	Max Load (lbs)	Recom'd Rim Width* (in)	Tire Width (in)	Overall Diameter (in)	Static Loaded Radius (in)	Rolling Circ. (in)	Flat Plate Area (in ²)	Weight (lbs)	Tread Depth 32nd in.
TRR230	4.00-15SL	Triple Rib RS	TT	4	52	25	585	3	4.6	24.1	11.6	74	17	12	NA
TRR233	4.00-19SL	Triple Rib RS	TT	4	52	25	715	3	4.4	28.3	13.6	87	19	14	NA
TRR235	5.00-15SL	Triple Rib RS	TT	4	44	25	715	3	5.3	25.6	12.1	77	25	14	NA
TRD239	5.50-16SL	Triple Rib HD	TT	6	56	25	1,050	4	6	27.8	13	83	29	17	14
TRD275	6.00-16SL	Triple Rib HD	TT	6	52	25	1,140	4	6.3	28.8	13.3	85	36	21	14

Bias F-2/F-2M

Goodyear

Catalog #	Tire Size	Design	TL/TT	Load Rating	Inflation Pressure (psi)	Max Load mph	Max Load (lbs)	Recom'd Rim Width* (in)	Tire Width (in)	Overall Diameter (in)	Static Loaded Radius (in)	Rolling Circ. (in)	Flat Plate Area (in ²)	Weight (lbs)	Tread Depth 32nd in.
TRD281	6.50-16SL	Triple Rib HD	TT	6	48	25	1,230	4.5	6.9	30	13.9	89	41	26	18
TRD381	6.50-16SL	Triple Rib HD	TL	6	48	25	1,230	4.5	6.9	30	13.9	89	41	30	18
TRD283	7.50-16SL	Triple Rib HD	TT	6	44	25	1,480	5.5	8.4	32.4	15.1	96	48	32	18
TRD383	7.50-16SL	Triple Rib HD	TL	6	44	25	1,480	5.5	8.4	32.4	15.1	96	48	37	18
TRD284	7.50-16SL	Triple Rib HD	TT	8	56	25	1,710	5.5	8.4	32.4	15.1	96	48	34	18
44R283	7.50-16SL	Four Rib	TT	6	44	25	1,480	5.5	8	31.8	15.1	96	34	30	15
TRD278	7.50-18SL	Triple Rib HD	TT	6	44	25	1,610	5.5	8.4	34.4	16.1	103	52	39	18
TRD290	7.5L-15SL	Triple Rib HD	TT	6	44	25	1,430	6	8.2	29.3	13.4	85.5	33	23	17
TRD244	9.5L-15SL	Triple Rib HD	TT	8	48	25	1,870	7	9.8	30.7	14.2	92	53	42	27
SR1343	9.5L-15SL	Super Rib	TL	6	36	25	1,520	7	9.8	30.7	14.2	92	53	45	27
TRD298	10.00-16SL	Triple Rib HD	TT	8	44	25	2,340	8	10.8	35.2	16.4	105	67	51	24
TRD398	10.00-16SL	Triple Rib HD	TL	8	44	25	2,340	8	10.8	35.2	16.4	105	67	55	24
44R298	10.00-16SL	Four Rib	TT	8	44	25	2,340	8	10.3	34.4	16	104	57	54	20
DRT398	10.00-16SL	Dyna Rib	TL	8	44	25	2,340	8	10.9	35.2	16.4	105	67	58	26
TRD395	11.00-16SL	Triple Rib HD	TL	8	40	25	2,600	10	12.4	37.9	17.6	113	75	71	27
44R295	11.00-16SL	Four Rib	TT	8	40	25	2,600	10	12.8	37.9	17.6	113	75	80	22
DRT395	11.00-16SL	Dyna Rib	TL	8	40	25	2,600	10	12.8	38.3	17.6	110	84	83	29
DRT396	11.00-16SL	Dyna Rib	TL	12	60	25	3,420	10	12.8	38.3	17.6	110	84	95	29
DRT316	11.00-24SL	Dyna Rib	TL	12	60	25	4,400	10	12.8	46.3	21.6	140	85	121	29
TRD218	11L-15SL	Triple Rib HD	TT	8	44	25	2,090	8	11	32	14.4	93	53	47	24
DRT314	11L-15SL	Dyna Rib	TL	6	32	25	1,710	8	11.3	31.5	14.6	93	59	57	28
DRT389	14L-16.1SL	Dyna Rib	TL	10	44	25	3,420	11	14.2	38.7	17.9	114	100	116	33
DRT362	14L-16.1SL	Dyna Rib	TL	12	52	25	3,860	11	14.2	38.7	17.9	114	100	117	33
DRT351	16.5L-16.1SL	Dyna Rib	TL	8	32	25	3,520	14	17	42.4	19.4	124	143	154	47

*See Approved Rim Contours section

Bias F-3

Goodyear



Goodyear Laborer F-3

- Industrial use for rugged applications
- Resists tearing and cracking with special tread compound
- Excellent handling and mobility with its five-rib design

Goodyear Multi Rib F-3

- Easy mobility with the rounded shoulder design
- Withstands scuffing, abrasions and bruises with the reinforced sidewall construction

Catalog #	Tire Size	Design	TL/TT	Load Rating	Inflation Pressure (psi)	Max Load mph	Max Load (lbs)	Recom'd Rim Width* (in)	Tire Width (in)	Overall Diameter (in)	Static Loaded Radius (in)	Rolling Circ. (in)	Flat Plate Area (in ²)	Weight (lbs)	Tread Depth 32nd in.
4MR3T8	9.00-10SL	Multi Rib	TL	10	60	25	1,820	6	9.4	26	11.9	76	38	31	10
4LT318	11L-15SL	Laborer	TL	8	44	25	2,090	8	11.3	30.8	14.1	90	56	46	12
4LT310	11L-15SL	Laborer	TL	10	52	25	2,340	8	11.3	30.8	14.1	90	56	46	12
4LT315	11L-16SL	Laborer	TL	10	52	25	2,470	8	11.2	31.8	14.7	94	60	56	16
4LT317	11L-16SL	Laborer	TL	12	64	25	2,760	8	11.2	31.8	14.7	94	60	63	16
4LT388	14.5/75-16.1SL	Laborer	TL	10	40	25	3,200	11	14.7	36	16.5	105	120	99	19
4LT588	14.5/75-16.1SL	Laborer	TL	14	56	25	3,960	11	14.7	36	16.5	105	120	102	19

*See Approved Rim Contours section

Goodyear

Radial I-1



Goodyear FS24

- Radial construction
- Large contact area
- Round shoulders
- Highway appearing tread design
- Low rolling resistance
- Excellent protection against punctures
- Smooth running on the road
- Long life
- Very good stability

Catalog #	Tire Size	Design	TL/TT	Load Rating	Inflation Pressure (psi)	Max Load mph	Max Load (lbs)	Recom'd Rim Width* (in)	Tire Width (in)	Overall Diameter (in)	Static Loaded Radius (in)	Rolling Circ. (in)	Flat Plate Area (in ²)	Weight (lbs)	Tread Depth 32nd in.
FS2432	340/60R16.5	FS24	TL	145A8/B	73	30	6,400	11	12.7	32.3	14.4	96	120	88.9	11
FS2418	340/65R18	FS24	TL	148A8/B	78	30	6,950	11	12.7	35.2	15.7	105	110	98	11
FS2484	360/65R17.5	FS24	TL	151A8/B	73	30	7,600	10.5	14.1	35.8	16.1	107	120	110	11
FS2461	380/55R16.5	FS24	TL	150A8/B	73	30	7,400	12	13.7	33.15	14.8	99	116	98	11
FS2471	380/60R16.5	FS24	TL	150A8/B	73	30	7,400	12	13.4	34.4	15.3	102.2	120	95	11
FS24WT	400/50R16.5	FS24	TL	148A8/B	73	30	6,950	12	15.9E	32.2E	14.5E	97E	125E	88E	11
FS2493	440/55R18	FS24	TL	154A8/B	52	30	8,250	14	15.7	38.3	17.1	113.8	168	128	11
FS2693	440/55R18	FS24	TL	159A8/B	73	30	9,650	14	15.7	37.1	16.6	110.4	156	128	11
FS24XT	460/45R16.5	FS24	TL	152A8/B	73	30	7,850	14	17.9E	32.2E	14.5E	97E	135E	129E	11
FS24DN	480/55R22.5	FS24	TL	166A8/B	73	30	11,700	16	18.9E	43.3E	19.5E	130E	190E	160E	11
FS24YT	500/40R16.5	FS24	TL	153A8/B	73	30	8,050	16	19.9E	32.2E	14.5E	97E	145E	135E	11

*See Approved Rim Contours section

Goodyear

Bias I-1



RIB IMPLEMENT



FARM UTILITY

Goodyear Rib Implement I-1

- Easy rolling resistance with its five-rib design
- Designed for dependable on/off highway service
- Sidewall abrasion protection from the raised diamond scuff band

Goodyear Farm Utility I-1

- Outstanding flotation
- Easy steering from the heavy grooved ribs
- Extra wide design



PNEUMATIC DRIVE



DRILL RIB

Goodyear Pneumatic Drive I-1

- Minimum ground disturbance
- Excellent stubble resistance

Goodyear Drill Rib I-1

- Distinct shoulder ridges
- Smooth center
- Primarily designed for grain drills

Catalog #	Tire Size	Design	TL/TT	Load Rating	Inflation Pressure (psi)	Max Load mph	Max Load (lbs)	Recom'd Rim Width* (in)	Tire Width (in)	Overall Diameter (in)	Static Loaded Radius (in)	Rolling Circ. (in)	Flat Plate Area (in ²)	Weight (lbs)	Tread Depth 32nd in.
4RB262	4.00-18SL	Rib Implement	TT	4	44	30	880	3	4.6	26.7	12.6	80	21	14	5
4RB372	5.00-15SL	Rib Implement	TL	4	36	30	965	3	5.2	25.2	11.5	73	26	15	5
4RB353	5.90-15SL#	Rib Implement	TL	4	36	30	1,140	4.5	6.1	26.2	12	77	34	17	7
4RB326	6.00-16SL	Rib Implement	TL	6	44	30	1,520	4	6.6	28.4	13.2	84	42	24	8
4RB381	6.50-16SL	Rib Implement	TL	6	44	30	1,710	4.5	6.9	28.9	13.2	84	44	24	7
4RB388	6.70-15SL#	Rib Implement	TL	6	44	30	1,610	4.5	6.9	28.2	12.9	82	40	21	8
4FU382	7.50-14SL	Farm Utility	TL	4	28	30	1,360	5.5	7.9	27	12.2	78	42	19	8

Mix Order Key'd

Bias I-1

Goodyear

Catalog #	Tire Size	Design	TL/TT	Load Rating	Inflation Pressure (psi)	Max Load mph	Max Load (lbs)	Recom'd Rim Width* (in)	Tire Width (in)	Overall Diameter (in)	Static Loaded Radius (in)	Rolling Circ. (in)	Flat Plate Area (in ²)	Weight (lbs)	Tread Depth 32nd in.
4RB392	7.50-16SL	Rib Implement	TL	10	60	30	2,680	5.5	8.1	31.2	14.2	91	52	37	8
4DR301	7.50-20SL	Drill Rib	TL	4	28	30	1,760	5.5	8.5	36.8	17.2	111	66	52	NA
4DR301	7.50-20SL	Drill Rib	TL	10	60	30	2,910	5.5	8.5	36.8	17.2	111	66	55	NA
4FU337	7.60-15SL	Farm Utility	TL	8	52	30	2,090	6	8	29.3	13.4	85	44	23	6
4FU336	7.60-15SL	Farm Utility	TL	6	40	30	1,760	6	8	29.3	13.4	85	44	24	6
4FU389	8.5L-14SL	Farm Utility	TL	6	36	30	1,870	6	8.8	28.1	12.8	82	47	24	7
4RB273	9.00-10SL	Rib Implement	TT	4	24	30	1,480	6	9.1	25.9	11	70	48	21	10
4RB3J8	9.00-24SL	Rib Implement	TL	8	40	30	3,520	8	11	42.6	19.3	123	94	69	10
4FU398	9.5L-14SL	Farm Utility	TL	6	32	30	1,930	7	9.7	28.6	13	83	61	26	7
4FU344	9.5L-15SL	Farm Utility	TL	8	44	30	2,470	7	9.5	29.8	13.6	87	60	30	7
4FL344	9.5L-15SL**	Farm Utility	TL	8	44	30	2,470	7	9.5	29.8	13.6	87	60	29	7
4FU3D7	9.5L-15SL	Farm Utility	TL	12	64	30	3,200	7	9.5	29.8	13.6	87	60	36	7
4FU3M1	10.00-15SL	Farm Utility	TL	8	40	30	3,200	8	11.2	33.5	14.8	94	80	43	11
4RB3K7	11.25-24SL	Rib Implement	TL	8	32	30	4,080	10	13.3	45.8	20.6	132	127	87	11
4RB3K9	11.25-24SL	Rib Implement	TL	12	48	30	5,200	10	13.3	45.8	20.6	132	127	99	11
4RB361	11.25-28SL	Rib Implement	TL	12	48	30	5,360	10	13.2	50.1	22.6	144	134	118	11
4FU391	11L-14SL	Farm Utility	TL	8	36	30	2,470	8	10.7	29.6	13.2	84	79	33	8
4FU318	11L-15SL	Farm Utility	TL	8	36	30	2,540	8	10.7	30.3	13.5	86	77	32	7
4FL318	11L-15SL**	Farm Utility	TL	8	36	30	2,540	8	10.7	30.3	13.5	86	77	32	7
4FU319	11L-15SL	Farm Utility	TL	10	44	30	2,910	8	10.7	30.3	13.5	86	77	35	7
4FU317	11L-15SL	Farm Utility	TL	12	52	30	3,200	8	10.7	30.3	13.5	86	77	42	7
4FL317	11L-15SL**#	Farm Utility	TL	12	52	30	3,200	8	10.7	30.3	13.5	86	77	43	7
4FU324	11L-16SL	Farm Utility	TL	10	44	30	3,000	8	10.5	31.1	13.9	89	82	36	9
4FU340	12.5L-15SL	Farm Utility	TL	8	36	30	3,000	10	12.6	32.4	14.5	93	98	39	9
4FL340	12.5L-15SL**	Farm Utility	TL	8	36	30	3,000	10	12.6	32.4	14.5	93	98	39	9
4FU341	12.5L-15SL	Farm Utility	TL	10	44	30	3,420	10	12.6	32.4	14.5	93	98	39	9
4FL341	12.5L-15SL**	Farm Utility	TL	10	44	30	3,420	10	12.6	32.4	14.5	93	98	36	9
4FU305	12.5L-15SL**	Farm Utility	TL	12	52	30	3,860	10	12.6	32.4	14.5	93	98	47	9
4FL305	12.5L-15SL**#	Farm Utility	TL	12	52	30	3,860	10	12.6	32.4	14.5	93	98	47	9
4FU3BC	12.5L-16SL	Farm Utility	TL	12	52	30	3,960	10	12.4	33.7	15	96	113	56	9
4FU368	14L-16.1SL	Farm Utility	TL	8	32	30	3,860	11	14	37.1	16.1	103	138	60	11
4FU362	14L-16.1SL	Farm Utility	TL	12	44	30	4,680	11	14	37.1	16.1	103	138	69	11
4FU310	16.5L-16.1SL	Farm Utility	TL	10	36	30	5,200	14	16.6	39.8	17.3	110	163	107	13
4FU3L1	16.5L-16.1SL	Farm Utility	TL	14	48	30	6,400	14	16.6	39.8	17.3	110	163	111	13
4FU7L1	16.5L-16.1SL#	Farm Utility	TL	20	64	30	7,600	14	16.6	39.8	17.3	110	163	119	13
4FU3H7	19L-16.1SL	Farm Utility	TL	10	32	30	6,000	16	19.5	42.7	18.7	126	167	133	14
4FU349	21.5L-16.1SL	Farm Utility	TL	10	28	30	6,600	18	21.9	43.7	18.3	117	253	132	15
4FU3J1	21.5L-16.1SL	Farm Utility	TL	14	36	30	7,850	18	21.9	43.7	18.3	117	253	146	15
4FU3Q4	21.5L-16.1SL#	Farm Utility	TL	18	36	30	8,800	18	21.9	43.7	18.3	117	253	161	15
4FU3L1	16.5L-16.1SL	Farm Utility	TL	14	48	30	6,400	14	16.6	39.8	17.3	110	163	111	13
4FU7L1	16.5L-16.1SL#	Farm Utility	TL	20	64	30	7,600	14	16.6	39.8	17.3	110	163	119	13
4FU3H7	19L-16.1SL	Farm Utility	TL	10	32	30	6,000	16	19.5	42.7	18.7	126	167	133	14
4FU349	21.5L-16.1SL	Farm Utility	TL	10	28	30	6,600	18	21.9	43.7	18.3	117	253	132	15
4FU3J1	21.5L-16.1SL	Farm Utility	TL	14	36	30	7,850	18	21.9	43.7	18.3	117	253	146	15
4FU3Q4	21.5L-16.1SL#	Farm Utility	TL	18	44	30	8,800	18	21.9	43.7	18.3	117	253	161	15

*See Approved Rim Contours section

**With Stubble Resistant Compound

Minimum Quantity Order

Goodyear

Bias FI



Goodyear Farm Highway Service I-1

- D.O.T. approved for highway use
- Designed for implements and wagons transported intermittently at highway speeds
- Flotation and load carrying capacity of Farm Service (SL) and highway speed characteristics of (LT) tire

Catalog #	Tire Size	Design	TL/TT	Load Rating	Inflation Pressure (psi)	Max Load mph	Max Load (lbs)	Recom'd Rim Width* (in)	Tire Width (in)	Overall Diameter (in)	Static Loaded Radius (in)	Rolling Circ. (in)	Flat Plate Area (in ²)	Weight (lbs)	Tread Depth 32nd in.
4HS313	9.5L-15FI	Farm Highway Service	TL	D	60	Highway	2,680	8	9.9	29.8	13.6	87	44	37	11
4HS3L1	10.00-15FI	Farm Highway Service	TL	D	60	Highway	3,960	8	11.2	33.9	14.9	95	80	44	11
4HS3F6	12.5L-16FI	Farm Highway Service	TL	D	60	Highway	3,860	10	12.8	33.7	15	96	113	55	9
4HS3F3	14L-16FI	Farm Highway Service	TL	D	45	Highway	4,290	11	14	37.1	16.1	103	138	80	13
4HS3E0	16.5L-16FI	Farm Highway Service	TL	E	60	Highway	6,450	14	16.1	39.8	17.3	110	163	114	14
4HSSH7	19L-16FI	Farm Highway Service	TL	E	45	Highway	6,800	16	18.8	43.1	18.1	127	160	118	14
4HS6H7	19L-16FI	Farm Highway Service	TL	F	60	Highway	8,050	16	18.8E	43.1E	18.1E	127E	160E	118E	14
4HS3E9	21.5L-16FI	Farm Highway Service	TL	E	45	Highway	8,050	18	21.7	44	19.6	131	180	161	15

*See Approved Rim Contours section



Goodyear Farm Highway Service II I-1

- Rounder shape sidewall for improved durability
- Flatter tread profile to increase contact area
- Large radius tread grooves to reduce groove cracking
- D.O.T. approved for highway use

Catalog #	Tire Size	Design	TL/TT	Load Rating	Inflation Pressure (psi)	Max Load mph	Max Load (lbs)	Recom'd Rim Width* (in)	Tire Width (in)	Overall Diameter (in)	Static Loaded Radius (in)	Rolling Circ. (in)	Flat Plate Area (in ²)	Weight (lbs)	Tread Depth 32nd in.
HS2383	11L-15FI	Farm Highway Service II	TL	C	45	Highway	2,600	8	10.5	31.1	13.7	91	66	44	10
HS2386	11L-15FI	Farm Highway Service II	TL	D	60	Highway	3,120	8	10.5	31.1	13.7	91	66	44	10
HS2392	11L-15FI	Farm Highway Service II	TL	F	90	Highway	3,960	8	10.5	31.1	13.7	91	66	54	10
HS2363	12.5L-15FI	Farm Highway Service II	TL	D	60	Highway	3,740	10	12.7	33.6	14.7	96	68	54	10
HS2387	12.5L-15FI	Farm Highway Service II	TL	F	90	Highway	4,680	10	12.7	33.6	14.7	96	68	64	10

*See Approved Rim Contours section

Goodyear

Radial I-3



Goodyear Super Flot Radial

- Designed for high flotation for tillage, hay and liquid fertilizer tanks
- Radial construction for rugged performance applications
- Design for free roll or light ground traction applications

Catalog #	Tire Size	Design	TL/TT	Load Rating Free	Load Rating Traction	Inflation Pressure (psi)	Max Speed mph	Max Load Free Roll (lbs)	Max Load Traction (lbs)	Recom'd Rim Width (in)	Tire Width (in)	Overall Diameter (in)	Static Loaded Radius (in)	Rolling Circ. (in)	Flat Plate Area (in ²)	Weight (lbs)	Tread Depth 32nd in.	
				Roll														
SPF429	500/60R22.5	Super Flot	TL	163B	151B	46	30	10,700	7,600	16DC	19.1	46.7	20.9	140	232	219	31	30
SPF4ET	600/50R22.5	Super Flot	TL	168B	156B	46	30	12,300	8,800	20DC	23.2	47.2	21.2	141	340	273	31	30
SPF4ES	710/40R22.5	Super Flot	TL	170B	158B	46	30	13,200	9,350	24DC	27.1	47.1	20.4	141	446	299	31	30

*See Approved Rim Contours section

Minimum Quantity Order

Radial I-3

Goodyear



Goodyear Muck Master Radial

- Large section for floatation
- Low profile for stability
- Massive lugs design for higher loads
- Lug concentration on center for excellent road ability

Catalog #	Tire Size	Design	TL/TT	Load Rating Free Roll	Inflation Pressure (psi)	Max Speed mph	Max Load (lbs)	Recom'd Rim Width* (in)	Tire Width (in)	Overall Diameter (in)	Static Loaded Radius (in)	Rolling Circ. (in)	Flat Plate Area (in ²)	Weight (lbs)	Tread Depth 32nd in.	No. of Lugs
TSS4GC	IF520/75R46CF0	Muck Master	TL	166A8	35	25	11,700	18	22.1	75.2	34	227	376	563	49	36
4SS59R	750/60R26	Muck Master	TL	173B/183A3	58	30/10	14,300/19,300	25	29.4	62.3	28.1	186	507	592	41	36
GSS58R	750/55R30	Muck Master	TL	172B/182A3	58	30/10	13,900/18,700	25	29.4	62.3	28.1	186	507	570	41	36
MMRW80	380/55R22.5	Muck Master	TL	153A8/B	73	30	8050	13	14.7	39.6	17.2	119	131	148	19	36

*See Approved Rim Contours section

Bias I-3

Goodyear



SURE GRIP TRACTION



TRACTION IMPLEMENT

Goodyear Sure Grip Traction I-3

- Ruler straight lugs for grip with even, steady pull
- Excellent cleanability provided by the open tread center
- Aggressive lug design

Goodyear Traction Implement I-3

- Traction design for implement service



SURE GRIP IMPLEMENT



SURE GRIP LUG

Goodyear Sure Grip Implement I-3

- Traction for all types of farm implements
- Improved tread wear from the flared lug design at the centerline

Goodyear Sure Grip Lug I-3

- Good choice for industrial equipment
- Good traction and long wear
- Wide, sturdy overlapping lugs



Goodyear Contractor I-3

- Excellent traction and wear are the benefits of the broad, curved lugs
- High strength construction gives it exceptional durability

Catalog #	Tire Size	Design	TL/TT	Load Rating	Inflation Pressure (psi)	Max Load mph	Max Load (lbs)	Recom'd Rim Width* (in)	Tire Width (in)	Overall Diameter (in)	Static Loaded Radius (in)	Rolling Circ. (in)	Flat Plate Area (in ²)	Weight (lbs)	Tread Depth 32nd in.	No. of Lugs
4T133S	5.00-15SL	Traction Implement	TL	4	36	30	965	3	5.2	25.6	11.8	75	32	16	15	28
4T1353	5.90-15SL	Traction Implement	TL	4	36	30	1,140	4.5	6.3	26.7	12.4	80	45	17	15	28
4TG267	6.70-15SL	Sure Grip Traction	TT	4	32	30	1,280	4.5	7.4	28.8	13.1	84	52	20	16	40
4TG3B2	7.50-16SL	Sure Grip Traction	TL	4	28	30	1,650	5.5	8.3	31.5	14.1	90	72	32	17	42
4TG2BA	7.50-18SL	Sure Grip Traction	TT	4	28	30	1,710	5.5	7.8	33.5	15.1	96	73	34	17	44
4TG203	7.50-20SL	Sure Grip Traction	TT	4	28	30	1,760	5.5	7.8	35.05	15.9	103	73	35	17	48
4TG336	7.60-15SL	Sure Grip Traction	TL	6	40	30	1,760	6	7.8	29.6	13.6	88	61	28	16	40
4TG338	7.60-15SL	Sure Grip Traction	TL	10	64	30	2,400	6	7.8	29.6	13.6	88	61	29	16	40
46W39N	12.5/80-18	Contractor	TL	6	28	25	3,420	9	11.7	37.6	17.1	112	131	75	31	56
4GL5J9	12.5/80/18	Sure Grip Lug	TL	14	62	30	6,600	9	12	39	17.3	119	145	102	31	40
4TG306	12.5L-15SL	Sure Grip Traction	TL	6	28	30	2,540	10	12	33.3	14.8	94	110	50	22	36

Goodyear

Bias I-3

Catalog #	Tire Size	Design	TL/TT	Load Rating	Inflation Pressure (psi)	Max Load mph	Max Load (lbs)	Recom'd Rim Width* (in)	Tire Width (in)	Overall Diameter (in)	Static Loaded Radius (in)	Rolling Circ. (in)	Flat Plate Area (in ²)	Weight (lbs)	Tread Depth 32nd in.	No. of Lugs
4TG305	12.5L-15SL	Sure Grip Traction	TL	12	52	30	3,860	10	12	33.3	14.8	94	110	57	22	36
4TG327	16.5L-16.1SL	Sure Grip Traction	TL	6	24	30	3,960	14	16	40.9	17.7	113	199	101	26	32
4TG3M3	21.5L-16.1SL	Sure Grip Traction	TL	8	24	30	6,000	18	21.6	43.6	18.6	121	306	218	32	32
4TG362	21.5L-16.1SL	Sure Grip Traction	TL	14	36	30	7,850	18	21.6	43.6	18.6	121	306	236	32	32
4TG3W3	21.5L-16.1SL	Sure Grip Traction	TL	12	32	30	7,150	18	21.6	43.6	18.6	121	306	230	32	32

*See Approved Rim Contours section

Goodyear

Bias HF-1/HF-2



SOFTAC



SOFTAC II

Goodyear SofTrac HF-1

- Button tread design
- Wide footprint with excellent traction
- Low ground bearing pressure
- Good for turf applications

Goodyear SofTrac II HF-1

- Good flotation due to the wide, flat tread
- Minimal ground disruption provided by its button tread design
- Dependable traction on or off the road



RIB TERRA



TUNDRA GRIP

Goodyear Tundra Grip LF HF-1

- Reduced vibration in field and road service
- Improved traction from its three-pitch tread design
- Longer body life provided by its natural shape casing

Goodyear Rib Terra HF-1

- Minimal ground disturbance
- Grooves for lateral traction



SMOOTH



SOFTURF

Goodyear Smooth Terra HF-1

- Minimum ground disturbance
- Excellent stubble resistance

Goodyear SofTurf HF-1

- Designed for low ground pressure use
- Ideal for fine lawn maintenance and can also be used for industrial applications



XTRA TRACTION



SFT105

Goodyear Xtra Traction HF-1

Goodyear SFT105 HF-1

- Specially designed for turf applications
- Minimum soil disturbance
- Low inflation operating pressures

Bias HF-1/HF-2

Goodyear



SFT115



Terra Rib

Goodyear SFT115 HF-1

- Specially designed for turf applications
- Minimum soil disturbance
- Low inflation operating pressures

Goodyear Terra Rib HF-1

- Minimum ground disturbance
- Limited grooves for lateral traction



Goodyear Super Terra Grip HF-2

- For low pressure flotation applications
- Provides lateral traction
- Lug design for traction in a flotation design

Goodyear Xtra Trac HF-2

Catalog #	Tire Size	Design	TL/TT	Load/Ply Rating	Inflation Pressure (psi)	Max Load mph	Max Load (lbs)	Recom'd Rim Width* (in)	Tire Width (in)	Overall Diameter (in)	Static Loaded Radius (in)	Rolling Circ. (in)	Flat Plate Area (in ²)	Weight (lbs)	Tread Depth 32nd in.	No. of Lugs
STG321	16x6.50-8NHS#	Super Terra Grip	TL	4	28	10	620	5.375	6.5	16.3	7.6	48	25	7	13	30
GST273	18x9.50-8NHS	Smooth Terra	TL	2	12	10	695	7	9.1	17.5	8.2	52	45	12	8	NA
RTR171	18x9.50-8NHS	Rib Terra	TT	10	60	10	1,775	7	9.5	17.7	7.6	48	43	16	8	NA
4FS2J3	24x13.00-12NHS	SofTrac II	TL	4	18	30	1,755	10.5	12.8	23.3	10.5	66	122	26	8	NA
4SF324	24x8.50-14NHS	SFT105	TL	4	22	10	1,230	7	8.6	24	11	73	47	22	9	NA
4SR321	25x10.00-12NHS	SofTrac	TL	6	32	30	1980	8	9.7	24.7	10.7	71.5	135	24	9	NA
TR4393	25x7.50-15NHS	Terra Rib	TL	4	30	30	960	5.5	7.5	25.4	11.2	75	45	23	9	NA
TR436A	25x7.50-15NHS	Terra Rib	TL	6	45	30	1,230	5.5	7.5	25.4	11.2	75	45	23	9	NA
4SR4WQ	25x10.50-15NHS	SofTrac	TL	4	30	30	980	8	10.5	25.2	11.8	77	64	32	9	NA
4SR6WQ	25x10.50-15NHS	SofTrac	TL	6	45	30	1230	8	10.5	25.2	11.8	77	64	38	9	NA
4SR327	25x8.50-14NHS	SofTrac	TL	6	32	10	1,640	7	8.4	25.4	11.5	72	57	27	9	NA
STG361	26x12.00-12NHS	Super Terra Grip	TL	4	20	30	1,780	10.5	12.1	26.2	11	69	85	28	24	40
TR4395	27x9.50-15NHS	Terra Rib	TL	6	45	30	1,610	7	9.6	27.5	12.3	80	70	31	10	NA
TR4306	27x9.50-15NHS	Terra Rib	TL	10	75	30	2,150	7	9.6	27.5	12.3	80	70	39	10	NA
4SR3H6	27x10.50-15NHS	SofTrac	TL	4	30	30	1,320	8.5	10.5	27.2	12.7	82	80	32	11	NA
4303M7	27x12LL-15NHS	SofTurf	TL	6	30	30	1,320	10	12	27.5	12.2	85	75	35	10	NA
4SR348	27x8.50-15NHS	SofTrac	TL	4	30	30	1,230	7	8.6	26.6	12	78	60	30	11	NA
XTR3L5	29x12.50-15NHS	Xtra Traction	TL	4	20	30	1,320	10	12.8	19.2	13.4	86	77	46	12	NA
STGB20	29x12.50-15NHS#	Super Terra Grip	TL	4	20	30	1,320	10	11.8	29.2	13.3	86	90	44	20	36
STGC20	29x12.50-15NHS	Super Terra Grip	TL	6	30	30	1,710	10	11.8	29.2	13.3	86	90	48	20	36
STGD20	29x12.5-15NHS	Super Terra Grip	TL	8	45	30	2,150	10	11.8	29.2	13.3	86	90	49	20	36
4SR3L5	29x12.50-15NHS	SofTrac	TL	4	20	30	1,320	10	12.8	29.2	13.4	86	77	49	12	NA
4SR34B	31x12.50-15NHS	SofTrac	TL	4	20	30	1,650	10	13	31.2	13.7	89	110	58	12	NA
XTR396	31x13.50-15NHS	Xtra Traction	TL	4	30	30	2,090	10	14.5	31.2	13.7	89	110	52	23	NA
4SR34A	31x13.50-15NHS	SofTrac	TL	4	20	30	1,650	10	13.8	30.8	14	91	100	47	12	NA
TR4396	31x13.50-15NHS	Terra Rib	TL	6	30	30	2,090	10	13.6	32	13.9	90	100	56	12	NA
TR4397	31x13.50-15NHS	Terra Rib	TL	8	45	30	2,600	10	13.6	32	13.9	90	100	60	12	NA
TR4597	31x13.50-15NHS	Terra Rib	TL	12	75	30	3,520	10	13.6	32	13.9	90	100	64	12	NA
TRX3A8	31x15.50-15NHS	Xtra Trac	TL	8	45	30	2,760	13	14.5	31.2	13.7	89	110	67	23	NA
STG331	31x15.50-15NHS	Super Terra Grip	TL	4	20	30	1,710	13	15.5	31.5	13.9	90	130	57	24	36
STG3A4	31x15.50-15NHS	Super Terra Grip	TL	8	45	30	2,760	13	15.5	31.5	13.9	90	130	65	24	36
4SR35B	31x15.50-15NHS	SofTrac	TL	4	20	30	1,710	13	15.2	31.2	13.8	89	115	55	13	NA
4SR3A4	31x15.50-15NHS	SofTrac**	TL	8	45	30	2,760	13	15.2E	31.2E	13.8E	89E	115E	48E	13	NA
4SR3M0	33x12.50-15NHS	SofTrac	TL	4	20	30	2,090	10	12.8	33.8	15.2	102	126	55	12	NA

Minimum Quantity Order

Goodyear

Bias HF-1/HF-2

Catalog #	Tire Size	Design	TL/TT	Load/Ply Rating	Inflation Pressure (psi)	Max Load mph	Max Load (lbs)	Recom'd Rim Width* (in)	Tire Width (in)	Overall Diameter (in)	Static Loaded Radius (in)	Rolling Circ. (in)	Flat Plate Area (in ²)	Weight (lbs)	Tread Depth 32nd in.	No. of Lugs
4SF3M0	33x12.50-15NHS	SFT105	TL	4	20	30	2,090	10	13.6	33.2	14.5	100	126	51	12	NA
4S54MV	33x21.50-16.1NHS	SFT115	TL	4	15	30	1,760	18	21.8	33.1	14.5	100	143	66	11	NA
STG416	38x14.00-20NHS	Super Terra Grip	TL	8	50	30	3,540	11	14	38.5	17.8	115	130	87	25	42
4SR462	38x14.00-20NHS#	SofTrac	TL	4	25	30	2,340	11	14.6	38.2	17.6	114	140	83	16	NA
STG398	38x20.00-16.1NHS	Super Terra Grip	TL	8	35	30	4,400	16	18.5	38.5	17.2	114	160	109	25	40
4SR323	41x14.00-20NHS	SofTrac	TL	4	25	30	3,080	11	14	41.2	18.3	122	170	90	18	NA
4SR342	44x18.00-20NHS	SofTrac	TL	4	20	30	3,420	14	18.6	45.1	20	134	213	134	24	NA
STG551	54x31.00-26NHS	Super Terra Grip	TL	16	50	30	9,100	26	30.5	54.4	24.6	160	394	409	44	40
4SF632	54x31.00-26NHS	SFT105	TL	6	20	30	5,360	26	30.5	54.4	24.6	160	394	257	30	NA
4SF032	54x31.00-26NHS	SFT105	TL	10	30	30	6,800	26	30.5	55	24.8	164	394	272	30	NA
TG4636	66x44.00-25NHS	Tundra Grip LF	TL	6	15	30	7,600	36	44.4E	67.2E	31.2E	203E	513E	na	12	NA
TG4B36	66x44.00-25NHS	Tundra Grip LF	TL	20	50	30	15,700	36	44.4	67.2	31.2	203	513	680	12	NA
TG4T36	66x44.00-25NHS	Tundra Grip LF	TL	26	65	30	18,200	36	44.4E	67.2E	31.2E	203E	513E	na	12	NA
STX5F4	66x43.00-25NHS	Super Terra Grip XT	TL	16	40	30	13,200	36	41.5	67.4	31.8	200	567	859	79	40
STXTF4	66x43.00-25NHS	Super terra Grip XT LF	TL	26	65	30	17,600	36	41.5E	67.4E	31.8E	200E	567E	na	79	40
STG9F3	66x43.00-25NHS	Super Terra Grip LF	TL	20	50	30	14,800	36	43.3	66.5	29.4	197	600	827	61	40
STG6F3	66x43.00-25NHS	Super terra Grip LF	TL	6	15	30	7,400	36	43.3E	67.4E	31.8E	197E	600E	na	61	40
STGTF3	66x43.00-25NHS	Super terra Grip LF	TL	26	65	30	17,600	36	41.9	66.5	31.3	199	641	799	61	40

*See Approved Rim Contours section

**Denman Mold

Minimum Quantity Order

Radial HF-1/HF-2/HF-3

Goodyear



Goodyear Tundra Grip Radial HF-1

- Reduced vibration in field and road service
- Improved traction from its three-pitch tread design
- Longer body life provided by its natural shape casing



Goodyear Super Terra Rib Radial HF-1

- Minimum ground disturbance
- Limited grooves for lateral traction



SUPER TERRA GRIP



SUPER TERRA GRIP D

Goodyear Super Terra Grip Radial HF-2

- Reduced vibration in field and road service
- Improved traction from its three-pitch tread design
- Longer body life provided by its natural shape casing



Goodyear Super Terra Grip XT Radial HF-3

- Reduced vibration in field and road service
- Improved traction from its three-pitch tread design
- Longer body life provided by its natural shape casing

Catalog #	Tire Size	Design	TL/TT	Load Rating	Inflation Pressure (psi)	Max Load mph	Max Load (lbs)	Recom'd Rim Width* (in)	Tire Width (in)	Overall Diameter (in)	Static Loaded Radius (in)	Rolling Circ. (in)	Flat Plate Area (in ²)	Weight (lbs)	Tread Depth 32nd in.	No. of Lugs
4RG2T2	48x31.00R20NHS	Super Terra Grip XT	TL	150A8/B	45	30	7,400	26	29.9	50.9	24	152	270	431	57	40
SRG4S1	54x31.00R26NHS	Super Terra Grip	TL	147A8/B	30	30	6,800	26	30.5	55	24.8	164	394	394	44	40
SRG6S1	54x31.00R26NHS	Super Terra Grip	TL	157A8/B	50	30	9,100	26	30.6	55	24.8	164	394	400	44	40
RSD61T	44x41.00R20NHS	Super Terra Grip D	TL	153A8/B	65	30	8,050	34	36.3	45	21.4	134	441	329	30	40
RSR61T	44x41.00R20NHS	Super Terra Rib	TL	153A8/B	65	30	8,050	34	37.4	47.5	22.6	141	139	352	17	NA
RTGAF3	1000/50R25	Super Terra Grip	TL	142A8/B	6	30	5,840	36	42.5	64	29.4	190	701	661	61	40
RTGSF3	1000/50R25	Super Terra Grip	TL	172A8/B	35	30	13,900	36	42.5	64	29.4	190	701	751	61	40
RTG6F3	1000/50R25	Super Terra Grip	TL	178A8/B	46	30	16,500	36	42.5	64	29.4	190	701	810	61	40
TGRD36	1050/50R25	Tundra Grip Radial	TL	178A8/B	41	30	16,500	36	42.6	69.2	31.4	203	798	681	12	NA
TGRD46	1050/40R32	Tundra Grip Radial	TL	178A8/B	46	30	16,500	36	42.6E	69.2E	31.4E	203E	798E	680E	12	nA
TGRD37	1250/40R25	Tundra Grip Radial	TL	180A8/B	41	30	17,600	44	49.5E	69.1E	31.4E	199E	725E	700E	12	NA
TGRD47	1250/30R32	Tundra Grip Radial	TL	177A8/B	41	30	16,100	44	49.5E	69.1E	31.4E	199E	725E	700E	12	NA
RTGB73	1250/35R42	Super Terra Grip	TL	181A8/B	35	30	18,200	44	49.5	76.1	35.5	226E	566	1,077	31	42
TGRB73	1250/35R42	Tundra Grip Radial	TL	181A8/B	35	30	18,200	44	50.4	76.9	36.9	243	635	1,373	16	NA

*See Approved Rim Contours section

Goodyear

Bias Skid Steer



Goodyear IT323 SS

- Heavier under tread
- Sidewall scuff rib
- Wear pad design for better wear



SURE GRIP LUG



INDUSTRIAL XTRA GRIP

Goodyear Sure Grip Lug SS

- Directional design for excellent traction
- For use in soft soil operations where traction and flotation are required

Goodyear Industrial Xtra Grip SS

Catalog #	Tire Size	Design	TL/TT	Load Rating	Inflation Pressure (psi)	Max Load mph	Max Load (lbs)	Recom'd Rim Width* (in)	Tire Width (in)	Overall Diameter (in)	Static Loaded Radius (in)	Rolling Circ. (in)	Flat Plate Area (in ²)	Weight (lbs)	Tread Depth 32nd in.	No. of Lugs
4DG330	5.70-8NHS	Industrial Xtra Grip	TT	B	50	5	710	4.5	5.8	18.6	8.6	55.5	13	12	na	NA
4GL379	25x8.50-14NHS	Sure Grip Lug	TL	6	32	5	1,640	7	8.4	25.4	11.5	72.2	57	30	18	40
4GL3J3	27x8.50-15NHS	Sure Grip Lug	TL	4	35	5	1,840	7	8.5	27.2	12.2	79	65	31	18	44
4GL339	27x8.50-15NHS	Sure Grip Lug	TL	6	45	5	2,480	7	8.5	27.2	12.2	79	65	36	18	44
432339	27x8.50-15NHS#	IT323	TL	6	45	5	2,480	7	8.8	27.2	12.2	79	65	37	18	40
4233L6	27x10.50-15NHS	IT323	TL	4	30	5	2,085	8.5	10	27.2	12.7	82.3	80	43	20	44
4323H7	27x10.50-15NHS#	IT323	TL	6	45	5	2,610	8.5	10	27.2	12.7	82.3	80	44	20	44
4GL3H7	27x10.50-15NHS	Sure Grip Lug	TL	6	45	5	2,610	8.5	10.3	27.2	12.7	82	80	37	18	40
4GL3C8	10-16.5NHS	Sure Grip Lug	TL	6	45	5	3,500	8.25	10.9	30.4	14.1	91	83	51	21	46
4GL3D1	10-16.5NHS	Sure Grip Lug	TL	8	60	5	4,140	8.25	10.9	30.4	14.1	91	83	53	21	46
4323D1	10-16.5NHS	IT323	TL	8	60	5	4,140	8.25	10.8	30.6	14.2	92.4	83	58	25	40
4323L8	31x15.50-15NHS	IT323	TL	8	35	5	4,480	12	15.7	31.5	13.9	90	110	83	25	40
4GL3E8	12-16.5NHS#	Sure Grip Lug	TL	8	50	5	4,810	9.75	12.6	32.7	14.8	98	110	72	23	46
4GL3J7	12-16.5NHS	Sure Grip Lug	TL	10	65	5	5,600	9.75	12.6	32.7	14.8	98	110	74	23	46
4323J7	12-16.5NHS	IT323	TL	10	65	5	5,600	9.75	12.7	32.9	14.9	99	110	77	26	40
4323H9	15-19.5NHS	IT323	TL	8	40	5	7,250	12.25	15.9	40.1	18	117	163	121	30	44
4GL3H9	15-19.5NHS#	Sure Grip Loader	TL	8	40	5	7,250	12.25	15.9	40.1	18	117	163	121	26	38
4GL336	15-19.5NHS	Sure Grip Loader	TL	12	60	5	9,190	12.25	15.9	40.1	18	117	163	136	26	38

*See Approved Rim Contours section
Minimum Quantity Order

Bias Smooth

Goodyear



Goodyear Smooth
Goodyear Smooth Implement
Goodyear Smooth Industrial
Goodyear Snow Plow
Goodyear Smooth Mono Rail

- Specialty service tires for use on paving equipment and rollers



GLASS POLISHER



COMPACTOR

Goodyear Glass Polisher
Goodyear Compactor

Catalog #	Tire Size	Design	TL/TT	Load Rating	Inflation Pressure (psi)	Max Load mph	Max Load (lbs)	Recom'd Rim Width* (in)	Tire Width (in)	Overall Diameter (in)	Static Loaded Radius (in)	Rolling Circ. (in)	Flat Plate Area (in ²)	Weight (lbs)	Tread Depth 32nd in.
3SM018	4.00-8NHS	Smooth Implement	TL	4	34	5	335	3	4.4	16.3	7.5	47	na	5	3
KGP381	20x14.00-10NHS	Glass Polisher	TL	4	na	na	na	na	13.6	20	na	na	na	20	na
3SM329	4.50-12NHS	Smooth Mono Rail	TT	8	100	30	1,240	4.25	5.3	21.9	10.5	66	na	14	5
SNP632	4.50-16	Snow Plow	TT	6	na	na	na	na	na	na	na	na	na	16	na
3SM2P6	6.50-10NHS**	Smooth Mono Rail	TL	10	100	30	1,825	5	7	22.7	10.6	66.6	na	21	5
3SN278	6.00-16NHS	Smooth Industrial	TT	10	75	20	2,230	5.5	7.3	29	13.8	85.1	30.4	29	8
3SI319	11L-15SL	Smooth Implement	TL	10	44	5	2,910	8	10.5	30.3	13.5	86	77	37	12
3SC3A2	8.5/90-15K	Compactor	TL	6	50	5	3,900	6	8.5	30.6	13.8	88	76	47	0
3SC2S2	7.50-15NHS	Compactor	TT	12	110	5	5,860	6.5	8.4	31	14.2	91	64	52	0
3SC2E1	7.50-15NHS	Compactor	TT	14	125	5	6,300	6.5	8.4	31	14.2	91	64	50	0
3SC679	16.9-30	Smooth	TL	6	18	25	3,740	15	18	57.6	26.1	169	213	80	0

*See Approved Rim Contours section

** Minimum Quantity Order

#Tire rim fitment for these tires are not interchangeable. The 15K tire will only fit on a 5" drop center rim. The NHS tire is designed to fit on a 5" flat base rim. The 8.5/90-15K size designation was established to advise of this distinction.

Goodyear

LS-2/HF-4



Goodyear Logger Lug III LS-2

- Optimal lug angle provides optimized balance between traction and cut resistance
- Special forestry compound for increased resistance to tread chunking and tearing
- Steel belt construction provides excellent penetration resistance

Catalog #	Tire Size	Design	TT/TL	Ply Rating	20 mph	5 mph	Rim	Tire Width (in)	Overall Diameter (in)	Static Loaded Radius (in)	Rolling Circ. (in)	Flat Plate Area (in²)	Weight (lbs)	Tread Depth 32nd in	No. of Lugs
					Load/Inflation lbs. (PSI)										
LL3056	18.4-26	Logger Lug III	TT	10	5,680 (25)	7,950 (30)	DW16A	18.4	58.2	26.7	176	185	380	63	36
LL3054	18.4-34	Logger Lug III	TT	10	6,400 (25)	8,950 (30)	DW16A	18.4	65.7	29.9	202	190	452	63	40
LL3586	23.1-26	Logger Lug III	TT	16	9,900 (35)	13,900 (40)	DW20B	23.5	64.2	29.3	188	265	637	64	34
YL3586	23.1-26	Logger Lug III	TL	16	9,900 (35)	13,900 (40)	DW20B	23.5	64.2	29.3	188	265	629	64	34
LL3599	24.5-32	Logger Lug III	TT	16	11,000 (30)	15,400 (35)	DH21	25.2	71.7	32.7	214	350	730	67	36
YL3599	24.5-32	Logger Lug III	TL	16	11,000 (30)	15,400 (35)	DH21	25.2	71.7	32.7	214	350	750	67	36



Goodyear Logger Lug III HD LS-2

- Twice as much steel Armor construction as standard Logger Lug III for excellent penetration resistance
- Same Chunk and tread resistance tread
- Improved lug stability and wear

Catalog #	Tire Size	Design	TT/TL	Ply Rating	20 mph	5 mph	Rim	Tire Width (in)	Overall Diameter (in)	Static Loaded Radius (in)	Rolling Circ. (in)	Flat Plate Area (in²)	Weight (lbs)	Tread Depth 32nd in	No. of Lugs
					Load/Inflation lbs. (PSI)										
LL7586	23.1-26	Logger Lug III HD	TT	16	9,900 (35)	13,900 (40)	DW20B	23.5	64.2	29.3	188	265	648	64	34
LL7799	24.5-32	Logger Lug III HD	TT	18	12,000 (35)	16,800 (40)	DH21	25.2	71.7	32.7	214	350	785	67	36
YL7799	24.5-32	Logger Lug III HD	TL	18	12,000 (35)	16,800 (40)	DH21	25.2	71.1	32.7	214	350	800E	64	36
LL7598	28L-26	Logger Lug III HD	TT	16	10,500 (30)	14,700 (35)	DW25B	28	64.8	29.3	195	280	706	71	30
LL7998	28L-26	Logger Lug III HD	TT	20	11,400 (35)	16,000 (40)	DW25B	28	64.8	29.3	195	280	731	71	30
YL7998	28L-26	Logger Lug III HD	TL	20	11,400	16,000 (40)	DW25A	28.0	64.8	28.8	195	280	750E	71	30
LL7996	30.5L-32	Logger Lug III HD	TT	20	13,200 (30)	18,500 (35)	DH27	30.5	74	33.3	219	370	964	70	32
YL7996	30.5L-32	Logger Lug III HD	TL	20	13,200 (30)	18,500 (35)	DH27	30.5	74	33.3	219	370	1,009	70	32
LL7996	30.5L-32	Logger Lug III HD	TT	26	15,700 (40)	22,000 (45)	DH27	30.5	74	33.3	219	370	958	70	32
YL7996	30.5L-32	Logger Lug III HD	TL	26	15,700 (40)	22,000 (45)	DH27	30.5	74	33.3	219	370	1020	70	32
LL79D5	DH35.5L-32	Logger Lug III HD	TT	20	16,100 (25)	22,500 (30)	DH31	35.6	78.9	36	288	575	1367	75	28
YL79D5	DH35.5L-32	Logger Lug III HD	TL	20	16,100 (25)	22,500 (30)	DH31	35.6	78.9	36	288	575	1367	75	28
LL7TD5	DH35.5L-32	Logger Lug III HD	TT	26	19,300 (35)	27,000 (40)	DH31	35.6	78.9	36	288	575	1360	75	28
YL7TD5	DH35.5L-32	Logger Lug III HD	TL	26	19,300 (35)	27,000 (40)	DH31	35.6	78.9	36	288	575	1400	75	28

LS-2/HF-4

Goodyear



Goodyear Logger Lug III Flotation HF-4

- Extra wide tread for high flotation
- Provides lower ground pressure
- Special steel armor construction for increased penetration resistance
- Tread compounds to increase resistance to chunking and tearing

Catalog #	Tire Size	Design	TT/TL	Ply Rating	20 mph	5 mph	Rim	Tire Width (in)	Overall Diameter (in)	Static Loaded Radius (in)	Rolling Circ. (in)	Flat Plate Area (in ²)	Weight (lbs)	Tread Depth 32nd in	No. of Lugs
					Load/Inflation lbs. (PSI)										
YL33F3	66x43.00-25 NHS	Logger Lug III Flotation	TL	14	12,300 (35)	19,400 (35)	36.0TH	41.2	69.4	32.9	197	600	1489	112	40
YL39F3	66x43.00-25 NHS	Logger Lug III Flotation	TL	20	14,800 (50)	23400 (50)	36.0TH	41.2	69.4	32.9	211	600E	1535	112	40
YL33F6	66x43.00-26 NHS	Logger Lug III Flotation	TL	14	12,000 (35)	19,000 (35)	DW36A	41.2	69.4	32.9	197	600	1488	112	40
YL39F6	66x43.00-26 NHS	Logger Lug III Flotation	TL	20	14,800 (50)	23400 (50)	36.0TH	41.2	69.4	32.9	211	600E	1501	112	40
YL33R3	67x34.00-25 NHS	Logger Lug III Flotation	TL	14	13,200 (40)	20,900 (40)	30.0TH	34.1	69.4	32.2	201	550	1324	118	30
YL3R65	67x34.00-26 NHS	Logger Lug III Flotation	TL	14	13,200 (40)	20,900 (40)	DW30A	34.1	69.4	32.2	201	550	1311	118	30
YL35R6	DH73x44.00-32*	Logger Lug III Flotation	TL	16	15,200 (40)	24,000 (40)	DH36	41.3	74.9	35.5	218	705	1607	104	44
YL39R6	DH73x44.00-32*	Logger Lug III Flotation	TL	20	17,600 (50)	27,800 (50)	DH36	41.8	74.2	41.9	218	705	NA	104	44
YL39V6	DH73x50.00-32*	Logger Lug III Flotation	TL	20	17,100 (45)	27,000 (45)	DH44	49.1	74.4	49.2	219	856	NA	104	44
YL35V6	DH73x50.00-32*	Logger Lug III Flotation	TL	16	14,800 (35)	23,400 (35)	DH44	50.1	75.3	35.6	219	856	1849	104	44

*HF-3 plus NSD greater than HF-3, less than HF-4. (1) Aralon breakers instead of steel

Goodyear

Tracker



Tracker P



Tracker HP



Tracker PT



Tracker WS EMT



Tracker MudRunner



Tracker CL



Tracker ATT



Tracker MP

Tracker P, Tracker PT, Tracker MudRunner, Tracker ATT, Tracker HP, Tracker WS EMT, Tracker CL, Tracker MP

- Available in varied tread styles, each designed for versatile performance in a variety of settings.
- Available in run-flat (EMT) technology.
- Available in half-knob, directional rib, and varied-angle lug patterns for traction and steering response in mud, snow, and utility applications.

Catalog #	Tire Size	Design	TT/TL	Load Rating	Load/Inflation lbs. (PSI)		Max Load	Rim Width	Tire Width (in)	Overall Diameter (in)	Static Loaded Radius (in)	Rolling Circ. (in)	Flat Plate Area (in ²)	Weight (lbs)	Tread Depth 32nd in
ATP3A5	AT22x11-10	Tracker P EMT	TL	3*	7 (45)	50	385 (175)	8.5	10.0 (254)	22.0 (559)	9.8 (249)	61.6 (1565)	65(419)	18 (8)	20
ATP2A5	AT22x11-10 EMT	Tracker P EMT	TL	2*	2 (15)	50	330 (150)	8.5	10.9 (277)	21.9 (556)	9.8 (249)	62.0 (1575)	65(419)	24 (11)	19
APE3A5	AT22x11-10 EMT	Tracker P EMT	TL	3*	3 (21)	50	385 (175)	8.5	10.9 (277)	21.9 (556)	9.8 (249)	62.0 (1575)	65(419)	24 (11)	19
ATP337	AT24x8-12	Tracker P	TL	3*	7 (45)	50	310 (140)	6	8.0 (203)	23.8 (605)	10.8 (274)	68.0 (1727)	44(284)	16 (7)	19
ATP205	AT24x11-10 EMT	Tracker P EMT	TL	2*	2 (15)	50	385 (175)	8.5	11.0 (279)	24.0 (610)	10.8 (274)	67.9 (1725)	65(419)	29 (13)	20
ATP306	AT25x8-12	Tracker P	TL	3*	7 (45)	50	340 (155)	6	7.4 (188)	24.8 (630)	11.3 (287)	71.0 (1803)	58(374)	14 (6)	16
ATP206	AT25x8-12 EMT	Tracker P EMT	TL	2*	2 (15)	50	290 (132)	6	7.7 (196)	24.6 (625)	10.9 (277)	68.0 (1727)	51(329)	21 (10)	16
APT308	AT25x11-10	Tracker P	TL	3*	7 (45)	50	455 (206)	8.5	10.2 (259)	25.5 (648)	11.3 (287)	71.0 (1803)	56(361)	26 (12)	24
APE208	AT25x11-10 EMT	Tracker P EMT	TL	2*	2 (15)	50	395 (180)	8.5	10.5 (267)	25.1 (638)	11.0 (279)	72.0 (1753)	65(419)	35 (16)	24
APE308	AT25x11-10 EMT	Tracker P EMT	TL	3*	3 (21)	50	455 (206)	8.5	10.5 (267)	25.1 (638)	11.0 (279)	72.0 (1753)	65(419)	35 (16)	24
ATP2U6	AT23x7-10	Tracker PT	TL	2*	5 (35)	50	240 (109)	6	6.9 (175)	23.1 (587)	10.4 (264)	65.1 (1654)	45(290)	11 (5)	16
AMR3R1	AT25x8-11	Tracker Mudrunner	TL	3*	7 (45)	50	355 (161)	6.5	8.2 (208)	24.4 (620)	11.3 (287)	71.0 (1803)	31(200)	18 (8)	24
AMR306	AT25x8-12	Tracker Mudrunner	TL	3*	7(45)	50	340 (145)	6	8.1 (206)	25.0 (635)	11.7 (297)	73.5 (1867)	31(200)	22 (10)	25
ARE206	AT25x8-12 EMT	Tracker Mudrunner EMT	TL	2*	7 (45)	50	340 (155)	6	8.1 (206)	25.0 (635)	11.7 (297)	73.5 (1867)	31(200)	22 (10)	25

Tracker

Goodyear

Catalog #	Tire Size	Design	TT/TL	Load Rating	Load/Inflation lbs. (PSI)		Max Load	Rim Width	Tire Width (in)	Overall Diameter (in)	Static Loaded Radius (in)	Rolling Circ. (in)	Flat Plate Area (in ²)	Weight (lbs)	Tread Depth 32nd in
AMR3V7	AT25x10-11	Tracker Mudrunner	TL	3*	7 (45)	50	420 (191)	8	10.7 (272)	24.4 (620)	11.3 (287)	71.0 (1803)	38(245)	27 (12)	29
AMR321	AT25x10-12	Tracker Mudrunner	TL	3*	7(45)	50	400 (180)	8	9.8 (249)	25.3 (643)	11.9 (302)	74.8 (1900)	40(258)	26 (12)	28
ARE221	AT25x10-12 EMT	Tracker Mudrunner EMT	TL	2*	7 (45)	50	400 (180)	8	9.8 (249)	25.3 (643)	11.9 (302)	74.8 (1900)	40(258)	26 (12)	28
AMR308	AT25x11-10	Tracker Mudrunner	TL	3*	7(45)	50	455 (206)	8.5	10.7 (272)	25.9 (645)	11.5 (292)	72.0 (1829)	41(265)	30 (14)	30
ARE208	AT25x11-10 EMT	Tracker Mudrunner EMT	TL	2*	7 (45)	50	455 (206)	8.5	10.7 (272)	25.4 (645)	11.5 (292)	72.0 (1829)	48(310)	30 (14)	30
AMR3P6	AT26x9-12	Tracker Mudrunner	TL	3*	7(45)	50	410 (186)	6	8.1 (206)	26.0 (660)	11.9 (302)	75.0 (1905)	53(342)	24 (11)	26
AMR3X0	AT26x12-10	Tracker Mudrunner	TL	3*	7 (45)	50	510 (230)	9.5	12.2 (310)	26.4 (671)	12.0 (305)	75.4 (1915)	54(348)	33 (15)	32
AMR361	AT26x12-12	Tracker Mudrunner	TL	3*	7(45)	50	520 (236)	9.5	12.0 (305)	26.5 (673)	12.4 (315)	78.0 (1981)	47(303)	32 (15)	32
AMR3T0	AT27x9-12	Tracker Mudrunner	TL	3*	7(45)	50	440 (200)	6	8.2 (208)	27.0 (686)	12.3 (312)	77.0 (1956)	72(465)	22 (10)	27
AMR309	AT27x12-12	Tracker Mudrunner	TL	3*	7(45)	50	550 (250)	8.5	12.0 (305)	27.0 (686)	12.6 (320)	79.0 (2007)	96(619)	32 (15)	32
ATA232	AT24x8-11	Tracker ATT	TL	2*	5 (35)	50	275 (125)	6.5	8.0 (203)	24.2 (615)	11.2 (284)	70.4 (1788)	48(310)	14 (6)	19
ATE232	AT24x8-11 EMT	Tracker ATT	TL	2*	2 (15)	50	275 (125)	6.5	8.0 (203)	24.2 (615)	11.2 (284)	70.4 (1788)	48(310)	21 (10)	19
ATA228	AT24x10-11	Tracker ATT	TL	2*	5 (35)	50	340 (155)	8	10.3 (262)	24.1 (612)	11.3 (287)	71.0 (1803)	54(348)	17 (8)	19
ATE228	AT24x10-11 EMT	Tracker ATT	TL	2*	2 (15)	50	340 (155)	8	10.3 (262)	24.1 (612)	11.3 (287)	71.0 (1803)	54(348)	27 (12)	19
AHP1T9	AT22x7-11	Tracker HP	TL	1*	4 (25)	50	175 (80)	5.5	7.0 (178)	22.0 (559)	10.0 (254)	62.8 (1595)	40(258)	10 (5)	15
AHP124	AT22x10-9	Tracker HP	TL	1*	4 (25)	50	245 (112)	8	10.0 (254)	21.8 (554)	10.2 (259)	64.1 (1628)	60(387)	15 (7)	16
AWE2A5	AT22x11-10 EMT	Tracker WS EMT	TL	2*	2 (15)	50	330 (150)	8.5	10.0 (254)	22.0 (559)	9.8 (249)	61.5 (1562)	63(406)	23 (10)	15
AWE2A8	AT22x8-10 EMT	Tracker WS EMT	TL	2*	2 (15)	50	240 (109)	6.5	7.7 (196)	21.9 (556)	9.8 (249)	61.6 (1565)	46(297)	17 (8)	15
AWE205	AT24x11-10 EMT	Tracker WS EMT	TL	2*	2 (15)	50	385 (175)	8.5	10.0 (254)	23.9 (607)	10.7 (272)	67.2 (1707)	74(477)	27 (12)	19
ACL237	AT24x8-12	Tracker CL	TL	2*	5 (35)	50	265 (121)	6	7.6 (193)	23.8 (605)	10.9 (277)	68.5 (1740)	31(200)	15 (7)	16
ACL208	AT25x11-10	Tracker CL	TL	2*	5 (35)	50	395 (180)	8.5	10.6 (269)	24.6 (625)	11.3 (287)	71.0 (1803)	48(310)	20 (9)	16
AMP332	AT24x8-11	Tracker MP	TL	3*	7 (45)	50	320 (145)	6.5	8.0 (203)	24.0 (610)	11.0 (279)	69.1 (1755)	45(290)	16 (7)	18
AMP328	AT24x10-11	Tracker MP	TL	3*	7 (45)	50	395 (180)	8	10.0 (254)	24.0 (610)	11.3 (287)	71.0 (1803)	56(361)	20 (9)	18

Wrangler

Goodyear



Wrangler Sport

- Deep, non-directional button tread design for performance in a variety of applications
- Good combination of traction, steering response and ride comfort.

Catalog #	Tire Size	Design	TT/TL	Load Rating	Load/Inflation lbs. (PSI)		Max Load	Rim Width	Tire Width (in)	Overall Diameter (in)	Static Loaded Radius (in)	Rolling Circ. (in)	Flat Plate Area (in ²)	Weight (lbs)	Tread Depth 32nd in
AWS195	AT22x8.00-10	Wrangler Sport	TL	2*	5 (35)	50	240 (109)	6	7.7 (196)	21.9 (556)	9.8 (249)	62.9 (1598)	46(297)	11 (5)	15
AWS1A5	22x11.00-10 NHS	Wrangler Sport	TL	2*	5 (35)	50	330 (150)	8.5	10.0 (254)	22.0 (559)	9.8 (249)	62.9 (1598)	63(406)	16 (7)	15
AWS105	24x11.00-10 NHS	Wrangler Sport	TL	2*	5 (35)	50	385 (175)	8.5	10.0 (254)	23.9 (607)	10.7 (272)	66.6 (1692)	74(477)	18 (8)	19

Goodyear

Rawhide



Rawhide III



Rawhide ATT



Rawhide Grip



Rawhide RS



Rawhide Terra

Rawhide III, Rawhide ATT, Rawhide Grip, Rawhide RS, Rawhide Terra

- Range of deep tread styles for gaining traction and flotation in the most challenging conditions — from mud and clay to sand and bogs.
- Available in long-bar, claw-shaped, and short-bar designs at up to ¾-inch depths and large voids for excellent self-cleaning.
- Available with run-flat (EMT) technology.

Catalog #	Tire Size	Design	TT/TL	Load Rating	Load/Inflation lbs. (PSI)		Max Load	Rim Width	Tire Width (in)	Overall Diameter (in)	Static Loaded Radius (in)	Rolling Circ. (in)	Flat Plate Area (in ²)	Weight (lbs)	Tread Depth 32nd in
ARG206	25x8-12 NHS	Rawhide grip	TL	2*	7 (45)	50	340 (155)	6	7.6 (193)	25.4 (645)	11.5 (292)	72.2 (1834)	38(245)	18 (8)	24
ARG306	AT25x8-12	Rawhide grip	TL	3*	7 (45)	50	340 (155)	6	7.6 (193)	25.4 (645)	11.5 (292)	72.2 (1834)	38(245)	18 (8)	24
ARG321	AT25x10-12	Rawhide grip	TL	3*	7 (45)	50	420 (190)	8	9.3 (236)	25.3 (643)	11.3 (287)	71.0 (1803)	40(258)	26 (12)	24
ARG308	AT25x11-10	Rawhide grip	TL	3*	7 (45)	50	455 (206)	8.5	10.3 (262)	25.3 (643)	11.4 (290)	71.5 (1816)	44(284)	28 (13)	24
ARG346	AT25x11-12	Rawhide grip	TL	3*	7 (45)	50	455 (206)	8.5	10.4 (264)	25.6 (650)	11.6 (295)	72.9 (1852)	50(323)	25 (11)	24
ARG3P6	AT26x9-12	Rawhide grip	TL	3*	7 (45)	50	410 (185)	6.5	8.5 (216)	26.0 (660)	11.9 (302)	74.8 (1900)	53(342)	24 (11)	24
ARG3U6	AT26x11-12	Rawhide grip	TL	3*	7 (45)	50	485 (220)	8.5	10.3 (262)	26.2 (665)	11.9 (302)	74.8 (1900)	66(426)	28 (13)	24
AR3387	22x11.00-8 NHS	Rawhide III	TL	2*	5 (35)	50	340 (150)	8.5	11.2 (284)	21.5 (546)	9.6 (244)	60.3 (1532)	54(348)	22 (10)	19
AR3373	25x12-9 NHS	Rawhide III	TL	2*	5 (35)	50	430 (195)	10	12.3 (312)	24.2 (615)	10.8 (274)	68.0 (1727)	67(432)	25 (11)	19
AR3051	AT25x11.5-9	Rawhide III	TL	2*	5 (35)	50	410 (185)	10	12.0 (305)	25.5 (648)	11.2 (284)	70.4 (1788)	67(432)	25 (11)	19
ARA304	AT23x8-11	Rawhide ATT	TL	3*	7 (45)	50	290 (132)	6.5	8.0 (203)	23.0 (584)	10.1 (257)	63.0 (1600)	48(310)	16 (7)	24
ARA3A9	AT24x9-11	Rawhide ATT	TL	3*	7 (45)	50	365 (165)	7.5	9.0 (229)	24.0 (610)	10.6 (269)	66.6 (1692)	75(484)	19 (9)	24
AAE3A9	AT24x9-11 EMT	Rawhide ATT EMT	TL	2*	2 (15)	50	310 (140)	7.5	9.0 (229)	23.8 (605)	10.6 (269)	66.6 (1692)	75(484)	27 (12)	24
ARA306	AT25x8-12	Rawhide ATT	TL	3*	7 (45)	50	340 (155)	6	7.6 (193)	25.4 (645)	11.5 (292)	72.2 (1834)	66(426)E	18 (8)	24
ARA321	AT25x10-12	Rawhide ATT	TL	3*	7 (45)	50	420 (190)	8	10.15 (257)	25.0 (635)	11.9 (302)	74.8 (1800)	75(484)E	21 (10)	26
ARA40N	AT25x11-9	Rawhide ATT	TL	3*	7 (45)	50	465 (212)	9	11.0 (279)	25.0 (635)	11.1 (282)	70.0 (1778)	99(639)	21 (10)	24
ARR306	25x8-12 NHS	Rawhide rs	TL	2*	7 (45)	50	340 (155)	6	7.9 (201)	25.1 (638)	11.3 (287)	71.0 (1803)	34(220)E	19 (9)	23
ARR321	AT25x10-12	Rawhide rs	TL	3*	7 (45)	50	190 (420)	8	9.4 (239)	24.8 (630)	11.1 (282)	69.7 (1771)	36(232)E	22 (10)	23
ART387	21x11.00-8 NHS	Rawhide Terra	TL	2*	5 (35)	50	310 (140)	8.5	11.0 (279)	20.4 (518)	9.0 (229)	56.6 (1438)	65(419)	17 (8)	16

ATT

Goodyear



ATT901



ATT902



ATT911



ATT912



ATT913

ATT901, ATT902, ATT911, ATT912, ATT913

- Made for 2- and 4-wheel-drive ATVs that require performance in a variety of settings.
- Small button directional tread pattern provides excellent combination of traction, steering response and ride comfort.

Catalog #	Tire Size	Design	TT/TL	Load Rating	Load/Inflation lbs. (PSI)		Max Load	Rim Width	Tire Width (in)	Overall Diameter (in)	Static Loaded Radius (in)	Rolling Circ. (in)	Flat Plate Area (in ²)	Weight (lbs)	Tread Depth 32nd in
A011A1	AT21x7-10	ATT901	TL	1*	4 (25)	50	165 (75)	5.5	6.4 (163)	21.1 (536)	7.0 (178)	44.1 (1120)	46(297)	10 (5)	14
A02564	AT22x9-8	ATT902	TL	1*	4 (25)	50	225 (103)	7	9.1 (231)	22.4 (569)	10.1 (257)	63.3 (1608)	63(406)	13 (6)	16
A11204	AT23x8-11	ATT911	TL	2*	5 (35)	50	255 (115)	6.5	7.3 (185)	23.1 (587)	10.2 (259)	50.3 (1278)	48(310)	11 (5)	14
A121P0	AT25x11-9	ATT912	TL	1*	4 (25)	50	255 (115)	9	10.5 (267)	24.2 (615)	11.1 (282)	69.9 (1775)	82(529)	15 (7)	16
A131A9	AT24x9-11	ATT913	TL	1*	4 (25)	50	255 (115)	7.5	9.1 (231)	23.9 (607)	10.5 (267)	59.8 (1519)	75(484)	15 (7)	14

Runamuck

Goodyear




Runamuck

- Excellent flotation for extremely wet, swampy or sandy conditions
- Long, thin tread lug spans width of tire for paddle effect in water
- Large voids result in excellent self-cleaning

Catalog #	Tire Size	Design	TT/TL	Load Rating	Load/Inflation lbs. (PSI)		Max Load	Rim Width	Tire Width (in)	Overall Diameter (in)	Static Loaded Radius (in)	Rolling Circ. (in)	Flat Plate Area (in ²)	Weight (lbs)	Tread Depth 32nd in
ARM3A8	22x10.00-8 NHS	Runamuck	TL	2*	5 (35)	50	300 (136)	7	9.6 (244)	22.5 (572)	9.2 (234)	57.8 (1468)	45(290)	15 (7)	13

Goodyear

Compass Terra



Compass Terra

- Race-tested knobby design
- Great for trails and back roads
- Rugged cord body resists bruising and punctures

Catalog #	Tire Size	Design	TT/TL	Load Rating	Load/Inflation lbs. (PSI)		Max Load	Rim Width	Tire Width (in)	Overall Diameter (in)	Static Loaded Radius (in)	Rolling Circ. (in)	Flat Plate Area (in²)	Weight (lbs)	Tread Depth 32nd in
ACT387	AT21x11-8	Compass Terra	TL	2*	5 (35)	50	310 (140)	8.5	11.1 (282)	20.4 (518)	8.9 (226)	56.6 (1438)	53(342)	15 (7)	16