

Contents

| | | | |
|--|-----------|--|-----------|
| Radial R-1/R-1S..... | 2 | Smooth | 20 |
| Titan Hi Traction Lug Radial R-1 | 2 | Titan Road Roller/Road Roller II | 20 |
| Titan Hi Power Lug Radial R-1 | 3 | HF-1, HF-2 | 21 |
| Titan Tru Grip Lug Radial R-1 | 3 | Titan Flo-Trac Rib HF-1 | 21 |
| Titan Super Hi-Power Lug II Radial R-1 | 3 | Titan Multi Trac C/S HF-1 | 21 |
| Titan Hi Load Radial R-1S..... | 3 | Titan Classic Rib HF-1 | 21 |
| Bias R-1 | 4 | Titan Classic TX HF-1 | 21 |
| Titan Hi Traction Lug R-1..... | 4 | Titan Soft Turf/LSW and LSW 430 HF-1 | 21 |
| Titan Tru Grip Lug R-1 | 6 | Titan Flo-Trac Lug HF-2..... | 21 |
| Titan Hi Power Lug R-1 | 6 | Titan Tru Power II HF-2..... | 21 |
| Titan Tru Power R-1 | 7 | Bias Skid Steer | 23 |
| Titan Farm Tractor R-1..... | 8 | Titan Contractor FWD SS | 23 |
| Titan Traction Drive R-1 | 8 | Titan H/E SS | 23 |
| Titan Lift Rigger II R-1..... | 8 | Titan HD2000 SS | 23 |
| Titan TT415 R-1 | 8 | Titan HD2000 II SS..... | 23 |
| Radial R-1W..... | 9 | Titan Trac Loader SS..... | 23 |
| Titan TT49V Radial R-1W..... | 9 | Titan Trac Loader Chevron SS | 23 |
| Titan AG49H Radial R-1W | 9 | Titan Ultimate | 23 |
| Titan AG49M Radial R-1W | 9 | Titan MXL SS..... | 23 |
| Bias R-2 | 11 | Titan Soft Turf | 23 |
| Titan Special Service R-2..... | 11 | ATV | 25 |
| Radial R-3 | 12 | Titan 489 X/T Rears ATV | 25 |
| Titan Torc Trac Radial R-3 | 12 | Titan 589 M/T Rears ATV | 25 |
| Titan Torc Trac II Radial R-3..... | 12 | Titan Fast Trekker Rears ATV | 26 |
| Bias R-3, R-4 | 12 | Titan Radial Mud Monster ATV | 26 |
| Titan Torc Trac R-3 | 12 | Titan Raptor ATV..... | 26 |
| Titan Torc Trac II R-3 | 12 | Titan Sabre Tooth ATV | 26 |
| Titan Multi Trac R-3 | 12 | | |
| Titan RDSXL | 13 | | |
| Titan Industrial Tractor Lug II R-4..... | 13 | | |
| Titan Industrial Tractor Lug R-4 | 14 | | |
| Titan Industrial Contractor R-4 | 14 | | |
| Bias F-1, F-2, F-2M, F-3 | 15 | | |
| Titan Tru-Trac Front Tractor F-1..... | 15 | | |
| Titan Tru-Trac F-2 | 15 | | |
| Titan Tru-Trac Multi Rib F-2M | 15 | | |
| Titan Contractor F-3 | 16 | | |
| Titan Industrial Front Tractor F-3 | 16 | | |
| Bias I-1, I-3..... | 17 | | |
| Titan Dura Life I-1 | 17 | | |
| Titan Hi Flotation I-1 | 17 | | |
| Titan Packer I-1..... | 17 | | |
| Titan Planter AG41B I-1 | 17 | | |
| Titan Dura Life Planter | 17 | | |
| Titan Stubble Guard I-1 | 18 | | |
| Titan Contractor I-3..... | 19 | | |
| Titan Contractor II I-3 | 19 | | |
| Titan TI422 I-3 | 19 | | |
| Titan Traction Implement I-3..... | 19 | | |
| FI | 20 | | |
| Titan Highway Implement FI..... | 20 | | |

Middle of the Book

Tire Information Section1-120

| | |
|---|-----|
| Industry Standards/Tire Selection Chart | 1 |
| Things You Should Know About Farm Tires..... | 2 |
| High Flexion Tires Description..... | 7 |
| LSW Description | 8 |
| Radial Sizes by Rolling Circumference..... | 9 |
| Int'l Load Index/Speed Symbols..... | 13 |
| Rolling Circumference | 14 |
| Optimum Tractor Tire Performance..... | 15 |
| LSW & Metric Conversion Tables..... | 19 |
| Load & Inflation Tables | 20 |
| Horse Power Capability..... | 95 |
| Liquid Fill Procedures..... | 104 |
| Approved Rim Contours | 111 |
| RCI Chart..... | 120 |

Safety SectionS:1-22

Titan

Radial R-1



Titan Hi Traction Lug Radial R-1

- Superior traction and side hill slip resistance
- Combines long bar/medium bar traction for cleanability, smooth ride and more power to the ground

| Catalog # | Tire Size | Design | TL/TT | Load Rating | Inflation Pressure (psi) | Max Speed (mph) | Max Load (lbs) | Recom'd Rim Width* (in) | Tire Width (in) | Overall Diameter (in) | Static Loaded Radius (in) | Rolling Circ. (in) | Flat Plate Area (in ²) | Weight (lbs) | Tread Depth 32nd in. | Number of Lugs |
|-----------|-----------|-----------------|-------|-------------|--------------------------|-----------------|----------------|-------------------------|-----------------|-----------------------|---------------------------|--------------------|------------------------------------|--------------|----------------------|----------------|
| 4RDH14 | 320/85R24 | Hi Traction Lug | TL | 142A8/B | 67 | 30 | 5,840 | 12 | 13.3 | 46.1 | 20.9 | 138 | 120 | 132 | 44 | 44 |
| 4RD422 | 13.6R24 | Hi Traction Lug | TL | 128A8/B | 24 | 30 | 3,960 | 12 | 14.3 | 48.3 | 21.7 | 145 | 141 | 147 | 46 | 48 |
| 48E324 | 13.6R28 | Hi Traction Lug | TL | 3* | 30 | 30 | 3,740 | 12 | 14.2 | 52.5 | 23.7 | 156 | 156E | 199 | 51 | 52 |
| 4RD434 | 14.9R24 | Hi Traction Lug | TL | 120A8/B | 18 | 30 | 3,080 | 13 | 16.6 | 50.2 | 22.7 | 151 | 229 | 156 | 47 | 48 |
| 4RDH34 | 380/85R24 | Hi Traction Lug | TL | 143A8/B | 46 | 30 | 6,000 | 13 | 16.6 | 50.2 | 27.7 | 151 | 229 | 169 | 47 | 48 |
| 48E438 | 380/85R28 | Hi Traction Lug | TL | 133A8/B | 23 | 30 | 4,540 | 13 | 16 | 54.2 | 24.9 | 162 | 175 | 210 | 50 | 54 |
| 48E430 | 380/85R30 | Hi Traction Lug | TL | 135A8/B | 23 | 30 | 4,800 | 13 | 16 | 56.2 | 25.6 | 169 | 165E | 226 | 50 | 52 |
| 48E435 | 380/85R34 | Hi Traction Lug | TL | 137A8/B | 23 | 30 | 5,080 | 13 | 16 | 60.2 | 27.6 | 181 | 224 | 242 | 52 | 56 |
| 48E79A | 380/85R34 | Hi Traction Lug | TL | 148A8/B | 46 | 30 | 6,950 | 13 | 16 | 60.2 | 27.6 | 181 | 224 | 255 | 52 | 56 |
| 48EA32 | 380/90R46 | Hi Traction Lug | TL | 144A8/B | 23 | 30 | 6,150 | 13 | 15.7 | 72.3 | 34 | 218 | 300 | 321 | 50 | 68 |
| 48ED32 | 380/90R46 | Hi Traction Lug | TL | 149A8/B | 35 | 30 | 7,150 | 13 | 15.7 | 72.3 | 34 | 218 | 300 | 321 | 50 | 68 |
| 48EH32 | 380/90R46 | Hi Traction Lug | TL | 156A8/B | 49 | 30 | 8,800 | 13 | 15.7 | 72.3 | 34 | 218 | 300 | 368 | 50 | 68 |
| 48E032 | 380/90R46 | Hi Traction Lug | TL | 168A8/B | 78 | 30 | 12,300 | 13 | 15.7 | 72.3 | 34 | 218 | 300 | 370 | 50 | 68 |
| 48E246 | 16.9R26 | Hi Traction Lug | TL | 2* | 24 | 30 | 4,800 | 15 | 18.1 | 54.4 | 24.5 | 163 | 196E | 225 | 52 | 52 |
| 48E220 | 16.9R38 | Hi Traction Lug | TL | 2* | 24 | 30 | 5,680 | 15 | 18 | 66.6 | 30.6 | 200 | 235E | 305 | 52 | 60 |
| 48E448 | 420/85R28 | Hi Traction Lug | TL | 139A8/B | 23 | 30 | 5,360 | 15 | 18.1 | 56.5 | 25.5 | 169 | 202E | 263 | 52 | 52 |
| 48E479 | 420/90R30 | Hi Traction Lug | TL | 142A8/B | 23 | 30 | 5,840 | 15 | 17.8 | 58.9 | 26.7 | 176 | 408E | 258 | 56 | 52 |
| 48E154 | 18.4R34 | Hi Traction Lug | TL | 1* | 18 | 30 | 5,360 | 16 | 18.8 | 65.1 | 29.6 | 195 | 356 | 323 | 53 | 56 |
| 48E477 | 480/80R38 | Hi Traction Lug | TL | 149A8/B | 23 | 30 | 7,150 | 16 | 19.8 | 69.1 | 31.6 | 208 | 454 | 355 | 53 | 60 |
| 48E677 | 480/80R38 | Hi Traction Lug | TL | 152A8/B | 29 | 30 | 7,850 | 16 | 19.8 | 69.1 | 31.6 | 208 | 454 | 362 | 53 | 60 |
| 48E442 | 480/80R42 | Hi Traction Lug | TL | 151A8/B | 23 | 30 | 7,600 | 16 | 19.3 | 73.1 | 33.6 | 220 | 400E | 390 | 53 | 60 |
| 48E542 | 480/80R42 | Hi Traction Lug | TL | 154A8/B | 29 | 30 | 8,250 | 16 | 19.3 | 73.1 | 33.6 | 220 | 400E | 395 | 53 | 60 |
| 48E842 | 480/80R42 | Hi Traction Lug | TL | 162A8/B | 46 | 30 | 10,500 | 16 | 19.3 | 73.1 | 33.6 | 220 | 400E | 428 | 53 | 60 |
| 48E942 | 480/80R42 | Hi Traction Lug | TL | 166A8/B | 58 | 30 | 11,700 | 16 | 19.3 | 73.1 | 33.6 | 220 | 400E | 436 | 53 | 60 |
| 48E447 | 480/80R46 | Hi Traction Lug | TL | 155A8/B | 29 | 30 | 8,550 | 16 | 19.3 | 78.9 | 35.9 | 235 | 425E | 403 | 53 | 64 |
| 48E547 | 480/80R46 | Hi Traction Lug | TL | 158A8/B | 35 | 30 | 9,350 | 16 | 19.3 | 78.9 | 35.9 | 235 | 425E | 411 | 53 | 64 |
| 48E489 | 520/85R38 | Hi Traction Lug | TL | 148A8/B | 17 | 30 | 6,950 | 18 | 21.3 | 72.9 | 33.1 | 218 | 430E | 411 | 55 | 60 |
| 48E689 | 520/85R38 | Hi Traction Lug | TL | 158A8/B | 29 | 30 | 9,350 | 18 | 21.3 | 72.9 | 33.1 | 218 | 430E | 467 | 55 | 60 |
| 48E789 | 520/85R38 | Hi Traction Lug | TL | 160A8/B | 35 | 30 | 9,900 | 18 | 21.3 | 72.9 | 33.1 | 218 | 430E | 467 | 55 | 60 |
| 48E452 | 520/85R42 | Hi Traction Lug | TL | 157A8/B | 23 | 30 | 9,100 | 18 | 21.3 | 76.9 | 35.1 | 231 | 435E | 471 | 55 | 64 |
| 48E199 | 24.5R32 | Hi Traction Lug | TL | 1* | 18 | 30 | 8,520 | 21 | 25.3 | 70.6 | 31.6 | 211 | 461E | 521 | 56 | 56 |
| 48E599 | 24.5R32 | Hi Traction Lug | TL | 5* | 38 | 30 | 12,800 | 21 | 25.3 | 70.6 | 31.6 | 211 | 461E | 607 | 56 | 56 |
| 48E699 | 24.5R32 | Hi Traction Lug | TL | 6* | 46 | 30 | 14,300 | 21 | 25.3 | 70.6 | 31.6 | 211 | 461E | 607 | 56 | 56 |

*See Approved Rim Contours section

Radial R-1/R-1S

Titan



Titan Hi Power Lug Radial R-1

- Single Bar Design with wide overlapping lugs
- Deep Tread and excellent tread wear and durability
- Designed to deliver power to the ground
- Design offers maximum cleaning and sidehill slip resistance

| Catalog # | Tire Size | Design | TL/TT | Load Rating | Inflation Pressure (psi) | Max Speed (mph) | Max Load (lbs) | Recom'd Rim Width* (in) | Tire Width (in) | Overall Diameter (in) | Static Loaded Radius (in) | Rolling Circ. (in) | Flat Plate Area (in ²) | Weight (lbs) | Tread Depth 32nd in. | Number of Lugs |
|-----------|-----------|--------------|-------|-------------|--------------------------|-----------------|----------------|-------------------------|-----------------|-----------------------|---------------------------|--------------------|------------------------------------|--------------|----------------------|----------------|
| 4R3434 | 14.9R24 | Hi Power Lug | TL | 120A8/B | 18 | 30 | 3,080 | 13 | 15.5 | 49.8 | 22.7 | 148 | 78 | 156 | 47 | 36 |
| 4R3450 | 18.4R30 | Hi Power Lug | TL | 143A8/B | 24 | 30 | 6,000 | 16 | 19.3 | 61 | 27.3 | 182 | 322 | 277 | 50 | 40 |
| 4R3750 | 480/80R30 | Hi Power Lug | TL | 139A8/B | 17 | 30 | 5,360 | 16 | 19.2 | 60.5 | 27.1 | 181 | 347 | 277 | 50 | 40 |
| 49T454 | 480/80R34 | Hi Power Lug | TL | 140A8/B | 17 | 30 | 5,520 | 16 | 19.5 | 64.5 | 28.9 | 193 | 429 | 341 | 54 | 42 |
| 4R36Q7 | 23.1R30 | Hi Power Lug | TL | 168A8/B | 46 | 30 | 12,300 | 20 | 24 | 66.5 | 30.1 | 200 | 350E | 492 | 52 | 40 |

*See Approved Rim Contours section



Titan Tru Grip Lug Radial R-1

- Single bar design with wide overlapping lugs
- Deep Tread and excellent tread wear and durability
- Designed to deliver power to the ground
- Design offers maximum cleaning and sidehill slip resistance

| Catalog # | Tire Size | Design | TL/TT | Load Rating | Inflation Pressure (psi) | Max Speed (mph) | Max Load (lbs) | Recom'd Rim Width* (in) | Tire Width (in) | Overall Diameter (in) | Static Loaded Radius (in) | Rolling Circ. (in) | Flat Plate Area (in ²) | Weight (lbs) | Tread Depth 32nd in. | Number of Lugs |
|-----------|-----------|---------------------|-------|-------------|--------------------------|-----------------|----------------|-------------------------|-----------------|-----------------------|---------------------------|--------------------|------------------------------------|--------------|----------------------|----------------|
| 4R6414 | 12.4R24 | Tru Grip Lug Radial | TL | 122A8/B | 36 | 30 | 3,300 | 10 | 12.6 | 44.7 | 20.4 | 134 | 142 | 114 | 42 | 36 |

*See Approved Rim Contours section



Titan Super Hi-Power Lug II Radial R-1

- Single bar design with wide overlapping lugs
- Deep tread cuts through soil and penetrates easily for maximum traction
- Also provides excellent tread wear and durability

| Catalog # | Tire Size | Design | TL/TT | Load Rating | Inflation Pressure (psi) | Max Speed (mph) | Max Load (lbs) | Recom'd Rim Width* (in) | Tire Width (in) | Overall Diameter (in) | Static Loaded Radius (in) | Rolling Circ. (in) | Flat Plate Area (in ²) | Weight (lbs) | Tread Depth 32nd in. | Number of Lugs |
|-----------|-----------|-----------------------|-------|-------------|--------------------------|-----------------|----------------|-------------------------|-----------------|-----------------------|---------------------------|--------------------|------------------------------------|--------------|----------------------|----------------|
| 49T252 | 20.8R42 | Super Hi-Power Lug II | TL | 155A8/B | 24 | 30 | 8,550 | 18 | 21.2 | 76.5 | 35 | 230 | 400E | 496 | 55 | NA |

*See Approved Rim Contours section



Titan Hi Load Radial R-1S

- Delivers superior tread wear
- Reduced lug-induced vibration
- Higher load capabilities over standard R-1 radials
- Stability at transport speeds

| Catalog # | Tire Size | Design | TL/TT | Load Rating | Inflation Pressure (psi) | Max Speed (mph) | Max Load (lbs) | Recom'd Rim Width* (in) | Tire Width (in) | Overall Diameter (in) | Static Loaded Radius (in) | Rolling Circ. (in) | Flat Plate Area (in ²) | Weight (lbs) | Tread Depth 32nd in. | Number of Lugs |
|-----------|-----------|----------------|-------|-------------|--------------------------|-----------------|----------------|-------------------------|-----------------|-----------------------|---------------------------|--------------------|------------------------------------|--------------|----------------------|----------------|
| 48S532 | 380/90R46 | Hi Load Radial | TL | 154A8/B | 42 | 30 | 8,250 | 13 | 15.7 | 72.3 | 34 | 218 | 234 | 352 | 41 | 48 |
| 48S832 | 380/90R46 | Hi Load Radial | TL | 164A8/B | 68 | 30 | 11,000 | 13 | 15.7 | 72.3 | 34 | 218 | 234 | 393 | 41 | 48 |
| 48S032 | 380/90R46 | Hi Load Radial | TL | 168A8/B | 78 | 30 | 12,300 | 13 | 15.7 | 72.3 | 34 | 218 | 234 | 405 | 41 | 48 |

*See Approved Rim Contours section

Titan

Bias R-1



Titan Hi Traction Lug R-1

- Exclusive long bar/medium bar tread pattern
- This design follows a symmetrical lug pattern to eliminate side-to-side rocking and promotes even wear

| Catalog # | Tire Size | Design | TL/TT | Load Rating | Inflation Pressure (psi) | Max Speed (mph) | Max Load (lbs) | Recom'd Rim Width* (in) | Tire Width (in) | Overall Diameter (in) | Static Loaded Radius (in) | Rolling Circ. (in) | Flat Plate Area (in ²) | Weight (lbs) | Tread Depth 32nd in. | Number of Lugs |
|-----------|-----------|-----------------|-------|-------------|--------------------------|-----------------|----------------|-------------------------|-----------------|-----------------------|---------------------------|--------------------|------------------------------------|--------------|----------------------|----------------|
| 48D665 | 7-14 | Hi Traction Lug | TL | 6 | 36 | 20 | 990 | 6 | 6.7 | 27.5 | 12.7 | 83 | 66 | 26 | 33 | 44 |
| 48D865 | 7-14 | Hi Traction Lug | TL | 8 | 48 | 20 | 1,170 | 6 | 6.7 | 27.5 | 12.7 | 83 | 66 | 27 | 33 | 44 |
| 48D666 | 7-16 | Hi Traction Lug | TL | 6 | 36 | 20 | 1,100 | 6 | 7.5 | 29.8 | 14.7 | 89 | 68 | 32 | 34 | 44 |
| 48D066 | 7-16 | Hi Traction Lug | TL | 10 | 60 | 20 | 1,480 | 6 | 7.5 | 29.8 | 14.7 | 89 | 68 | 36 | 34 | 44 |
| 48D667 | 8-16** | Hi Traction Lug | TL | 6 | 28 | 20 | 1,360 | 6 | 8.4 | 31.1 | 14.4 | 96 | 80 | 36 | 31 | 44 |
| 48D067 | 8-16 | Hi Traction Lug | TL | 10 | 48 | 20 | 1,870 | 6 | 8 | 30.5 | 13.9 | 91 | 80 | 38 | 31 | 44 |
| 48D684 | 8.3-24 | Hi Traction Lug | TL | 6 | 34 | 20 | 1,610 | 7 | 8.3 | 39.1 | 18.2 | 117 | 60 | 56 | 37 | 48 |
| 48D695 | 9.5-16 | Hi Traction Lug | TL | 6 | 30 | 20 | 1,390 | 8 | 9.7 | 33.6 | 14.1 | 101 | 54 | 50 | 40 | 44 |
| 48D663 | 9.5-20 | Hi Traction Lug | TL | 6 | 30 | 20 | 1,650 | 8 | 9.3 | 37.5 | 17.1 | 113 | 88 | 57 | 41 | 48 |
| 48D694 | 9.5-24 | Hi Traction Lug | TL | 6 | 30 | 25 | 1,870 | 8 | 9.4 | 42 | 19.8 | 126 | 87 | 65 | 41 | 48 |
| 48D404 | 11.2-24 | Hi Traction Lug | TL | 4 | 18 | 25 | 1,650 | 10 | 11.8 | 43.6 | 20.1 | 130 | 99 | 88 | 43 | 44 |
| 48D604 | 11.2-24 | Hi Traction Lug | TL | 6 | 26 | 25 | 2,090 | 10 | 11.8 | 43.6 | 20.1 | 130 | 99 | 100 | 43 | 44 |
| 48D804 | 11.2-24 | Hi Traction Lug | TL | 8 | 36 | 25 | 2,540 | 10 | 11.8 | 43.6 | 20.1 | 130 | 99 | 102 | 43 | 44 |
| 47D804 | 11.2-24 | Hi Traction Lug | TT | 8 | 36 | 25 | 2,540 | 10 | 11.8 | 43.6 | 20.1 | 130 | 99 | 92 | 43 | 44 |
| 48D004 | 11.2-24 | Hi Traction Lug | TL | 10 | 44 | 25 | 2,830 | 10 | 11.8 | 43.6 | 20.1 | 130 | 99 | 106 | 43 | 44 |
| 48D410 | 11.2-28 | Hi Traction Lug | TL | 4 | 18 | 25 | 1,760 | 10 | 11.8 | 47.6 | 22.1 | 147 | 100E | 101 | 43 | 48 |
| 48D414 | 12.4-24 | Hi Traction Lug | TL | 4 | 16 | 25 | 1,870 | 11 | 12.2 | 45.7 | 21.2 | 137 | 110 | 108 | 44 | 44 |
| 48D614 | 12.4-24 | Hi Traction Lug | TL | 6 | 24 | 25 | 2,400 | 11 | 12.2 | 45.7 | 21.2 | 137 | 110 | 113 | 44 | 44 |
| 48D814 | 12.4-24 | Hi Traction Lug | TL | 8 | 32 | 25 | 2,830 | 11 | 12.2 | 45.7 | 21.2 | 137 | 110 | 114 | 44 | 44 |
| 48D114 | 12.4-24 | Hi Traction Lug | TL | 12 | 48 | 25 | 3,520 | 11 | 12.2 | 45.7 | 21.2 | 137 | 110 | 130 | 44 | 44 |
| 48D412 | 12.4-28 | Hi Traction Lug | TL | 4 | 16 | 25 | 1,980 | 11 | 13 | 49.8 | 23.1 | 152 | 150E | 108 | 44 | 48 |
| 48D612 | 12.4-28 | Hi Traction Lug | TL | 6 | 24 | 25 | 2,540 | 11 | 13 | 49.8 | 23.1 | 152 | 150E | 114 | 44 | 48 |
| 47D619 | 12.4-42 | Hi Traction Lug | TT | 6 | 24 | 25 | 3,080 | 11 | 12.5 | 64.5 | 30.3 | 193 | 155E | 158 | 32 | 60 |
| 48D019 | 12.4-42 | Hi Traction Lug | TL | 10 | 40 | 25 | 4,180 | 11 | 12.5 | 64.5 | 30.3 | 193 | 155E | 183 | 48 | 60 |
| 48D119 | 12.4-42 | Hi Traction Lug | TL | 12 | 48 | 25 | 4,680 | 11 | 12.5 | 64.5 | 30.3 | 193 | 155E | 184 | 48 | 60 |
| 48D422 | 13.6-24 | Hi Traction Lug | TL | 4 | 14 | 25 | 2,040 | 12 | 14.3 | 47.9 | 21.9 | 143 | 143E | 132 | 46 | 48 |
| 48D622 | 13.6-24 | Hi Traction Lug | TL | 6 | 22 | 25 | 2,680 | 12 | 14.3 | 47.9 | 21.9 | 143 | 143E | 133 | 46 | 48 |
| 48D822 | 13.6-24 | Hi Traction Lug | TL | 8 | 28 | 25 | 3,080 | 12 | 14.3 | 47.9 | 21.9 | 143 | 143E | 141 | 46 | 48 |
| 47D424 | 13.6-28 | Hi Traction Lug | TT | 4 | 14 | 25 | 2,200 | 12 | 14.3 | 51.9 | 23.9 | 158 | 156E | 127 | 46 | 48 |
| 48D424 | 13.6-28** | Hi Traction Lug | TL | 4 | 14 | 25 | 2,200 | 12 | 14 | 52.1 | 24.1 | 160 | 147 | 136 | 46 | 48 |
| 47D624 | 13.6-28 | Hi Traction Lug | TT | 6 | 22 | 25 | 2,830 | 12 | 14.3 | 51.9 | 23.9 | 158 | 156E | 133 | 46 | 48 |
| 48D624 | 13.6-28 | Hi Traction Lug | TL | 6 | 22 | 25 | 2,830 | 12 | 14.3 | 51.9 | 23.9 | 158 | 156E | 143 | 46 | 48 |
| 47D824 | 13.6-28 | Hi Traction Lug | TT | 8 | 28 | 25 | 3,300 | 12 | 14.3 | 51.9 | 23.9 | 158 | 156E | 134 | 46 | 48 |
| 48D024 | 13.6-28 | Hi Traction Lug | TL | 10 | 36 | 25 | 3,740 | 12 | 14.3 | 51.9 | 23.9 | 158 | 156E | 151 | 46 | 48 |
| 48D434 | 14.9-24 | Hi Traction Lug | TL | 4 | 12 | 25 | 2,200 | 13 | 15.4 | 50.4 | 22.7 | 150 | 150E | 126 | 47 | 48 |
| 47D634 | 14.9-24 | Hi Traction Lug | TT | 6 | 20 | 25 | 3,000 | 13 | 15.4 | 50.4 | 22.7 | 150 | 150E | 132 | 47 | 48 |
| 48D634 | 14.9-24 | Hi Traction Lug | TL | 6 | 20 | 25 | 3,000 | 13 | 15.4 | 50.4 | 22.7 | 150 | 150E | 144 | 47 | 48 |
| 48D834 | 14.9-24 | Hi Traction Lug | TL | 8 | 26 | 25 | 3,520 | 13 | 15.4 | 50.4 | 22.7 | 150 | 150E | 146 | 47 | 48 |
| 47D638 | 14.9-28 | Hi Traction Lug | TT | 6 | 20 | 25 | 3,200 | 13 | 15.7 | 54.1 | 24.8 | 163 | 163E | 133 | 47 | 48 |
| 48D638 | 14.9-28 | Hi Traction Lug | TL | 6 | 20 | 25 | 3,200 | 13 | 15.7 | 54.1 | 24.8 | 163 | 163E | 140 | 47 | 48 |
| 48D038 | 14.9-28 | Hi Traction Lug | TL | 10 | 32 | 25 | 4,180 | 13 | 15.7 | 54.1 | 24.8 | 163 | 163E | 162 | 47 | 48 |

Bias R-1

Titan

| Catalog # | Tire Size | Design | TL/TT | Load Rating | Inflation Pressure (psi) | Max Speed (mph) | Max Load (lbs) | Recom'd Rim Width* (in) | Tire Width (in) | Overall Diameter (in) | Static Loaded Radius (in) | Rolling Circ. (in) | Flat Plate Area (in ²) | Weight (lbs) | Tread Depth 32nd in. | Number of Lugs |
|-----------|-----------|-------------------|-------|-------------|--------------------------|-----------------|----------------|-------------------------|-----------------|-----------------------|---------------------------|--------------------|------------------------------------|--------------|----------------------|----------------|
| 48D030 | 14.9-30 | Hi Traction Lug | TL | 10 | 32 | 25 | 4,300 | 13 | 15.7 | 56.1 | 25.8 | 169 | 168E | 196 | 47 | 48 |
| 47D674 | 15.5-38 | Hi Traction Lug | TT | 6 | 20 | 25 | 3,520 | 14 | 15.9 | 62.7 | 29.3 | 189 | 175E | 185 | 46 | 44 |
| 47D874 | 15.5-38 | Hi Traction Lug | TT | 8 | 26 | 25 | 4,080 | 14 | 15.9 | 62.7 | 29.3 | 189 | 175E | 186 | 46 | 44 |
| 48D645 | 16.9-24 | Hi Traction Lug | TL | 6 | 18 | 25 | 3,420 | 15 | 17.8 | 53 | 24 | 157 | 190E | 166 | 48 | 44 |
| 48D845 | 16.9-24 | Hi Traction Lug | TL | 8 | 24 | 25 | 4,080 | 15 | 17.8 | 53 | 24 | 157 | 190E | 166 | 48 | 44 |
| 48D646 | 16.9-26 | Hi Traction Lug | TL | 6 | 18 | 25 | 3,520 | 15 | 17.7 | 55 | 25 | 164 | 196E | 174 | 48 | 48 |
| 48D046 | 16.9-26 | Hi Traction Lug | TL | 10 | 28 | 25 | 4,540 | 15 | 17.7 | 55 | 25 | 164 | 196E | 191 | 48 | 48 |
| 48D648 | 16.9-28 | Hi Traction Lug | TL | 6 | 18 | 25 | 3,640 | 15 | 17.8 | 57 | 26 | 170 | 202E | 180 | 48 | 48 |
| 47D848 | 16.9-28 | Hi Traction Lug | TT | 8 | 24 | 25 | 4,300 | 15 | 17.8 | 57 | 26 | 170 | 202E | 169 | 48 | 48 |
| 48D048 | 16.9-28 | Hi Traction Lug | TL | 10 | 28 | 25 | 4,680 | 15 | 17.8 | 57 | 26 | 170 | 202E | 199 | 48 | 48 |
| 47D679 | 16.9-30 | Hi Traction Lug | TT | 6 | 18 | 25 | 3,740 | 15 | 17.8 | 59 | 27 | 176 | 209E | 181 | 48 | 52 |
| 48D679 | 16.9-30 | Hi Traction Lug | TL | 6 | 18 | 25 | 3,740 | 15 | 17.8 | 59 | 27 | 176 | 209E | 203 | 48 | 52 |
| 47D879 | 16.9-30 | Hi Traction Lug | TT | 8 | 24 | 25 | 4,400 | 15 | 17.8 | 59 | 27 | 176 | 209E | 185 | 48 | 52 |
| 48D379 | 16.9-30 | Hi Traction Lug | TL | 14 | 40 | 25 | 6,000 | 15 | 17.8 | 59 | 27 | 176 | 209E | 223 | 48 | 52 |
| 47D644 | 16.9-34 | Hi Traction Lug | TT | 6 | 18 | 25 | 3,960 | 15 | 17.8 | 63 | 29 | 188 | 222E | 190 | 48 | 52 |
| 47D844 | 16.9-34 | Hi Traction Lug | TT | 8 | 24 | 25 | 4,680 | 15 | 17.8 | 63 | 29 | 188 | 222E | 191 | 48 | 52 |
| 47D620 | 16.9-38 | Hi Traction Lug | TT | 6 | 18 | 25 | 4,180 | 15 | 17.8 | 67 | 31 | 200 | 235E | 198 | 48 | 56 |
| 48D620 | 16.9-38 | Hi Traction Lug | TL | 6 | 18 | 25 | 4,180 | 15 | 17.8 | 67 | 31 | 200 | 235E | 218 | 48 | 56 |
| 47D820 | 16.9-38 | Hi Traction Lug | TT | 8 | 24 | 25 | 4,940 | 15 | 17.8 | 67 | 31 | 200 | 235E | 206 | 48 | 56 |
| 48D890 | 18.4-16.1 | Hi Traction Lug | TL | 8 | 20 | 25 | 2,910 | 16 | 18.6 | 44.7 | 20.9 | 135 | 158E | 168 | 50 | 44 |
| 48D656 | 18.4-26 | Hi Traction Lug | TL | 6 | 16 | 25 | 3,960 | 16 | 19.4 | 57.7 | 26.2 | 171 | 246E | 196 | 50 | 48 |
| 48D056 | 18.4-26 | Hi Traction Lug | TL | 10 | 26 | 25 | 5,200 | 16 | 19.4 | 57.7 | 26.2 | 171 | 246E | 215 | 50 | 48 |
| 48D156 | 18.4-26 | Hi Traction Lug | TL | 12 | 32 | 25 | 5,840 | 16 | 19.4 | 57.7 | 26.2 | 171 | 246E | 222 | 50 | 48 |
| 48D556 | 18.4-26 | Hi Traction Lug | TL | 16 | 42 | 25 | 6,950 | 16 | 19.4 | 57.7 | 26.2 | 171 | 246E | 243 | 50 | 48 |
| 48D756# | 18.4-26 | Hi Traction Lug | TL | 18 | 46 | 25 | 7,400 | 16 | 19.4 | 57.7 | 26.2 | 171 | 246E | 243 | 50 | 48 |
| 48D650 | 18.4-30 | Hi Traction Lug | TL | 6 | 16 | 25 | 4,180 | 16 | 19.4 | 61.7 | 28.2 | 183 | 263E | 232 | 50 | 52 |
| 47D850 | 18.4-30 | Hi Traction Lug | TT | 8 | 20 | 25 | 4,800 | 16 | 19.4 | 61.7 | 28.2 | 183 | 263E | 209 | 50 | 52 |
| 48D150 | 18.4-30 | Hi Traction Lug | TL | 12 | 32 | 25 | 6,400 | 16 | 19.4 | 61.7 | 28.2 | 183 | 263E | 262 | 50 | 52 |
| 48D550 | 18.4-30 | Hi Traction Lug | TL | 16 | 42 | 25 | 7,400 | 16 | 19.4 | 61.7 | 28.2 | 183 | 263E | 287 | 50 | 52 |
| 47D654 | 18.4-34 | Hi Traction Lug | TT | 6 | 16 | 25 | 4,400 | 16 | 19.4 | 65.7 | 30.2 | 195 | 279E | 215 | 50 | 56 |
| 47D854 | 18.4-34 | Hi Traction Lug | TT | 8 | 20 | 25 | 5,080 | 16 | 19.4 | 65.7 | 30.2 | 195 | 279E | 221 | 50 | 56 |
| 48D054 | 18.4-34 | Hi Traction Lug | TL | 10 | 26 | 25 | 6,000 | 16 | 19.4 | 65.7 | 30.2 | 195 | 279E | 265 | 50 | 56 |
| 47D677 | 18.4-38 | Hi Traction Lug | TT | 6 | 16 | 25 | 4,680 | 16 | 19.4 | 69.7 | 32.2 | 206 | 295E | 247 | 50 | 60 |
| 47D877 | 18.4-38 | Hi Traction Lug | TT | 8 | 20 | 25 | 5,360 | 16 | 19.4 | 69.7 | 32.2 | 206 | 295E | 252 | 50 | 60 |
| 47D801 | 20.8-34 | Hi Traction Lug | TT | 8 | 18 | 25 | 5,840 | 18 | 21.7 | 68.9 | 31.5 | 203 | 322E | 290 | 51 | 56 |
| 47D889 | 20.8-38 | Hi Traction Lug | TT | 8 | 18 | 25 | 6,150 | 18 | 21.7 | 72.9 | 33.5 | 214 | 341E | 317 | 51 | 60 |
| 47D089 | 20.8-38 | Hi Traction Lug | TT | 10 | 22 | 25 | 6,950 | 18 | 21.7 | 72.9 | 33.5 | 214 | 341E | 315 | 51 | 60 |
| 47D389 | 20.8-38 | Hi Traction Lug | TT | 14 | 32 | 25 | 8,550 | 18 | 21.7 | 72.9 | 33.5 | 214 | 341E | 414 | 51 | 60 |
| 48D389 | 20.8-38 | Hi Traction Lug | TL | 14 | 32 | 25 | 8,550 | 18 | 21.7 | 72.9 | 33.5 | 214 | 341E | 396 | 51 | 60 |
| 48DD89 | 20.8-38 | Hi Load Harvester | TL | 28 | 62 | 25 | 12,800 | 18 | 21.7 | 72.9 | 33.5 | 214 | 341E | 456 | 51 | 60 |
| 48D886 | 23.1-26 | Hi Traction Lug | TL | 8 | 16 | 25 | 5,680 | 20 | 24.1 | 64.3 | 28.9 | 187 | 322E | 311 | 52 | 48 |
| 48D086 | 23.1-26 | Hi Traction Lug | TL | 10 | 20 | 25 | 6,400 | 20 | 24.1 | 64.3 | 28.9 | 187 | 322E | 334 | 52 | 48 |
| 48D186 | 23.1-26 | Hi Traction Lug | TL | 12 | 24 | 25 | 7,150 | 20 | 24.1 | 64.3 | 28.9 | 187 | 322E | 345 | 52 | 48 |
| 48D586 | 23.1-26 | Hi Traction Lug | TL | 16 | 34 | 25 | 8,800 | 20 | 24.1 | 64.3 | 28.9 | 187 | 322E | 343 | 52 | 48 |
| 47D888 | 23.1-34 | Hi Traction Lug | TT | 8 | 16 | 25 | 6,400 | 20 | 24.1 | 72.3 | 32.9 | 211 | 364E | 303 | 52 | 52 |
| 48D088 | 23.1-34 | Hi Traction Lug | TL | 10 | 20 | 25 | 7,400 | 20 | 24.1 | 72.3 | 32.9 | 211 | 364E | 339 | 52 | 52 |

#Minimum Order Quantity

**ECE certified

Titan

Bias R-1

| Catalog # | Tire Size | Design | TL/TT | Load Rating | Inflation Pressure (psi) | Max Speed (mph) | Max Load (lbs) | Recom'd Rim Width* (in) | Tire Width (in) | Overall Diameter (in) | Static Loaded Radius (in) | Rolling Circ. (in) | Flat Plate Area (in ²) | Weight (lbs) | Tread Depth 32nd in. | Number of Lugs |
|-----------|-----------|-----------------|-------|-------------|--------------------------|-----------------|----------------|-------------------------|-----------------|-----------------------|---------------------------|--------------------|------------------------------------|--------------|----------------------|----------------|
| 48D099 | 24.5-32 | Hi Traction Lug | TL | 10 | 20 | 25 | 7,850 | 21 | 25.5 | 72.2 | 32.7 | 210 | 364E | 402 | 53 | 48 |
| 48D199 | 24.5-32 | Hi Traction Lug | TL | 12 | 24 | 25 | 8,800 | 21 | 25.5 | 72.2 | 32.7 | 210 | 364E | 447 | 53 | 48 |
| 48D399 | 24.5-32 | Hi Traction Lug | TL | 14 | 28 | 25 | 9,650 | 21 | 25.5 | 72.2 | 32.7 | 210 | 364E | 448 | 53 | 48 |
| 48D599 | 24.5-32 | Hi Traction Lug | TL | 16 | 30 | 25 | 9,900 | 21 | 25.5 | 72.2 | 32.7 | 210 | 364E | 448 | 53 | 48 |
| 48DB99 | 24.5-32 | Hi Traction Lug | TL | 24 | 46 | 25 | 12,800 | 21 | 25.5 | 72.2 | 32.7 | 210 | 364E | 441 | 53 | 48 |
| 48D196 | 30.5L-32 | Hi Traction Lug | TL | 12 | 20 | 25 | 9,350 | 27 | 31.9 | 71.8 | 32.5 | 209 | 468E | 550 | 54 | 48 |
| 48D596 | 30.5L-32 | Hi Traction Lug | TL | 16 | 26 | 25 | 11,000 | 27 | 31.9 | 71.8 | 32.5 | 209 | 468E | 583 | 54 | 48 |

*See Approved Rim Contours section



Titan Tru Grip Lug R-1

- Single bar design with wide overlapping lugs
- Deep Tread and excellent tread wear and durability
- Designed to deliver power to the ground
- Design offers maximum cleaning and sidehill slip resistance

| Catalog # | Tire Size | Design | TL/TT | Load Rating | Inflation Pressure (psi) | Max Speed (mph) | Max Load (lbs) | Recom'd Rim Width* (in) | Tire Width (in) | Overall Diameter (in) | Static Loaded Radius (in) | Rolling Circ. (in) | Flat Plate Area (in ²) | Weight (lbs) | Tread Depth 32nd in. | Number of Lugs |
|-----------|-----------|--------------|-------|-------------|--------------------------|-----------------|----------------|-------------------------|-----------------|-----------------------|---------------------------|--------------------|------------------------------------|--------------|----------------------|----------------|
| 496814 | 12.4-24 | Tru Grip Lug | TL | 8 | 32 | 30 | 2,830 | 10 | 12.0 | 45.5 | 20.5 | 136 | 137 | 100 | 42 | 36 |

*See Approved Rim Contours section



Titan Hi Power Lug R-1

- Single Bar Design with wide overlapping lugs
- Deep Tread and excellent tread wear and durability
- Designed to deliver power to the ground
- Design offers maximum cleaning and sidehill slip resistance

| Catalog # | Tire Size | Design | TL/TT | Load Rating | Inflation Pressure (psi) | Max Speed (mph) | Max Load (lbs) | Recom'd Rim Width* (in) | Tire Width (in) | Overall Diameter (in) | Static Loaded Radius (in) | Rolling Circ. (in) | Flat Plate Area (in ²) | Weight (lbs) | Tread Depth 32nd in. | Number of Lugs |
|-----------|-----------|----------|-------|-------------|--------------------------|-----------------|----------------|-------------------------|-----------------|-----------------------|---------------------------|--------------------|------------------------------------|--------------|----------------------|----------------|
| 473404 | 11.2-24 | Hi Power | TT | 4 | 18 | 25 | 1,650 | 10 | 11.6 | 43.5 | 20.1 | 130 | 99 | 76 | 42 | 36 |
| 483404 | 11.2-24 | Hi Power | TL | 4 | 18 | 25 | 1,650 | 10 | 11.6 | 43.5 | 20.1 | 130 | 99 | 88 | 42 | 36 |
| 483604 | 11.2-24 | Hi Power | TL | 6 | 26 | 25 | 2,090 | 10 | 11.6 | 43.5 | 20.1 | 130 | 99E | 92 | 42 | 36 |
| 483804 | 11.2-24 | Hi Power | TL | 8 | 36 | 25 | 2,540 | 10 | 11.6 | 43.5 | 20.1 | 130 | 99E | 102 | 42 | 36 |
| 473408 | 11.2-38 | Hi Power | TT | 4 | 18 | 25 | 2,090 | 10 | 11.6 | 57.5 | 27.1 | 174 | 115E | 114 | 42 | 44 |
| 483408 | 11.2-38 | Hi Power | TL | 4 | 18 | 25 | 2,090 | 10 | 11.6 | 57.5 | 27.1 | 174 | 115E | 122 | 42 | 44 |
| 483608 | 11.2-38 | Hi Power | TL | 6 | 26 | 25 | 2,540 | 10 | 11.6 | 57.5 | 27.1 | 174 | 115E | 124 | 42 | 44 |
| 473418 | 12.4-38 | Hi Power | TT | 4 | 16 | 25 | 2,340 | 11 | 12.9 | 59.6 | 28 | 181 | 145E | 135 | 44 | 44 |
| 483818 | 12.4-38 | Hi Power | TL | 8 | 32 | 25 | 3,520 | 11 | 12.9 | 59.6 | 28 | 181 | 145E | 164 | 44 | 44 |
| 483118 | 12.4-38 | Hi Power | TL | 12 | 48 | 25 | 4,400 | 11 | 12.9 | 59.6 | 28 | 181 | 145E | 182 | 44 | 44 |
| 473624 | 13.6-28 | Hi Power | TT | 6 | 22 | 25 | 2,830 | 12 | 14.1 | 51.6 | 23.7 | 157 | 156E | 127 | 46 | 44 |
| 473628 | 13.6-38 | Hi Power | TT | 6 | 22 | 25 | 3,300 | 12 | 14.1 | 61.6 | 28.8 | 186 | 181E | 155 | 46 | 44 |
| 483128 | 13.6-38 | Hi Power | TL | 12 | 42 | 25 | 4,800 | 12 | 14.1 | 61.6 | 28.8 | 186 | 181E | 219 | 46 | 44 |
| 473434 | 14.9-24 | Hi Power | TT | 4 | 12 | 25 | 2,200 | 13 | 15.5 | 49.8 | 22.7 | 148 | 150E | 105 | 47 | 36 |
| 483434 | 14.9-24 | Hi Power | TL | 4 | 12 | 25 | 2,200 | 13 | 15.5 | 49.8 | 22.7 | 148 | 150E | 126 | 47 | 36 |
| 473634 | 14.9-24 | Hi Power | TT | 6 | 20 | 25 | 3,000 | 13 | 15.5 | 49.8 | 22.7 | 148 | 150E | 131 | 47 | 36 |
| 483634 | 14.9-24 | Hi Power | TL | 6 | 20 | 25 | 3,000 | 13 | 15.5 | 49.8 | 22.7 | 148 | 150E | 144 | 47 | 36 |

Bias R-1

Titan

| Catalog # | Tire Size | Design | TL/TT | Load Rating | Inflation Pressure (psi) | Max Speed (mph) | Max Load (lbs) | Recom'd Rim Width* (in) | Tire Width (in) | Overall Diameter (in) | Static Loaded Radius (in) | Rolling Circ. (in) | Flat Plate Area (in ²) | Weight (lbs) | Tread Depth 32nd in. | Number of Lugs |
|-----------|-----------|----------|-------|-------------|--------------------------|-----------------|----------------|-------------------------|-----------------|-----------------------|---------------------------|--------------------|------------------------------------|--------------|----------------------|----------------|
| 473631 | 14.9-26 | Hi Power | TT | 6 | 20 | 25 | 3,080 | 13 | 15.1 | 51.8 | 23 | 156 | 155E | 152 | 47 | 36 |
| 483631 | 14.9-26 | Hi Power | TL | 6 | 20 | 25 | 3,080 | 13 | 15.1 | 51.8 | 23 | 156 | 155E | 159 | 47 | 36 |
| 483031 | 14.9-26 | Hi Power | TT | 10 | 32 | 25 | 4,080 | 13 | 15.1 | 51.8 | 23 | 156 | 155E | 185 | 47 | 36 |
| 483838 | 14.9-28 | Hi Power | TL | 8 | 26 | 25 | 3,740 | 13 | 15.2 | 54.9 | 24.6 | 164 | 160E | 148 | 47 | 36 |
| 483038# | 14.9-28 | Hi Power | TL | 10 | 32 | 25 | 4,180 | 13 | 15.2 | 54.9 | 24.6 | 164 | 160E | 162 | 47 | 36 |
| 473673 | 14.9-38 | Hi Power | TT | 6 | 32 | 25 | 4,300 | 13 | 15.1 | 63.8 | 29.7 | 192 | 170E | 191 | 47 | 44 |
| 473674 | 15.5-38 | Hi Power | TT | 6 | 20 | 25 | 3,520 | 14 | 15.7 | 61.8 | 28.9 | 187 | 176E | 186 | 46 | 36 |
| 473679# | 16.9-30 | Hi Power | TT | 6 | 18 | 25 | 3,740 | 15 | 17.6 | 58.5 | 26.8 | 175 | 209E | 181 | 48 | 40 |
| 473658 | 18.4-28 | Hi Power | TT | 6 | 16 | 25 | 4,080 | 16 | 19.1 | 59.1 | 26.9 | 175 | 250E | 183 | 50 | 36 |
| 473850 | 18.4-30 | Hi Power | TT | 8 | 20 | 25 | 4,800 | 16 | 19.1 | 61.1 | 27.9 | 181 | 263E | 209 | 50 | 40 |
| 483850 | 18.4-30 | Hi Power | TL | 8 | 20 | 25 | 4,800 | 16 | 19.1 | 61.1 | 27.9 | 181 | 263E | 233 | 50 | 40 |
| 473654 | 18.4-34 | Hi Power | TT | 6 | 16 | 25 | 4,400 | 16 | 19.1 | 65.1 | 29.9 | 193 | 279E | 215 | 50 | 40 |
| 473877 | 18.4-38 | Hi Power | TT | 8 | 20 | 25 | 5,360 | 16 | 19.1 | 69.1 | 31.9 | 205 | 295E | 266 | 50 | 44 |
| 473889# | 20.8-38 | Hi Power | TT | 8 | 18 | 25 | 6,150 | 18 | 21.6 | 72.2 | 33.2 | 213 | 341E | 315 | 51 | 44 |
| 483086 | 23.1-26 | Hi Power | TL | 10 | 20 | 25 | 6,400 | 20 | 24 | 62.5 | 28.1 | 183 | 322E | 345 | 52 | 36 |
| 473882 | 23.1-30 | Hi Power | TT | 8 | 16 | 25 | 6,000 | 20 | 24 | 66.5 | 30.1 | 195 | 340E | 326 | 52 | 40 |
| 483082 | 23.1-30 | Hi Power | TL | 10 | 20 | 25 | 6,800 | 20 | 24 | 66.5 | 30.1 | 195 | 340E | 368 | 52 | 40 |
| 48Q196 | 30.5L-32 | Hi Power | TL | 12 | 26 | 25 | 9,350 | 27 | 31.1 | 71.5 | 31.9 | 213 | 468E | 583 | 59 | 36 |

*See Approved Rim Contours section
#Minimum Order Quantity



Titan Tru Power R-1

- Ultimate deep-traction tire with a large contact area to provide the best traction
- A great performer on wet or dry surfaces
- Features a specially designed rim guard to keep debris from the bead seat area

| Catalog # | Tire Size | Design | TL/TT | Load Rating | Inflation Pressure (psi) | Max Speed (mph) | Max Load (lbs) | Recom'd Rim Width* (in) | Tire Width (in) | Overall Diameter (in) | Static Loaded Radius (in) | Rolling Circ. (in) | Flat Plate Area (in ²) | Weight (lbs) | Tread Depth 32nd in. | Number of Lugs |
|-----------|--------------|-----------|-------|-------------|--------------------------|-----------------|----------------|-------------------------|-----------------|-----------------------|---------------------------|--------------------|------------------------------------|--------------|----------------------|----------------|
| 4233F5 | 5-12 | Tru Power | TL | 4 | 34 | 20 | 495 | 4 | 5 | 20.8 | 9.6 | 62 | na | 11 | 20 | NA |
| 4233C3 | 6-12 | Tru Power | TL | 4 | 28 | 20 | 600 | 5 | 5.7 | 22.7 | 10.3 | 70 | na | 15 | 20 | 32 |
| 4234C3 | 6-12 | Tru Power | TL | 6 | 42 | 20 | 760 | 5 | 5.7 | 22.7 | 10.3 | 70 | na | 17 | 20 | 32 |
| 423382 | 7-12 | Tru Power | TL | 4 | 24 | 20 | 715 | 6 | 6.5 | 23.9 | 10.9 | 72 | na | 21 | 23 | 32 |
| 423682 | 7-12 | Tru Power | TL | 6 | 36 | 20 | 910 | 6 | 6.5 | 23.9 | 10.9 | 72 | na | 21 | 23 | 32 |
| 423C82 | 180/85D12 ** | Tru Power | TL | 77A8/B | 20 | 30 | 910 | 6 | 7.2 | 23.9 | 10.7 | 71.4 | 50 | 21 | 23 | 32 |
| 423383 | 12.4-16 ** | Tru Power | TL | 6 | 24 | 20 | 1,820 | 10 | 12.7 | 37.6 | 17.2 | 115 | 77 | 72 | 32 | 40 |
| 423B83 | 320/85D16** | Tru Power | TL | 104A8/B | 15 | 30 | 1,980 | 10 | 12.7 | 37.6 | 16.7 | 111 | 150 | 72 | 32 | 40 |

*See Approved Rim Contours section
** ECE Certified

Titan

Bias R-1



Titan Farm Tractor R-1

- Great size range for antique and older tractors
- The open 45 degree lug provides self-cleaning and traction benefits

| Catalog # | Tire Size | Design | TL/TT | Load Rating | Inflation Pressure (psi) | Max Speed (mph) | Max Load (lbs) | Recom'd Rim Width* (in) | Tire Width (in) | Overall Diameter (in) | Static Loaded Radius (in) | Rolling Circ. (in) | Flat Plate Area (in ²) | Weight (lbs) | Tread Depth 32nd in. | Number of Lugs |
|-----------|-----------|--------------|-------|-------------|--------------------------|-----------------|----------------|-------------------------|-----------------|-----------------------|---------------------------|--------------------|------------------------------------|--------------|----------------------|----------------|
| 470402 | 11.2-34 | Farm Tractor | TT | 4 | 18 | 25 | 1,980 | 10 | 11.6 | 53.4 | 25.1 | 164 | na | 98 | 42 | 44 |
| 470406 | 11.2-36 | Farm Tractor | TT | 4 | 18 | 25 | 2,040 | 10 | 11.2 | 55.4 | 26.1 | 170 | na | 93 | 44 | 46 |
| 470416 | 12.4-36 | Farm Tractor | TL | 4 | 16 | 25 | 2,270 | 11 | 12.6 | 57.1 | 26.4 | 171 | na | 116 | 44 | NA |
| 470616 | 12.4-36 | Farm Tractor | TT | 6 | 24 | 25 | 2,830 | 11 | 12.6 | 57.1 | 26.4 | 171 | na | 131 | 44 | NA |
| 470693 | 13.9-36 | Farm Tractor | TT | 6 | 20 | 25 | 3,200 | 12 | 14.2 | 58.7 | 27.4 | 178 | na | 133 | 44 | 48 |

*See Approved Rim Contours section



Titan Traction Drive R-1

- Titan's Traction Drive R-1 tire is designed for irrigation service with minimal soil compaction and excellent wear

| Catalog # | Tire Size | Design | TL/TT | Load Rating | Inflation Pressure (psi) | Max Speed (mph) | Max Load (lbs) | Recom'd Rim Width* (in) | Tire Width (in) | Overall Diameter (in) | Static Loaded Radius (in) | Rolling Circ. (in) | Flat Plate Area (in ²) | Weight (lbs) | Tread Depth 32nd in. | Number of Lugs |
|-----------|-----------|----------------|-------|-------------|--------------------------|-----------------|----------------|-------------------------|-----------------|-----------------------|---------------------------|--------------------|------------------------------------|--------------|----------------------|----------------|
| 499511 | 14.9-24 | Traction Drive | TL | 4 | 16 | Creep | 4,640 | 13 | 15.4 | 50 | 22.8 | 149 | 150E | 137 | 47 | NA |

*See Approved Rim Contours section



Titan Lift Rigger II R-1

- Combines thicker, self-cleaning lugs in a directional pattern with a low aspect ratio
- Greater lateral stability and flotation than conventional aerial lift tires
- Also available in the stable LSW design

| Catalog # | Tire Size | Design | TL/TT | Load Rating | Inflation Pressure (psi) | Max Speed (mph) | Max Load (lbs) | Recom'd Rim Width* (in) | Tire Width (in) | Overall Diameter (in) | Static Loaded Radius (in) | Rolling Circ. (in) | Flat Plate Area (in ²) | Weight (lbs) | Tread Depth 32nd in. | Number of Lugs |
|-----------|------------|----------------|-------|-------------|--------------------------|-----------------|----------------|-------------------------|-----------------|-----------------------|---------------------------|--------------------|------------------------------------|--------------|----------------------|----------------|
| G3C34L | LSW400-648 | Lift Rigger II | TL | 150A8/B | 61 | 30 | 7,400 | 356 (mm) | 15.7 | 42.9 | 19.3 | 127 | na | 154 | 33 | 32 |
| 43C34L | 400/70-20 | Lift Rigger II | TL | 150A8/B | 61 | 30 | 7,400 | 14 | 15.9 | 42.9 | 19.3 | 127 | na | 164 | 33 | 32 |

*See Approved Rim Contours section



Titan TT415 R-1

- Combine tire features increased contact area for increased flotation
- Turf- and soil-friendly tread pattern

| Catalog # | Tire Size | Design | TL/TT | Load Rating | Inflation Pressure (psi) | Max Speed (mph) | Max Load (lbs) | Recom'd Rim Width* (in) | Tire Width (in) | Overall Diameter (in) | Static Loaded Radius (in) | Rolling Circ. (in) | Flat Plate Area (in ²) | Weight (lbs) | Tread Depth 32nd in. | Number of Lugs |
|-----------|-------------|--------|-------|-------------|--------------------------|-----------------|----------------|-------------------------|-----------------|-----------------------|---------------------------|--------------------|------------------------------------|--------------|----------------------|----------------|
| 4151F3 | 19.5L/60-26 | TT415 | TL | 12 | 48 | 25 | 9,490 | 16 | 19.7 | 49.6 | 21.4 | 146 | na | 214 | 42 | 42 |
| 4151C7 | 23.5L/55-26 | TT415 | TL | 12 | 40 | 25 | 11,540 | 20 | 23.6 | 53.1 | 22.4 | 156 | na | 324 | 49 | 40 |
| 45R1C7 | 23.5L/55R26 | TT415 | TL | 168A8 | 40 | 25 | 11,700 | 20 | 23.6 | 53.1 | 22.4 | 156 | na | 317 | 49 | 40 |

*See Approved Rim Contours section

Radial R-1W

Titan



Titan TT49V Radial R-1W

- Developed for high clearance with the Row Crop market in mind and features a deeper tread than an R-1 tire for improved traction



Titan AG49H Radial R-1W

- Modeled after popular European-style tires
- Specifically designed for soft, moist and sticky soils
- Deep tread for solid traction



Titan AG49M Radial R-1W

- Wide base and wider section width allow for higher loads
- Greater flotation, improved traction and smoother ride

| Catalog # | Tire Size | Design | TL/TT | Load Rating | Inflation Pressure (psi) | Max Speed (mph) | Max Load (lbs) | Recom'd Rim Width* (in) | Tire Width (in) | Overall Diameter (in) | Static Loaded Radius (in) | Rolling Circ. (in) | Flat Plate Area (in ²) | Weight (lbs) | Tread Depth 32nd in. | Number of Lugs |
|-----------|------------|--------|-------|-------------|--------------------------|-----------------|----------------|-------------------------|-----------------|-----------------------|---------------------------|--------------------|------------------------------------|--------------|----------------------|----------------|
| 49V7T3 | 230/115R54 | TT49V | TL | 146A8/B | 64 | 30 | 6,600 | 8 | 10.5 | 76.7 | 36 | 238 | 142 | 316 | 58 | 74 |
| 49V5V4 | 250/95R48 | TT49V | TL | 147A8/B | 73 | 30 | 6,800 | 8 | 9.5 | 67.1 | 31.7 | 206 | 174 | 205 | 56 | 68 |
| 49V7V1 | 290/90R38 | TT49V | TL | 138A8/B | 46 | 30 | 5,200 | 9 | 11.4 | 58.5 | 27.3 | 184 | 153E | 190 | 54 | 56 |
| 49V7V2 | 320/80R42 | TT49V | TL | 130A8/B | 23 | 30 | 4,180 | 10 | 12.5 | 62.2 | 29.2 | 191 | 177E | 225 | 60 | 58 |
| 49V445 | 320/85R38 | TT49V | TL | 138A8/B | 41 | 30 | 5,200 | 10 | 12.6 | 59.4 | 27.3 | 179 | 162E | 221 | 55 | 56 |
| 49V7V8 | 320/90R46 | TT49V | TL | 148A8/B | 52 | 30 | 6,950 | 10 | 12.6 | 68.7 | 32.2 | 210 | 216 | 267 | 54 | 66 |
| 49V7T5 | 320/90R46 | TT49V | TL | 156A8/B | 70 | 30 | 8,800 | 10 | 12.6 | 68.7 | 32.2 | 210 | 216 | 312 | 54 | 66 |
| 49V4V6 | 320/90R50 | TT49V | TL | 156A8/B | 67 | 30 | 8,800 | 10 | 12.5 | 72.6 | 34.2 | 220 | 170 | 327 | 54 | 68 |
| 49V8V6 | 320/90R50 | TT49V | TL | 161A8/B | 78 | 30 | 10,200 | 10 | 12.5 | 72.6 | 34.2 | 220 | 170 | 340 | 54 | 68 |
| 49V743 | 320/90R54 | TT49V | TL | 154A8/B | 60 | 30 | 8,250 | 10 | 12.5 | 76.7 | 35.2 | 233 | 178 | 328 | 56 | 72 |
| 49V843 | 320/90R54 | TT49V | TL | 161A8/B | 75 | 30 | 10,200 | 10 | 12.5 | 76.7 | 35.2 | 233 | 199 | 340 | 56 | 72 |
| 49V7V9 | 380/90R54 | TT49V | TL | 152A8/B | 35 | 30 | 7,850 | 12 | 14.5 | 81.5 | 36.5 | 244 | 270 | 378 | 58 | 78 |
| 49V8V9 | 380/90R54 | TT49V | TL | 162A8/B | 58 | 30 | 10,500 | 12 | 14.5 | 81.5 | 36.5 | 244 | 270 | 402 | 58 | 78 |
| 49M7M3 | 380/80R38 | AG49M | TL | 142A8/B | 35 | 30 | 5,840 | 12 | 15 | 61.9 | 28.7 | 186 | 246 | 243 | 60 | 38 |
| 49H748 | 16.9R28 | AG49H | TL | 136A8/B | 24 | 30 | 4,940 | 15 | 16.8 | 56 | 25.7 | 166 | 228E | 255 | 63 | 38 |
| 49H479 | 16.9R30 | AG49H | TL | 144A8/B | 36 | 30 | 6,150 | 15 | 17.5 | 57.7 | 26.5 | 175 | 233E | 271 | 60 | 36 |
| 49M7M4 | 420/85R34 | AG49M | TL | 147A8/B | 35 | 30 | 6,800 | 15 | 16.5 | 62.1 | 28.4 | 188 | 243 | 277 | 56 | 38 |
| 49M440 | 480/70R30 | AG49M | TL | 152A8/B | 46 | 30 | 7,850 | 15 | 18.4 | 57.8 | 26.2 | 171 | 264E | 298 | 66 | 38 |
| 49H777 | 18.4R38 | AG49H | TL | 146A8/B | 24 | 30 | 6,600 | 16 | 18.5 | 68 | 31.1 | 203 | 318E | 353 | 66 | 42 |
| 49H742 | 18.4R42 | AG49H | TL | 148A8/B | 24 | 30 | 6,950 | 16 | 18.3 | 72.2 | 33.2 | 212 | 335E | 448 | 66 | 46 |
| 49M751 | 480/80R50 | AG49M | TL | 159A8/B | 35 | 30 | 9,650 | 15 | 18.9 | 80.2 | 37.2 | 245 | 432 | 526 | 64 | 48 |
| 49M851 | 480/80R50 | AG49M | TL | 165A8/B | 46 | 30 | 11,400 | 15 | 18.9 | 80.2 | 37.2 | 245 | 432E | 550 | 64 | 48 |
| 49H789 | 20.8R38 | AG49H | TL | 153A8/B | 24 | 30 | 8,050 | 18 | 20.9 | 70.9 | 32.6 | 212 | 380E | 424 | 70 | 42 |
| 49H752 | 20.8R42 | AG49H | TL | 155A8/B | 24 | 30 | 8,550 | 18 | 21.4 | 75.5 | 34.1 | 225 | 423 | 509 | 66 | 40 |
| 49M771 | 520/85R46 | AG49M | TL | 158A8/B | 23 | 30 | 9,350 | 16 | 21.9 | 80.8 | 37 | 243 | 580 | 579 | 72 | 48 |
| 49M971 | 520/85R46 | AG49M | TL | 169A8/B | 46 | 30 | 12,800 | 16 | 21.9 | 80.8 | 37 | 243 | 357E | 630 | 72 | 48 |
| 49M7M6 | 600/70R30 | AG49M | TL | 152A8/B | 23 | 30 | 7,850 | 20 | 22.9 | 63.1 | 28.4 | 189 | 357E | 407 | 65 | 36 |

Titan

Radial R-1W

| Catalog # | Tire Size | Design | TL/TT | Load Rating | Inflation Pressure (psi) | Max Speed (mph) | Max Load (lbs) | Recom'd Rim Width* (in) | Tire Width (in) | Overall Diameter (in) | Static Loaded Radius (in) | Rolling Circ. (in) | Flat Plate Area (in ²) | Weight (lbs) | Tread Depth 32nd in. | Number of Lugs |
|-----------|-----------|--------|-------|-------------|--------------------------|-----------------|----------------|-------------------------|-----------------|-----------------------|---------------------------|--------------------|------------------------------------|--------------|----------------------|----------------|
| 49M770 | 620/70R42 | AG49M | TL | 160A8/B | 23 | 30 | 9,900 | 20 | 24.6 | 76.5 | 35 | 230 | 465E | 647 | 66 | 40 |
| 49M781 | 620/70R46 | AG49M | TL | 162A8/B | 23 | 30 | 10,500 | 20 | 24.6 | 80.2 | 36.9 | 241 | 470 | 691 | 73 | 42 |
| 49M5W6 | 710/60R30 | AG49M | TL | 162A8/B | 35 | 30 | 10,500 | 25 | 27.9E | 63.5E | 28.6E | 189E | 500E | 503 | 78 | 36 |
| 49M969 | 710/70R38 | AG49M | TL | 177A8/B | 46 | 30 | 16,100 | 23 | 28 | 76 | 34.8 | 227 | 490E | 737 | 78 | 40 |
| 49M769 | 710/70R38 | AG49M | TL | 166A8/B | 23 | 30 | 11,700 | 23 | 28 | 76 | 34.8 | 227 | 490E | 680 | 78 | 40 |

*See Approved Rim Contours section

Bias R-2

Titan



Titan Special Service R-2

- At its best in muddy, sticky soil conditions
- Curved lugs prevent mud clogging while adding traction and side hill slip resistance

| Catalog # | Tire Size | Design | TL/TT | Load Rating | Inflation Pressure (psi) | Max Speed (mph) | Max Load (lbs) | Recom'd Rim Width* (in) | Tire Width (in) | Overall Diameter (in) | Static Loaded Radius (in) | Rolling Circ. (in) | Flat Plate Area (in ²) | Weight (lbs) | Tread Depth 32nd in. | Number of Lugs |
|-----------|-----------|-----------------|-------|-------------|--------------------------|-----------------|----------------|-------------------------|-----------------|-----------------------|---------------------------|--------------------|------------------------------------|--------------|----------------------|----------------|
| 47B628 | 13.6-38 | Special Service | TT | 6 | 22 | 25 | 3,300 | 12 | 14 | 62.7 | 28.2 | 188 | 241E | 177 | 78 | 40 |
| 47B638 | 14.9-28 | Special Service | TT | 6 | 20 | 25 | 3,200 | 13 | 15.3 | 55.5 | 25.1 | 167 | na | 166 | 89 | 32 |
| 48B638 | 14.9-28 | Special Service | TL | 6 | 20 | 25 | 3,200 | 13 | 15.3 | 55.5 | 25.1 | 167 | na | 178 | 89 | 32 |
| 47B674 | 15.5-38 | Special Service | TT | 6 | 20 | 25 | 3,520 | 14 | 15.9 | 64.2 | 29.9 | 193 | 172E | 226 | 85 | 40 |
| 48B046 | 16.9-26 | Special Service | TL | 10 | 28 | 25 | 4,540 | 15 | 17.5 | 55.5 | 25.2 | 167 | 200E | 233 | 96 | 32 |
| 48B650 | 18.4-30 | Special Service | TL | 6 | 16 | 25 | 4,180 | 16 | 18.9 | 62.7 | 28.6 | 188 | 277E | 318 | 99 | 30 |
| 48B050# | 18.4-30 | Special Service | TL | 10 | 26 | 25 | 5,520 | 16 | 18.9 | 62.7 | 28.6 | 188 | 277E | 342 | 99 | 30 |
| 47B654 | 18.4-34 | Special Service | TT | 6 | 16 | 25 | 4,400 | 16 | 18.9 | 66 | 30.3 | 198 | 290E | 278 | 99 | 32 |
| 48B154 | 18.4-34 | Special Service | TL | 12 | 32 | 25 | 6,600 | 16 | 18.9 | 66 | 30.3 | 198 | 290E | 325 | 99 | 32 |
| 47B877 | 18.4-38 | Special Service | TT | 8 | 20 | 25 | 5,360 | 16 | 18.6 | 70.2 | 32.3 | 210 | 300E | 324 | 99 | 34 |
| 47B889 | 20.8-38 | Special Service | TT | 8 | 18 | 25 | 6,150 | 18 | 20.2 | 72.8 | 33.4 | 218 | 385E | 385 | 104 | 34 |
| 47B089 | 20.8-38 | Special Service | TT | 10 | 22 | 25 | 6,950 | 18 | 20.2 | 72.8 | 33.4 | 218 | 385E | 393 | 104 | 34 |
| 47B886 | 23.1-26 | Special Service | TT | 8 | 16 | 25 | 5,680 | 20 | 23 | 65.2 | 29.3 | 194 | 291E | 393 | 109 | 30 |
| 48B086 | 23.1-26 | Special Service | TL | 10 | 20 | 25 | 6,400 | 20 | 23 | 65.2 | 29.3 | 194 | 291E | 427 | 109 | 30 |
| 47B882 | 23.1-30 | Special Service | TT | 8 | 16 | 25 | 6,000 | 20 | 23.5 | 68.6 | 31 | 205 | na | 403 | 109 | 32 |
| 47B888 | 23.1-34 | Special Service | TT | 8 | 16 | 25 | 6,400 | 20 | 23.5 | 72.6 | 33 | 216 | 310E | 413 | 109 | 32 |
| 48B188 | 23.1-34 | Special Service | TL | 12 | 24 | 25 | 8,050 | 20 | 23.5 | 72.6 | 33 | 216 | 310E | 462 | 109 | 32 |
| 47B099 | 24.5-32 | Special Service | TT | 10 | 20 | 25 | 7,850 | 21 | 24.5 | 72.1 | 32.6 | 215 | 320E | 514 | 112 | 32 |
| 48B599 | 24.5-32 | Special Service | TL | 16 | 30 | 25 | 9,900 | 21 | 24.5 | 72.1 | 32.6 | 215 | 320E | 574 | 112 | 32 |
| 48B198 | 28L-26 | Special Service | TL | 12 | 20 | 25 | 7,400 | 25 | 28.4 | 64.3 | 28.9 | 192 | 408E | 505 | 109 | 28 |
| 48B598 | 28L-26 | Special Service | TL | 16 | 28 | 25 | 9,100 | 25 | 28.4 | 64.3 | 28.9 | 192 | 408E | 552 | 109 | 28 |
| 47B096 | 30.5L-32 | Special Service | TT | 10 | 16 | 25 | 8,250 | 27 | 29.8 | 73.4 | 33.2 | 218 | 500E | 621 | 113 | 30 |
| 48B096 | 30.5L-32 | Special Service | TL | 10 | 16 | 25 | 8,250 | 27 | 29.8 | 73.4 | 33.2 | 218 | 500E | 648 | 113 | 30 |
| 48B196 | 30.5L-32 | Special Service | TL | 12 | 20 | 25 | 9,350 | 27 | 29.8 | 73.4 | 33.2 | 218 | 500E | 692 | 113 | 30 |
| 48B396 | 30.5L-32 | Special Service | TL | 14 | 22 | 25 | 9,900 | 27 | 29.8 | 73.4 | 33.2 | 218 | 500E | 694 | 113 | 30 |

*See Approved Rim Contours section
#Minimum Order Quantity

Titan

Radial R-3



TORC TRAC



TORC TRAC II

Titan Torc Trac Radial R-3

- Minimizes ground disturbance with its wide, flat footprint and deep grooves
- Performance proven as an original equipment tire

Titan Torc Trac II Radial R-3

- Features radial construction for reduced rolling resistance, increased footprint area and reduced fuel consumption
- This rugged tire minimizes ground disturbance with a button tread pattern that offers good performance on vibratory rollers and combine applications

| Catalog # | Tire Size | Design | TL/TT | Load Rating | Inflation Pressure (psi) | Max Speed (mph) | Max Load (lbs) | Recom'd Rim Width* (in) | Tire Width (in) | Overall Diameter (in) | Static Loaded Radius (in) | Rolling Circ. (in) | Flat Plate Area (in ²) | Weight (lbs) | Tread Depth 32nd in. |
|-----------|-----------|---------------------|-------|-------------|--------------------------|-----------------|----------------|-------------------------|-----------------|-----------------------|---------------------------|--------------------|------------------------------------|--------------|----------------------|
| 48G556 | 18.4R26 | Torc Trac Radial | TL | 146A8/B | 32 | 30 | 6,600 | 16 | 19.1 | 55.4 | 24.7 | 166 | 224E | 283 | 29 |
| 48G686 | 23.1R26 | Torc Trac II Radial | TL | 161A8/B | 42 | 30 | 10,200 | 20 | 22.8 | 59.6 | 26.8 | 175 | 245 | 449 | 31 |
| 4R5299 | 24.5R32 | Torc Trac II Radial | TL | 159A8/B | 24 | 30 | 9,650 | 21 | 23.5 | 70.6 | 31.2 | 210 | 450 | 535 | 36 |
| 4R5599 | 24.5R32 | Torc Trac II Radial | TL | 169A8/B | 38 | 30 | 12,800 | 21 | 23.5 | 70.6 | 31.2 | 210 | 450 | 568 | 36 |
| 4R5699 | 24.5R32 | Torc Trac II Radial | TL | 173A8/B | 48 | 30 | 14,300 | 21 | 23.5 | 70.6 | 31.2 | 210 | 450 | 535 | 36 |
| 48G798 | 28LR26 | Torc Trac II Radial | TL | 174A8/B | 54 | 30 | 14,800 | 25 | 28 | 62.6 | 27.8 | 184 | 419 | 511 | 30 |
| 48G796 | 30.5LR32 | Torc Trac II Radial | TL | 181A8/B | 52 | 30 | 18,200 | 27 | 30 | 69.8 | 31.7 | 209 | 572 | 732 | 37 |

*See Approved Rim Contours section

Titan

Bias R-3



TORC TRAC



TORC TRAC II

Titan Torc Trac R-3

- Minimizes ground disturbance with its wide, flat footprint and deep grooves
- Performance proven as an original equipment tire

Titan Torc Trac II R-3

- This rugged tire minimizes ground disturbance with a button tread pattern that offers good performance on vibratory rollers and combine applications



MULTI TRAC

Titan Multi Trac R-3

- Greater tread depth and more rubber on the contact surface to provide increased puncture resistance and longer tire life
- Shoulder design minimizes turf damage

| Catalog # | Tire Size | Design | TL/TT | Load Rating | Inflation Pressure (psi) | Max Speed (mph) | Max Load (lbs) | Recom'd Rim Width* (in) | Tire Width (in) | Overall Diameter (in) | Static Loaded Radius (in) | Rolling Circ. (in) | Flat Plate Area (in ²) | Weight (lbs) | Tread Depth 32nd in. |
|-----------|------------|--------------|-------|-------------|--------------------------|-----------------|----------------|-------------------------|-----------------|-----------------------|---------------------------|--------------------|------------------------------------|--------------|----------------------|
| 485363 | 12-16.5NHS | Torc Trac | TL | 8 | 50 | 20 | 3,270 | 9.75 | 11.8 | 33.1 | 14.9 | 98 | 110E | 74 | 23 |
| 485317 | 12-16.5NHS | Torc Trac | TL | 10 | 65 | 20 | 3,810 | 9.75 | 11.8 | 33.1 | 14.9 | 98 | 110E | 75 | 23 |
| 474381 | 13.6-16 | Multi Trac | TL | 4 | 14 | 25 | 1,570 | 12 | 15.4 | 38.1 | 17 | 113 | 100E | 101 | 24 |
| 4743W0 | 13.6-16** | Multi Trac | TL | 8 | 28 | 25 | 2,340 | 12 | 14.5 | 39.9 | 18.3 | 122 | 82 | 93 | 24 |
| 4743L4 | 13.6-16 | Multi Trac | TL | 14 | 50 | 25 | 3,300 | 12 | 14.3 | 39.5 | 17 | 110 | 113 | 115 | 24 |
| 485424 | 13.6-28 | Torc Trac II | TL | 4 | 14 | 25 | 2,200 | 12 | 14 | 50.8 | 23.5 | 151 | 160E | 108 | 24 |
| 475624 | 13.6-28 | Torc Trac II | TT | 6 | 22 | 25 | 2,830 | 12 | 14 | 50.8 | 23.5 | 151 | 160E | 103 | 24 |
| 475634 | 14.9-24 | Torc Trac | TT | 6 | 20 | 25 | 3,000 | 13 | 15.2 | 48.4 | 21.2 | 144 | 157E | 134 | 27 |
| 485634 | 14.9-24 | Torc Trac | TL | 6 | 20 | 25 | 3,000 | 13 | 15.5 | 48.4 | 21.2 | 144 | 157E | 147 | 27 |
| 485834 | 14.9-24 | Torc Trac | TL | 8 | 26 | 25 | 3,520 | 13 | 15.2 | 48.4 | 21.2 | 144 | 157E | 147 | 27 |
| 485034 | 14.9-24 | Torc Trac | TL | 10 | 32 | 25 | 3,960 | 13 | 15.2 | 48.4 | 21.2 | 144 | 157E | 160 | 27 |

Bias R-3

Titan

| Catalog # | Tire Size | Design | TL/TT | Load Rating | Inflation Pressure (psi) | Max Speed (mph) | Max Load (lbs) | Recom'd Rim Width* (in) | Tire Width (in) | Overall Diameter (in) | Static Loaded Radius (in) | Rolling Circ. (in) | Flat Plate Area (in ²) | Weight (lbs) | Tread Depth 32nd in. |
|-----------|------------------|----------------|-------|-------------|--------------------------|-----------------|----------------|-------------------------|-----------------|-----------------------|---------------------------|--------------------|------------------------------------|--------------|----------------------|
| 4853X3 | 33x15.50-16.5NHS | Torc Trac | TL | 12 | 60 | 5 | 6,600 | 12 | 14.5 | 33.3 | 14.8 | 98 | 128 | 94 | 23 |
| 4853R9 | 33x15.50-16.5NHS | Torc Trac | TL | 14 | 70 | 5 | 7,150 | 12 | 14.5 | 33.3 | 14.8 | 98 | 128 | 94 | 23 |
| 485845 | 16.9-24 | Torc Trac | TL | 8 | 24 | 25 | 4,080 | 15 | 17.7 | 51.4 | 22.9 | 151 | 196E | 163 | 28 |
| 485045 | 16.9-24 | Torc Trac | TL | 10 | 28 | 25 | 4,400 | 15 | 17.7 | 51.4 | 22.9 | 151 | 196E | 178 | 28 |
| 485345# | 16.9-24 | Torc Trac | TL | 14 | 40 | 25 | 5,520 | 15 | 17.7 | 51.4 | 22.9 | 151 | 196E | 184 | 28 |
| 485690 | 18.4-16.1 | Torc Trac | TL | 6 | 16 | 25 | 2,540 | 16 | 19.3 | 43.2 | 19.3 | 128 | 135E | 141 | 29 |
| 485056 | 18.4-26 | Torc Trac | TL | 10 | 26 | 25 | 5,200 | 16 | 19.1 | 55.8 | 25.4 | 165 | 224E | 249 | 29 |
| 485156 | 18.4-26 | Torc Trac | TL | 12 | 32 | 25 | 5,840 | 16 | 19.6 | 57.1 | 26.2 | 174 | 177 | 254 | 29 |
| 485756 | 18.4-26 | Torc Trac | TL | 18 | 46 | 25 | 7,400 | 16 | 19.1 | 55.8 | 25.4 | 165 | 224E | 267 | 29 |
| 4743D9 | 21.5L-16.1SL | Multi Trac C/S | TL | 4 | 12 | 30 | 3,520 | 18 | 21.2 | 44.7 | 19.3 | 129 | 220 | 147 | 24 |
| 48A886 | 23.1-26 | Torc Trac II | TL | 8 | 16 | 25 | 5,680 | 20 | 22.8 | 59.6 | 26.8 | 175 | 394E | 291 | 31 |
| 485086 | 23.1-26 | Torc Trac | TL | 10 | 20 | 25 | 6,400 | 20 | 24.4 | 62 | 28 | 187 | 330 | 336 | 35 |
| 48A586 | 23.1-26 | Torc Trac II | TL | 16 | 34 | 25 | 8,800 | 20 | 22.8 | 59.6 | 26.8 | 175 | 394E | 337 | 31 |
| 475886 | 23.1-26 | Torc Trac | TT | 8 | 16 | 25 | 5,680 | 20 | 24 | 61.7 | 27.8 | 182 | 394E | 314 | 35 |
| 485086 | 23.1-26 | Torc Trac | TL | 10 | 20 | 25 | 6,400 | 20 | 24 | 61.7 | 27.8 | 182 | 394E | 334 | 35 |
| 485186 | 23.1-26 | Torc Trac | TL | 12 | 24 | 25 | 7,150 | 20 | 24 | 61.7 | 27.8 | 182 | 394E | 367 | 35 |
| 485199 | 24.5-32 | Torc Trac II | TL | 12 | 24 | 25 | 8,800 | 21 | 24.2 | 69.9 | 32.4 | 211 | 327E | 441 | 35 |
| 485599 | 24.5-32 | Torc Trac II | TL | 16 | 30 | 25 | 9,900 | 21 | 24.2 | 69.9 | 32.4 | 211 | 327E | 441 | 35 |
| 485198 | 28L-26 | Torc Trac II | TL | 12 | 20 | 25 | 7,400 | 25 | 28 | 62.6 | 27.8 | 184 | 443E | 435 | 30 |
| 48L398 | 28LL-26 | Torc Trac II | TL | 14 | 24 | 25 | 7,600 | 25 | 26.6 | 61.3 | 26.8E | 180E | 433E | 370 | 31 |
| 485598 | 28L-26 | Torc Trac II | TL | 16 | 28 | 25 | 9,100 | 25 | 28 | 62.6 | 27.8 | 184 | 443E | 470 | 30 |
| 485196 | 30.5L-32 | Torc Trac II | TL | 12 | 20 | 25 | 9,350 | 27 | 29.5 | 70.5 | 32 | 209 | 564E | 530 | 37 |
| 485596 | 30.5L-32 | Torc Trac II | TL | 16 | 26 | 25 | 11,000 | 27 | 29.5 | 70.5 | 32 | 209 | 564E | 561 | 37 |

*See Approved Rim Contours section
#Minimum Order Quantity **ECE Certified



Titan RDSXL

| Catalog # | Tire Size | Design | TL/TT | Load Rating | Inflation Pressure (psi) | Max Speed (mph) | Max Load (lbs) | Recom'd Rim Width* (in) | Tire Width (in) | Overall Diameter (in) | Static Loaded Radius (in) | Rolling Circ. (in) | Flat Plate Area (in ²) | Weight (lbs) | Tread Depth 32nd in. |
|-----------|-------------|--------|-------|-------------|--------------------------|-----------------|----------------|-------------------------|-----------------|-----------------------|---------------------------|--------------------|------------------------------------|--------------|----------------------|
| RDS4XL | 600/50R22.5 | RDSXL | TL | 159D | 58 | 40 | 9650 | 20 | 24.4 | 47.3 | 21.1 | 141 | 210 | 290 | 22 |

*See Approved Rim Contours section

Bias R-4

Titan



Titan LSW Industrial Tractor Lug II R-4

| Catalog # | Tire Size | Design | TL/TT | Load Rating | Inflation Pressure (psi) | Max Speed (mph) | Max Load (lbs) | Recom'd Rim Width* (in) | Tire Width (in) | Overall Diameter (in) | Static Loaded Radius (in) | Rolling Circ. (in) | Flat Plate Area (in ²) | Weight (lbs) | Tread Depth 32nd in. |
|-----------|--------------|---------------------------|-------|-------------|--------------------------|-----------------|----------------|-------------------------|-----------------|-----------------------|---------------------------|--------------------|------------------------------------|--------------|----------------------|
| G9FD61 | LSW500/60D28 | Industrial Tractor Lug II | TL | 14 | 38 | 25 | 7,600 | 17 | 18.8 | 51.9 | 23.3 | 155 | 232 | 220 | 34 |

*See Approved Rim Contours section

Titan

Bias R-4



Titan Industrial Tractor Lug R-4

Titan Industrial Contractor R-4

- Extra wide lugs with extensive overlap at the center, designed to resist buckling, tearing and cracking
- Excellent tread wear and roadability, the laterally designed lugs result in even wear

| Catalog # | Tire Size | Design | TL/TT | Load Rating | Inflation Pressure (psi) | Max Speed (mph) | Max Load (lbs) | Recom'd Rim Width* (in) | Tire Width (in) | Overall Diameter (in) | Static Loaded Radius (in) | Rolling Circ. (in) | Flat Plate Area (in ²) | Weight (lbs) | Tread Depth 32nd in. |
|-----------|------------|-----------------------|-------|-------------|--------------------------|-----------------|----------------|-------------------------|-----------------|-----------------------|---------------------------|--------------------|------------------------------------|--------------|----------------------|
| 486634 | 14.9-24 | Industrial Tractor | TL | 6 | 24 | 25 | 4,300 | 13 | 15.3 | 48.1 | 22 | 143 | 140E | 147 | 34 |
| 486834 | 14.9-24 | Industrial Tractor | TL | 8 | 30 | 25 | 5,080 | 13 | 15.3 | 48.1 | 22 | 143 | 140E | 147 | 34 |
| 486134 | 14.9-24 | Industrial Tractor | TL | 12 | 42 | 25 | 6,400 | 13 | 15.3 | 48.1 | 22 | 143 | 140E | 167 | 34 |
| 4866T2 | 420/70-24 | Industrial Tractor | TL | 6 | 20 | 25 | 3,960 | 13 | 16.5 | 46.4 | 21.1 | 137 | 165E | 155 | 35 |
| 486645 | 16.9-24 ** | Industrial Tractor | TL | 6 | 22 | 25 | 4,940 | 15 | 17.9 | 51.3 | 23 | 153 | 240 | 166 | 35 |
| 486845 | 16.9-24 | Industrial Tractor | TL | 8 | 28 | 25 | 5,840 | 15 | 17.4 | 50.6 | 23 | 153 | 194E | 167 | 35 |
| 486045 | 16.9-24 | Industrial Tractor | TL | 10 | 32 | 25 | 6,400 | 15 | 17.4 | 50.6 | 23 | 153 | 194E | 173 | 35 |
| 486145 | 16.9-24 | Industrial Tractor | TL | 12 | 38 | 25 | 7,150 | 15 | 17.4 | 50.6 | 23 | 153 | 194E | 177 | 35 |
| 486345 | 16.9-24 | Industrial Tractor | TL | 14 | 44 | 25 | 7,850 | 15 | 17.4 | 50.6 | 23 | 153 | 194E | 180 | 35 |
| 486848 | 16.9-28 | Industrial Tractor | TL | 8 | 28 | 25 | 6,150 | 15 | 17.4 | 54.6 | 25 | 162 | 223E | 180 | 34 |
| 486148 | 16.9-28 | Industrial Tractor | TL | 12 | 38 | 25 | 7,600 | 15 | 17.4 | 54.6 | 25 | 162 | 223E | 201 | 34 |
| 486603 | 17.5L-24 | Industrial Tractor | TL | 6 | 20 | 25 | 4,400 | 15 | 17.1 | 48.8 | 22.3 | 145 | 192E | 153 | 32 |
| 4D6603 | 17.5L-24 | Industrial Contractor | TL | 6 | 20 | 25 | 4,400 | 15 | 17.1 | 48.8 | 22.3 | 145 | 192E | 153 | 32 |
| 486803 | 17.5L-24 | Industrial Tractor | TL | 8 | 26 | 25 | 5,360 | 15 | 17.1 | 48.8 | 22.3 | 145 | 192E | 153 | 32 |
| 486003 | 17.5L-24 | Industrial Tractor | TL | 10 | 32 | 25 | 6,150 | 15 | 17.1 | 48.8 | 22.3 | 145 | 192E | 167 | 32 |
| 486103 | 17.5L-24 | Industrial Tractor | TL | 12 | 36 | 25 | 6,600 | 15 | 17.1 | 48.8 | 22.3 | 145 | 192E | 173 | 32 |
| 4D6103 | 17.5L-24 | Industrial Contractor | TL | 12 | 36 | 25 | 6,600 | 15 | 17.1 | 48.8 | 22.3 | 145 | 192E | 173 | 32 |
| 486864 | 18.4-24 | Industrial Tractor | TL | 8 | 24 | 25 | 6,400 | 16 | 18.8 | 53.8 | 24.4 | 160 | 246E | 196 | 35 |
| 486164 | 18.4-24 | Industrial Tractor | TL | 12 | 36 | 25 | 8,250 | 16 | 18.8 | 53.8 | 24.4 | 160 | 246E | 218 | 35 |
| 486056 | 18.4-26 | Industrial Tractor | TL | 10 | 30 | 25 | 7,600 | 16 | 18.8 | 55.8 | 25.1 | 166 | 252E | 239 | 35 |
| 486156 | 18.4-26 | Industrial Tractor | TL | 12 | 36 | 25 | 8,800 | 16 | 18.8 | 55.8 | 25.1 | 166 | 252E | 239 | 35 |
| 486058 | 18.4-28 | Industrial Tractor | TL | 10 | 30 | 25 | 7,850 | 16 | 18.8 | 57.8 | 26.4 | 172 | 256E | 225 | 35 |
| 486861 | 19.5L-24 | Industrial Tractor | TL | 8 | 24 | 25 | 6,000 | 17 | 19.1 | 51.8 | 23.5 | 154 | 206E | 190 | 34 |
| 486061 | 19.5L-24 | Industrial Tractor | TL | 10 | 28 | 25 | 6,600 | 17 | 19.1 | 51.8 | 23.5 | 154 | 206E | 204 | 34 |
| 486161 | 19.5L-24 | Industrial Tractor | TL | 12 | 34 | 25 | 7,600 | 17 | 19.1 | 51.8 | 23.5 | 154 | 206E | 209 | 34 |
| 486075 | 21L-24 | Industrial Tractor | TL | 10 | 26 | 25 | 7,400 | 18 | 21 | 54.3 | 24.6 | 161 | 238E | 251 | 35 |
| 486175 | 21L-24 | Industrial Tractor | TL | 12 | 32 | 25 | 8,550 | 18 | 21 | 54.3 | 24.6 | 161 | 238E | 251 | 35 |
| 486076 | 21L-28 | Industrial Tractor | TL | 10 | 22 | 25 | 5,080 | 18 | 21 | 58.3 | 26.6 | 173 | 260E | 305 | 36 |
| 486176 | 21L-28 | Industrial Tractor | TL | 12 | 28 | 25 | 5,840 | 18 | 21 | 58.3 | 26.6 | 173 | 260E | 313 | 36 |
| 486376 | 21L-28 | Industrial Tractor | TL | 14 | 36 | 25 | 9,900 | 18 | 21 | 58.3 | 26.6 | 173 | 260E | 337 | 36 |

*See Approved Rim Contours section

***ECE Certified

Bias F-1

Titan



Titan Tru-Trac Front Tractor F-1

- Penetrates deep into soil for maximum steering control and minimal lateral side-slip because of its high center rib
- Used by original equipment manufacturers and offers excellent durability

| Catalog # | Tire Size | Design | TL/TT | Load Rating | Inflation Pressure (psi) | Max Speed (mph) | Max Load (lbs) | Recom'd Rim Width* (in) | Tire Width (in) | Overall Diameter (in) | Static Loaded Radius (in) | Rolling Circ. (in) | Flat Plate Area (in ²) | Weight (lbs) | Tread Depth 32nd in. |
|-----------|-----------|------------|-------|-------------|--------------------------|-----------------|----------------|-------------------------|-----------------|-----------------------|---------------------------|--------------------|------------------------------------|--------------|----------------------|
| 4602U4 | 12.4-30SL | Single Rib | TL | 10 | 40 | 25 | 3,520 | 12 | 13.5 | 53.5 | 24.5 | 159 | na | 117 | na |

*See Approved Rim Contours section

Bias F-2/F-2M

Titan



Titan Tru-Trac F-2

- Penetrates deep into soil for maximum steering control and minimal lateral side-slip because of its high center rib
- Used by original equipment manufacturers and offers excellent durability



Titan Tru-Trac Multi Rib F-2M

- Best for handling heavy loads on hard-packed surfaces
- Offers excellent load distribution and flotation
- Features a nylon carcass, durable tread compound and bead rim shield

| Catalog # | Tire Size | Design | TL/TT | Load Rating | Inflation Pressure (psi) | Max Speed (mph) | Max Load (lbs) | Recom'd Rim Width* (in) | Tire Width (in) | Overall Diameter (in) | Static Loaded Radius (in) | Rolling Circ. (in) | Flat Plate Area (in ²) | Weight (lbs) | Tread Depth 32nd in. |
|-----------|------------|--------------------|-------|-------------|--------------------------|-----------------|----------------|-------------------------|-----------------|-----------------------|---------------------------|--------------------|------------------------------------|--------------|----------------------|
| 461329 | 4.00-12SL | Tru-Trac | TL | 4 | 52 | 25 | 495 | 3 | 5 | 21.3 | 10 | 64 | 15E | 11 | 15 |
| 461230 | 4.00-15SL | Tru-Trac | TT | 4 | 52 | 25 | 585 | 3 | 4.6 | 24.6 | 11.6 | 73 | 17E | 12 | 14 |
| 461233 | 4.00-19SL | Tru-Trac | TT | 4 | 52 | 25 | 715 | 3 | 4.6 | 28.8 | 13.7 | 86 | 19E | 14 | 14 |
| 462235 | 5.00-15SL | Tru-Trac | TT | 4 | 44 | 25 | 715 | 3 | 5.5 | 26 | 12.2 | 77 | 25E | 14 | 16 |
| 462334 | 5.00-15SL | Tru-Trac | TL | 6 | 64 | 25 | 910 | 3 | 5.5 | 26 | 12.2 | 77 | 25E | 17 | 16 |
| 462338 | 5.50-16SL | Tru-Trac | TL | 4 | 40 | 25 | 855 | 4 | 6.3 | 27.9 | 13.1 | 83 | 29E | 19 | 17 |
| 462239 | 5.50-16SL | Tru-Trac | TT | 6 | 56 | 25 | 1,050 | 4 | 6.3 | 27.9 | 13.1 | 83 | 29E | 19 | 17 |
| 462375 | 6.00-16SL | Tru-Trac | TL | 6 | 52 | 25 | 1,140 | 4 | 6.7 | 29 | 13.6 | 86 | 36E | 23 | 18 |
| 462281 | 6.50-16SL | Tru-Trac | TT | 6 | 48 | 25 | 1,230 | 4.5 | 7.3 | 29.8 | 13.9 | 89 | 41E | 24 | 20 |
| 462381 | 6.50-16SL | Tru-Trac | TL | 6 | 48 | 25 | 1,230 | 4.5 | 7.3 | 29.8 | 13.9 | 89 | 41E | 26 | 20 |
| 462283 | 7.50-16SL | Tru-Trac | TT | 6 | 44 | 25 | 1,480 | 5.5 | 8.6 | 31.6 | 14.7 | 94 | 48E | 29 | 23 |
| 462383 | 7.50-16SL | Tru-Trac | TL | 6 | 44 | 25 | 1,480 | 5.5 | 8.6 | 31.6 | 14.7 | 94 | 98E | 32 | 23 |
| 462284 | 7.50-16SL | Tru-Trac | TT | 8 | 56 | 25 | 1,710 | 5.5 | 8.6 | 31.6 | 14.7 | 94 | 48E | 32 | 23 |
| 466383 | 7.50-16SL | Tru Trac Multi Rib | TL | 6 | 44 | 25 | 1,480 | 5.5 | 8.6 | 31.3 | 14.6 | 93 | 34E | 36 | 21 |
| 462278 | 7.50-18SL | Tru-Trac | TT | 6 | 44 | 25 | 1,610 | 5.5 | 8.6 | 33.9 | 15.8 | 101 | 52E | 34 | 23 |
| 462393 | 7.50-20SL | Tru-Trac | TL | 6 | 44 | 25 | 1,710 | 5.5 | 8.6 | 35.8 | 16.8 | 107 | 57E | 45 | 23 |
| 462290 | 7.5L-15SL | Tru-Trac | TT | 6 | 44 | 25 | 1,430 | 6 | 8.1 | 29.3 | 13.6 | 87 | 33E | 28 | 24 |
| 462390 | 7.5L-15SL | Tru-Trac | TL | 6 | 44 | 25 | 1,430 | 6 | 8.1 | 29.3 | 13.6 | 87 | 33E | 30 | 24 |
| 462244 | 9.5L-15SL | Tru-Trac | TT | 8 | 48 | 25 | 1,870 | 7 | 9.9 | 31.5 | 14.6 | 93 | 53E | 42 | 27 |
| 466343 | 9.5L-15SL | Tru Trac Multi Rib | TL | 6 | 36 | 25 | 1,520 | 7 | 9.9 | 31.5 | 14.6 | 93 | 53E | 47 | 27 |
| 462343 | 9.5L-15SL | Tru-Trac | TL | 6 | 36 | 25 | 1,520 | 7 | 9.9 | 31.5 | 14.6 | 93 | 53E | 42 | 27 |
| 462394 | 10.00-16SL | Tru-Trac | TL | 6 | 32 | 25 | 1,930 | 8 | 10.8 | 35.6 | 16.4 | 105 | 67E | 52 | 30 |

Titan

Bias F-2/F-2M

| Catalog # | Tire Size | Design | TL/TT | Load Rating | Inflation Pressure (psi) | Max Speed (mph) | Max Load (lbs) | Recom'd Rim Width* (in) | Tire Width (in) | Overall Diameter (in) | Static Loaded Radius (in) | Rolling Circ. (in) | Flat Plate Area (in ²) | Weight (lbs) | Tread Depth 32nd in. |
|-----------|--------------|--------------------|-------|-------------|--------------------------|-----------------|----------------|-------------------------|-----------------|-----------------------|---------------------------|--------------------|------------------------------------|--------------|----------------------|
| 466394 | 10.00-16SL | Tru Trac Multi Rib | TL | 6 | 32 | 25 | 1,930 | 8 | 11.2 | 35.5 | 16.4 | 105 | 67E | 56 | 28 |
| 466298 | 10.00-16SL | Tru Trac Multi Rib | TT | 8 | 44 | 25 | 2,340 | 8 | 11.2 | 35.5 | 16.4 | 105 | 67E | 56 | 28 |
| 462398 | 10.00-16SL | Tru-Trac | TL | 8 | 44 | 25 | 2,340 | 8 | 10.8 | 35.6 | 16.4 | 105 | 67E | 55 | 30 |
| 466398 | 10.00-16SL | Tru Trac Multi Rib | TL | 8 | 44 | 25 | 2,340 | 8 | 11.2 | 35.5 | 16.4 | 105 | 67E | 59 | 28 |
| 462395 | 11.00-16SL | Tru-Trac | TL | 8 | 40 | 25 | 2,600 | 10 | 12.3 | 38.3 | 17.6 | 113 | 75E | 79 | 33 |
| 462396 | 11.00-16SL | Tru-Trac | TL | 12 | 60 | 25 | 3,420 | 10 | 12.3 | 38.3 | 17.6 | 113 | 75E | 88 | 33 |
| 466295 | 11.00-16SL | Tru Trac Multi Rib | TT | 8 | 40 | 25 | 2,600 | 10 | 12.7 | 38.1 | 17.5 | 112 | 84E | 77 | 28 |
| 466396 | 11.00-16SL | Tru Trac Multi Rib | TL | 12 | 60 | 25 | 3,420 | 10 | 12.7 | 38.1 | 17.5 | 112 | 84E | 92 | 28 |
| 466395 | 11.00-16SL | Tru Trac Multi Rib | TL | 8 | 40 | 25 | 2,600 | 10 | 12.7 | 38.1 | 17.5 | 112 | 84E | 83 | 28 |
| 466347 | 11.00-20SL | Tru Trac Multi Rib | TL | 12 | 60 | 25 | 3,860 | 10 | 12.4 | 41.5 | 19.2 | 123 | 85E | 101 | 28 |
| 466348 | 11.00-24SL | Tru Trac Multi Rib | TL | 8 | 40 | 25 | 3,420 | 10 | 12.4 | 45.5 | 21.2 | 155 | 90E | 104 | 28 |
| 462218 | 11L-15SL | Tru-Trac | TT | 8 | 44 | 25 | 2,090 | 8 | 10.8 | 32.1 | 14.9 | 95 | 53E | 53 | 31 |
| 466318 | 11L-15SL | Tru Trac Multi Rib | TL | 8 | 44 | 25 | 2,090 | 8 | 10.9 | 31.8 | 14.7 | 94 | 59E | 57 | 27 |
| 462287 | 14L-16.1SL | Tru-Trac | TT | 8 | 36 | 25 | 3,000 | 11 | 14.8 | 40 | 18.3 | 118 | 90E | 97 | 44 |
| 466389 | 14L-16.1SL | Tru Trac Multi Rib | TL | 10 | 44 | 25 | 3,420 | 11 | 14.4 | 38.4 | 17.6 | 113 | 100E | 109 | 32 |
| 466352 | 16.5L-16.1SL | Tru Trac Multi Rib | TL | 10 | 40 | 25 | 4,080 | 14 | 17.3 | 42.2 | 19.3 | 124 | 143E | 160 | 36 |

*See Approved Rim Contours section

Titan

Bias F-3



Titan Contractor F-3

- Low section height design for loader backhoe applications
- Designed for excellent durability and good road handling characteristics



Titan Industrial Front Tractor F-3

- Designed for excellent durability
- Good road handling characteristics for industrial service

| Catalog # | Tire Size | Design | TL/TT | Load Rating | Inflation Pressure (psi) | Max Speed (mph) | Max Load (lbs) | Recom'd Rim Width* (in) | Tire Width (in) | Overall Diameter (in) | Static Loaded Radius (in) | Rolling Circ. (in) | Flat Plate Area (in ²) | Weight (lbs) | Tread Depth 32nd in. |
|-----------|----------------|--------------------------|-------|-------------|--------------------------|-----------------|----------------|-------------------------|-----------------|-----------------------|---------------------------|--------------------|------------------------------------|--------------|----------------------|
| 465318 | 11L-15SL | Contractor | TL | 8 | 44 | 25 | 2,090 | 8 | 11 | 31.3 | 14.5 | 93 | 56E | 53 | 15 |
| 465310 | 11L-15SL | Contractor | TL | 10 | 52 | 25 | 2,340 | 8 | 11 | 31.3 | 14.5 | 93 | 56E | 55 | 15 |
| 465315 | 11L-16SL | Contractor | TL | 10 | 52 | 25 | 2,470 | 8 | 11 | 32.3 | 15 | 96 | 60E | 56 | 15 |
| 465317 | 11L-16SL | Contractor | TL | 12 | 64 | 25 | 2,760 | 8 | 11 | 32.3 | 15 | 96 | 60E | 63 | 15 |
| 464396 | 11.00-16SL | Industrial Front Tractor | TL | 12 | 60 | 25 | 3,420 | 10 | 12.2 | 36.1 | 16.6 | 107 | 82E | 78 | 15 |
| 465388 | 14.5/75-16.1SL | Contractor | TL | 10 | 40 | 25 | 3,200 | 11 | 13.7 | 35.5 | 16.4 | 105 | 120E | 75 | 18 |
| 465203 | 480/45-17 | Contractor | TL | 134A8/B | 29 | 30 | 4,680 | 16 | 19.3E | 34E | 15.4E | 101E | 150E | 83 | 15 |
| 465303 | 480/45-17 | Contractor | TL | 146A8/B | 46 | 30 | 6,600 | 16 | 19.3 | 34 | 15.4 | 101 | 150E | 86 | 15 |
| 465703 | 480/45-17 | Contractor | TL | 153A8/B | 58 | 30 | 8,050 | 16 | 19.3E | 34E | 15.4E | 101E | 150E | 89 | 15 |
| 465803 | 480/45-17 | Contractor | TL | 155A8/B | 73 | 30 | 8,550 | 16 | 19.3E | 34E | 15.4E | 101E | 150E | 96 | 15 |

*See Approved Rim Contours section

Bias I-1

Titan



DURA LIFE



HI FLOTATION

Titan Dura Life I-1

- This popular OEM tire offers wide ribs for good ground contact and excellent treadwear
- Straight ahead directional control is maximized with a series of straight circumferential grooves and ribs

Titan Hi Flotation I-1

- Noted for its maximum flotation
- Features wide tread design, large footprint, deep grooves and low section height design



PACKER



PLANTER AG41B

Titan Packer I-1

- Developed for the latest air seeders to firm the soil after the seed has been put into place
- This tire can operate at inflation pressures of 6 to 45 PSI, depending on soil conditions

Titan Planter AG41B I-1

- Designed to minimize seed bed compaction
- Open center and ribs at tread edge straddle seed placement location
- Features one rib in each shoulder



DURA LIFE PLANTER

Titan Dura Life Planter

- Designed to minimize seed bed compaction
- Open center and ribs at tread edge straddle seed placement location
- Features one rib in each shoulder

| Catalog # | Tire Size | Design | TL/TT | Load Rating | Inflation Pressure (psi) | Max Speed (mph) | Max Load (lbs) | Recom'd Rim Width* (in) | Tire Width (in) | Overall Diameter (in) | Static Loaded Radius (in) | Rolling Circ. (in) | Flat Plate Area (in ²) | Weight (lbs) | Tread Depth 32nd in. |
|-----------|------------|-------------------|-------|-------------|--------------------------|-----------------|----------------|-------------------------|-----------------|-----------------------|---------------------------|--------------------|------------------------------------|--------------|----------------------|
| 418277 | 4.00-12SL | Dura Life | TT | 4 | 44 | 30 | 675 | 3 | 5 | 20.4 | 9.5 | 60 | na | 7 | 5 |
| 418249 | 4.00-9SL | Dura Life | TT | 4 | 44 | 30 | 550 | 3 | 4.8 | 17.4 | 7.9 | 51 | na | 5 | 5 |
| 418353 | 5.90-15SL | Dura Life | TL | 4 | 36 | 30 | 1,140 | 4.5 | 6.3 | 26.6 | 12.1 | 79 | na | 17 | 7 |
| 418381 | 6.50-16SL | Dura Life | TL | 6 | 44 | 30 | 1,710 | 4.5 | 6.9 | 28.7 | 13 | 85 | na | 24 | 7 |
| 418367 | 6.70-15SL | Dura Life | TL | 4 | 32 | 30 | 1,280 | 4.5 | 7 | 28.3 | 12.8 | 84 | na | 21 | 7 |
| 418388 | 6.70-15SL | Dura Life | TL | 6 | 44 | 30 | 1,610 | 4.5 | 7 | 28.3 | 12.8 | 84 | na | 21 | 7 |
| 418384 | 7.50-16SL | Dura Life | TL | 8 | 48 | 30 | 2,340 | 5.5 | 8.4 | 31 | 13.9 | 92 | na | 32 | 8 |
| 41A3X7 | 7.50-20SL | Dura Life Planter | TL | 8 | 48 | 30 | 2,540 | 5.5 | 8.1 | 34.9 | 16.4 | 104 | na | 46 | 18 |
| 41B301 | 7.50-20SL | AG41B | TL | 4 | 28 | 30 | 1,760 | 5.5 | 8.7E | 37.2E | 17E | 110E | na | 36E | 22 |
| 4183P6 | 7.50-24SL | Dura Life | TL | 8 | 48 | 30 | 2,680 | 7 | 8.6 | 39.5 | 17.4 | 116 | na | 48 | 8 |
| 418336 | 7.60-15SL | Dura Life | TL | 6 | 40 | 30 | 1,760 | 5.5 | 8.1 | 28.5 | 12.8 | 84 | na | 25 | 8 |
| 418337 | 7.60-15SL | Dura Life | TL | 8 | 52 | 30 | 2,090 | 5.5 | 8.1 | 28.5 | 12.8 | 84 | na | 27 | 8 |
| 410389 | 8.5L-14SL | Hi Flotation | TL | 6 | 36 | 30 | 1,870 | 6 | 8.6 | 28.6 | 12.8 | 84 | na | 28 | 11 |
| 418348 | 9.00-16SL | Dura Life | TL | 10 | 52 | 30 | 3,300 | 6 | 9.3 | 32.7 | 14.6 | 96 | na | 44 | 10 |
| 4183J8 | 9.00-24SL | Dura Life | TL | 8 | 40 | 30 | 3,520 | 8 | 10.5 | 42.3 | 19.2 | 125 | na | 68 | 10 |
| 410398 | 9.5L-14SL | Hi Flotation | TL | 6 | 32 | 30 | 1,930 | 7 | 9.8 | 29.2 | 13 | 86 | na | 28 | 11 |
| 410399 | 9.5L-14SL | Hi Flotation | TL | 8 | 44 | 30 | 2,400 | 7 | 9.8 | 29.2 | 13 | 86 | na | 31 | 11 |
| 410343 | 9.5L-15SL | Hi Flotation | TL | 6 | 32 | 30 | 2,040 | 7 | 9.8 | 30.2 | 13.5 | 89 | na | 32 | 11 |
| 4103D7 | 9.5L-15SL | Hi Flotation | TL | 12 | 64 | 30 | 3,200 | 7 | 9.8 | 30.2 | 13.5 | 89 | na | 37 | 11 |
| 410344 | 9.5L-15SL | Hi Flotation | TL | 8 | 44 | 30 | 2,470 | 7 | 9.8 | 30.2 | 13.5 | 89 | na | 35 | 11 |
| 4183L1 | 10.00-15SL | Dura Life | TL | 8 | 40 | 30 | 3,200 | 8 | 10.9 | 33.5 | 14.8 | 99 | na | 50 | 11 |
| 4183K7 | 11.25-24SL | Dura Life | TL | 8 | 32 | 30 | 4,080 | 10 | 12.6 | 45.7 | 20.6 | 135 | na | 93 | 11 |
| 410364 | 11L-14SL | Hi Flotation | TL | 6 | 28 | 30 | 2,040 | 8 | 10.7 | 30 | 13.3 | 88 | na | 32 | 11 |
| 410314 | 11L-15SL | Hi Flotation | TL | 6 | 28 | 30 | 2,150 | 8 | 10.8 | 31 | 13.3 | 92 | na | 35 | 11 |
| 410319 | 11L-15SL | Hi Flotation | TL | 10 | 44 | 30 | 2,910 | 8 | 10.8 | 31 | 13.3 | 92 | na | 46 | 11 |
| 410317 | 11L-15SL | Hi Flotation | TL | 12 | 52 | 30 | 3,200 | 8 | 10.8 | 31 | 13.3 | 92 | na | 50 | 11 |
| 410318 | 11L-15SL | Hi Flotation | TL | 8 | 36 | 30 | 2,540 | 8 | 10.8 | 31 | 13.3 | 92 | na | 39 | 11 |
| 410340 | 12.5L-15SL | Hi Flotation | TL | 8 | 36 | 30 | 3,000 | 10 | 12.1 | 32.1 | 14.3 | 95 | na | 52 | 11 |

Titan

Bias I-1

| Catalog # | Tire Size | Design | TL/TT | Load Rating | Inflation Pressure (psi) | Max Speed (mph) | Max Load (lbs) | Recom'd Rim Width* (in) | Tire Width (in) | Overall Diameter (in) | Static Loaded Radius (in) | Rolling Circ. (in) | Flat Plate Area (in ²) | Weight (lbs) | Tread Depth 32nd in. |
|-----------|----------------|--------------|-------|-------------|--------------------------|-----------------|----------------|-------------------------|-----------------|-----------------------|---------------------------|--------------------|------------------------------------|--------------|----------------------|
| 410341 | 12.5L-15SL | Hi Flotation | TL | 10 | 44 | 30 | 3,420 | 10 | 12.1 | 32.1 | 14.3 | 95 | na | 51 | 11 |
| 410305 | 12.5L-15SL | Hi Flotation | TL | 12 | 52 | 30 | 3,860 | 10 | 12.1 | 32.1 | 14.3 | 95 | na | 54 | 11 |
| 410368 | 14L-16.1SL | Hi Flotation | TL | 8 | 32 | 30 | 3,860 | 11 | 14.8 | 37.4 | 16.5 | 110 | na | 74 | 12 |
| 410362 | 14L-16.1SL | Hi Flotation | TL | 12 | 44 | 30 | 4,680 | 11 | 14.8 | 37.4 | 16.5 | 110 | na | 83 | 12 |
| 410348 | 16.5L-16.1SL | Hi Flotation | TL | 8 | 28 | 30 | 4,400 | 14 | 17.1 | 40.9 | 18 | 120 | na | 106 | 14 |
| 410350 | 16.5L-16.1SL | Hi Flotation | TL | 10 | 36 | 30 | 5,200 | 14 | 17.1 | 40.9 | 18 | 120 | na | 107 | 14 |
| 4103L1 | 16.5L-16.1SL | Hi Flotation | TL | 14 | 48 | 30 | 6,400 | 14 | 17.1 | 40.9 | 18 | 120 | na | 119 | 14 |
| 4103H7 | 19L-16.1SL | Hi Flotation | TL | 10 | 32 | 30 | 6,000 | 16 | 19.1 | 43.6 | 18.9 | 127 | na | 136 | 17 |
| 4105H7 | 19L-16.1SL | Hi Flotation | TL | 12 | 36 | 30 | 6,600 | 16 | 19.1 | 43.6 | 18.9 | 127 | na | 147 | 17 |
| 4109H7 | 19L-16.1SL | Hi Flotation | TL | 18 | 52 | 30 | 8,250 | 16 | 19.1 | 43.6 | 18.9 | 127 | na | 155 | 17 |
| 4103A9 | 21.5L-16.1SL | Hi Flotation | TL | 6 | 16 | 30 | 4,400 | 18 | 21.4 | 45 | 19.9 | 135 | na | 172 | 17 |
| 410349 | 21.5L-16.1SL | Hi Flotation | TL | 10 | 28 | 30 | 6,600 | 18 | 21.4 | 45 | 19.9 | 135 | na | 184 | 17 |
| 4103J1 | 21.5L-16.1SL | Hi Flotation | TL | 14 | 36 | 30 | 7,850 | 18 | 21.4 | 45 | 19.9 | 135 | na | 191 | 17 |
| 4103Q4 | 21.5L-16.1SL | Hi Flotation | TL | 18 | 44 | 30 | 8,800 | 18 | 21.4 | 45 | 19.9 | 135 | na | 196 | 17 |
| 410561 | 26x12.00-12NHS | Hi Flotation | TL | 12 | 62 | 10 | 3,420 | 8 | 11.7 | 25.5 | 11 | 77 | na | 34 | 12 |

STUBBLE GUARD COMPOUND

| | | | | | | | | | | | | | | | |
|--------|---------------|--------------|----|----|----|----|-------|-----|------|------|------|-----|----|-----|----|
| 41M353 | 5.90-15SL# | Dura Life | TL | 4 | 36 | 30 | 1,140 | 4.5 | 6.3 | 26.6 | 12.1 | 79 | na | 17 | 7 |
| 41M388 | 6.70-15SL# | Dura Life | TL | 6 | 44 | 30 | 1,610 | 4.5 | 7 | 28.3 | 12.8 | 84 | na | 21 | 7 |
| 41M3J8 | 9.00-24SL# | Dura Life | TL | 8 | 40 | 30 | 3,520 | 8 | 10.5 | 42.3 | 19.2 | 125 | na | 68 | 10 |
| 41L318 | 11L-15SL# | Hi Flotation | TL | 8 | 36 | 30 | 2,540 | 8 | 10.8 | 31 | 13.3 | 92 | na | 39 | 11 |
| 41L315 | 11L-15SL# | Hi Flotation | TL | 18 | 80 | 30 | 4,180 | 8 | 10.8 | 31 | 13.3 | 92 | na | 60 | 11 |
| 41L305 | 12.5L-15SL# | Hi Flotation | TL | 12 | 52 | 30 | 3,860 | 10 | 12.1 | 32.1 | 14.3 | 95 | na | 54 | 11 |
| 41L327 | 12.5L-15SL# | Hi Flotation | TL | 20 | 80 | 30 | 5,080 | 10 | 12.1 | 32.1 | 14.3 | 95 | na | 69 | 11 |
| 41L353 | 12.5L-16SL# | Hi Flotation | TL | 14 | 56 | 30 | 4,180 | 10 | 11.9 | 31.9 | 14.3 | 95 | na | 57 | 11 |
| 41L368 | 14L-16.1SL# | Hi Flotation | TL | 8 | 32 | 30 | 3,860 | 11 | 14.8 | 37.4 | 16.5 | 110 | na | 74 | 12 |
| 41L3L2 | 14L-16.1SL# | Hi Flotation | TL | 14 | 52 | 30 | 5,200 | 11 | 14.8 | 37.4 | 16.5 | 110 | na | 94 | 12 |
| 41L350 | 16.5L-16.1SL# | Hi Flotation | TL | 10 | 36 | 30 | 5,200 | 14 | 17.1 | 40.9 | 18 | 120 | na | 107 | 14 |
| 41L3A9 | 21.5L-16.1SL# | Hi Flotation | TL | 6 | 16 | 30 | 4,400 | 18 | 21.4 | 45 | 19.9 | 135 | na | 172 | 17 |
| 41M356 | 20.5/5.5-12# | Packer | TL | 4 | 36 | 30 | 740 | 4 | 5.8 | 20.6 | 9.4 | 61 | na | 14 | 8 |
| 41M355 | 26/6.50-15# | Packer | TL | 4 | 45 | 30 | 1,400 | 4.5 | 6.5 | 26.4 | 12.1 | 78 | na | 26 | 11 |
| 41M32T | 26/7.75-15# | Packer | TL | 4 | 45 | 30 | 1,610 | 4.5 | 6.5 | 26.4 | 12.1 | 78 | na | 29 | 11 |
| 41M39T | 26/9.50-15# | Packer | TL | 4 | 45 | 30 | 1,960 | 7 | 8.2 | 27.1 | 12 | 80 | na | 36 | 11 |

*See Approved Rim Contours section
Stubble Guard Tread Compound



Titan Stubble Guard I-1

- Kevlar® breakers
- Heavy duty carcass
- Higher ply ratings
- Premium tread compound
- Reduced stubble punctures
- Reduce stubble penetrations
- Enhanced load capacity
- Reduced stubble damage

| Catalog # | Tire Size | Design | TL/TT | Load Rating | Inflation Pressure (psi) | Max Speed (mph) | Max Load (lbs) | Recom'd Rim Width* (in) | Tire Width (in) | Overall Diameter (in) | Static Loaded Radius (in) | Rolling Circ. (in) | Flat Plate Area (in ²) | Weight (lbs) | Tread Depth 32nd in. |
|-----------|------------|--------------|-------|-------------|--------------------------|-----------------|----------------|-------------------------|-----------------|-----------------------|---------------------------|--------------------|------------------------------------|--------------|----------------------|
| SBG3D9 | 9.5L-15SL | Hi Flotation | TL | 16 | 80 | 30 | 3,640 | 7 | 9.2 | 30.4 | 13.4 | 90 | 43 | 48 | 11 |
| SBG366 | 10.00-15SL | Dura Life | TL | 16 | 72 | 30 | 4,680 | 8 | 11 | 34 | 15 | 100 | 68 | 63 | 11 |
| SBG315 | 11L-15SL | Hi Flotation | TL | 18 | 80 | 30 | 4,180 | 8 | 10.5 | 30.3 | 13.4 | 89 | 52 | 62 | 11 |
| SBG327 | 12.5L-15SL | Hi Flotation | TL | 20 | 80 | 30 | 4,940 | 10 | 12.3 | 31.8 | 14 | 93.5 | 71 | 72 | 11 |

*See Approved Rim Contours section
Kevlar is a registered trademark of the DuPont™ Company

Bias I-3

Titan



CONTRACTOR



CONTRACTOR II

Titan Contractor I-3

- An implement tire specially designed for high traction applications
- Frequently used on the front of backhoes

Titan Contractor II I-3

- More robust design for use on the front of large backhoes



TI422



TRACTION IMPLEMENT

Titan TI422 I-3

- Designed for low horsepower traction requirements, the TI422 offers good roadability and excellent durability

Titan Traction Implement I-3

- Designed for low horsepower traction requirements, the Traction Implement offers good roadability and excellent durability

| Catalog # | Tire Size | Design | TL/TT | Load Rating | Inflation Pressure (psi) | Max Speed (mph) | Max Load (lbs) | Recom'd Rim Width* (in) | Tire Width (in) | Overall Diameter (in) | Static Loaded Radius (in) | Rolling Circ. (in) | Flat Plate Area (in ²) | Weight (lbs) | Tread Depth 32nd in. |
|-----------|--------------|--------------------|-------|-------------|--------------------------|-----------------|----------------|-------------------------|-----------------|-----------------------|---------------------------|--------------------|------------------------------------|--------------|----------------------|
| 422303 | 7.50-20SL | Traction Implement | TL | 4 | 28 | 30 | 1,760 | 5.5 | 8.1 | 34.9 | 15.9 | 104 | na | 38 | 17 |
| 422204 | 7.50-24SL | Traction Implement | TT | 4 | 28 | 30 | 1,870 | 7 | 8.7 | 38.9 | 17.9 | 115 | na | 41 | 17 |
| 46W3X8 | 10.5/80-18 | Contractor | TL | 6 | 33 | 25 | 2,830 | 9 | 10.8 | 35.7 | 16.5 | 109 | na | 72 | 29 |
| 46W3J8 | 10.5/80-18 | Contractor | TL | 10 | 54 | 25 | 3,840 | 9 | 10.8 | 35.7 | 16.5 | 109 | na | 73 | 29 |
| 46W3J9 | 12.5/80-18 | Contractor | TL | 10 | 46 | 25 | 4,710 | 9 | 12 | 38.8 | 17.4 | 114 | na | 104 | 31 |
| 4223J9 | 12.5/80-18 | TI422 | TL | 10 | 46 | 25 | 4,710 | 9 | 12 | 38.8 | 17.4 | 114 | na | 92 | 34 |
| 42E3J9 | 12.5/80-18 | Contractor II | TL | 10 | 46 | 25 | 4,710 | 9 | 12.3 | 38.35 | 17.1 | 114 | na | 94 | 32 |
| 42E3T7 | 12.5/80-18 | Contractor II | TL | 12 | 56 | 25 | 5,360 | 9 | 12.3 | 38.35 | 17.1 | 114 | na | 95 | 32 |
| 499505 | 13.50-16.1SL | Traction Implement | TL | 6 | 24 | 30 | 3,520 | 11 | 13.5 | 40.8 | 17.8 | 120 | na | 85 | 23 |
| 4223M2 | 16.5L-16.1SL | TI422 | TL | 6 | 24 | 30 | 3,960 | 14 | 16.5 | 40 | 17.7 | 117 | na | 98 | 26 |
| 4223W6 | 16.5L-16.1SL | TI422 | TL | 10 | 36 | 30 | 5,200 | 14 | 16.5 | 40 | 17.7 | 117 | na | 109 | 26 |
| 4223M3 | 21.5L-16.1SL | TI422 | TL | 8 | 24 | 30 | 6,000 | 18 | 20.3 | 44.6 | 19.6 | 132 | na | 156 | 35 |
| G6W3J8 | LSW280/70D20 | Contractor | TL | 10 | 54 | 25 | 3,840 | 9 | 10.8 | 35.6 | 16.2 | 108 | na | 73 | 29 |
| G6W3J9 | LSW320/75D20 | Contractor | TL | 10 | 46 | 25 | 4,710 | 9 | 12.1 | 38.6 | 17.3 | 115 | na | 99 | 31 |
| G2E3T7 | LSW320/75D20 | Contractor II | TL | 12 | 56 | 25 | 5,360 | 9 | 11.6 | 38.4 | 17.5 | 117 | 120 | 95 | 32 |
| G2E5T7 | LSW320/75D20 | Contractor II | TL | 14 | 64 | 25 | 5,840 | 9 | 11.6 | 38.4 | 17.5 | 117 | 120 | 98 | 32 |

*See Approved Rim Contours section

Titan

Bias FI



Titan Highway Implement FI

- Offers D.O.T. compliance for approved operation at highway speeds
- Noted for its great handling and towing characteristics

| Catalog # | Tire Size | Design | TL/TT | Load Rating | Inflation Pressure (psi) | Max Speed (mph) | Max Load (lbs) | Recom'd Rim Width* (in) | Tire Width (in) | Overall Diameter (in) | Static Loaded Radius (in) | Rolling Circ. (in) | Flat Plate Area (in ²) | Weight (lbs) | Tread Depth 32nd in. |
|-----------|--------------|-------------------|-------|-------------|--------------------------|-----------------|----------------|-------------------------|-----------------|-----------------------|---------------------------|--------------------|------------------------------------|--------------|----------------------|
| 41H313 | 9.5L-15FI | Highway Implement | TL | D | 60 | 62 | 2,680 | 8 | 9.8 | 30.2 | 13.5 | 89 | na | 38 | 11 |
| 41H3A3 | 9.5L-15FI | Highway Implement | TL | F | 90 | 62 | 3,420 | 8 | 9.8 | 30.2 | 13.5 | 89 | na | 47 | 11 |
| 41H3L1 | 10.00-15FI | Highway Implement | TL | D | 60 | 62 | 3,960 | 8 | 11.2 | 34.1 | 15.3 | 101 | 67 | 49 | 11 |
| 41H383 | 11L-15FI | Highway Implement | TL | C | 45 | 62 | 2,600 | 8 | 10.6 | 31.1 | 13.8 | 92 | na | 39 | 11 |
| 41H386 | 11L-15FI | Highway Implement | TL | D | 60 | 62 | 3,080 | 8 | 10.6 | 31.1 | 13.8 | 92 | na | 43 | 11 |
| 41H392 | 11L-15FI | Highway Implement | TL | F | 90 | 62 | 3,960 | 8 | 10.6 | 31.1 | 13.8 | 92 | na | 51 | 11 |
| 41H387 | 12.5L-15FI | Highway Implement | TL | F | 90 | 62 | 4,680 | 10 | 12.1 | 32.1 | 14.3 | 95 | na | 62 | 11 |
| 41H382 | 13.50-15FI | Highway Implement | TL | C | 30 | 62 | 2,680 | 10 | 13.5 | 31.8 | 14.4 | 96 | na | 58 | 11 |
| 41H3D0 | 13.50-15FI | Highway Implement | TL | D | 45 | 62 | 3,300 | 10 | 13.5 | 31.8 | 14.4 | 96 | na | 62 | 11 |
| 41H3K0 | 13.50-15FI | Highway Implement | TL | E | 60 | 62 | 3,960 | 10 | 13.5 | 31.8 | 14.4 | 96 | na | 70 | 11 |
| 41H3F0 | 13.50-15FI | Highway Implement | TL | F | 75 | 62 | 4,540 | 10 | 13.5 | 31.8 | 14.4 | 96 | na | 75 | 11 |
| 41H388 | 14L-16.1FI | Highway Implement | TL | C | 30 | 62 | 3,420 | 11 | 14.2 | 37.5 | 16.7 | 112 | na | 79 | 12 |
| 41H3E0 | 16.5L-16.1FI | Highway Implement | TL | E | 60 | 62 | 6,450 | 14 | 17.2 | 41 | 18.2 | 121 | 146 | 109 | 11 |

*See Approved Rim Contours section

Titan

Bias Smooth



Titan Road Roller/Road Roller II Smooth

- Constructed of superior heat resistant nylon fabric plies to promote heat dissipation
- Designed for maximum life, this tire is frequently the tire of choice for industrial compactor applications

| Catalog # | Tire Size | Design | TL/TT | Load Rating | Inflation Pressure (psi) | Max Speed (mph) | Max Load (lbs) | Recom'd Rim Width* (in) | Tire Width (in) | Overall Diameter (in) | Static Loaded Radius (in) | Rolling Circ. (in) | Flat Plate Area (in ²) | Weight (lbs) | Tread Depth 32nd in. |
|-----------|-------------|----------------|-------|-------------|--------------------------|-----------------|----------------|-------------------------|-----------------|-----------------------|---------------------------|--------------------|------------------------------------|--------------|----------------------|
| 3GR256F | 7.50-15NHS | Road Roller II | TT | 6 | 55 | 5 | 3,900 | 6 | 8.1 | 30.8 | 14.1 | 92 | na | 46 | 0 |
| 3GR252F | 7.50-15NHS | Road Roller II | TT | 12 | 110 | 5 | 5,860 | 6 | 8.1 | 30.8 | 14.1 | 92 | na | 56 | 0 |
| 3GR2E1F | 7.50-15NHS | Road Roller II | TT | 14 | 125 | 5 | 6,300 | 6 | 8.1 | 30.8 | 14.1 | 92 | na | 56 | 0 |
| 3GR3A2 | 8.5/90-15K | Road Roller II | TL | 6 | 50 | 5 | 3,900 | 6 | 8.1 | 30.9 | 13.7 | 90 | na | 47 | 0 |
| 38R222F | 9.00-20NHS | Road Roller | TT | 12 | 90 | 5 | 8,950 | 7 | 10.2 | 39.8 | 18 | 117 | na | 115 | 0 |
| 38R283F | 11.00-20NHS | Road Roller | TT | 18 | 120 | 5 | 13,000 | 8 | 12.1 | 41.7 | 18.8 | 122 | na | 187 | 0 |

*See Approved Rim Contours section

#Tire rim fitment for these tires are not interchangeable. The 15K tire will only fit on a 5" drop center rim. The NHS tire is designed to fit on a 5" flat base rim. The 8.5/90-15K size designation was established to advise of this distinction.

Bias & Radial HF-1/HF-2

Titan



FLO-TRAC RIB



MULTI TRAC C/S

Titan Flo-Trac Rib HF-1

- Designed for maximum flotation and durability
- Low section height gives it improved handling

Titan Multi Trac C/S HF-1

- Greater tread depth and more rubber on the contact surface to provide increased puncture resistance and longer tire life
- Shoulder design minimizes turf damage



CLASSIC RIB



CLASSIC TX

Titan Classic Rib HF-1

- Specifically designed to reduce turf damage
- Good front end tire sporting a long-lasting, high performance rating

Titan Classic TX HF-1

- Landscaping projects, mowing and general grounds work are easily accomplished with this rugged tire, designed to take abuse
- Wide footprint endures heavy loads and provides stability and traction



Titan Soft Turf/LSW and LSW 430 HF-1

- Designed for low ground pressure use
- Ideal for fine lawn maintenance and can also be used for industrial applications
- Available in LSW
- The radial LSW430 is designed to reduce vehicle bounce, loping and sidewall heat build-up
- LSW430 features a low aspect ratio tire and a large diameter wheel



FLO-TRAC LUG



TRU POWER II

Titan Flo-Trac Lug HF-2

- Designed for maximum flotation and durability
- Features low section height for improved handling and roadability
- Open curved lug design allows for maximum self-cleaning and side hill slip resistance

Titan Tru Power II HF-2

- Ultimate deep-traction tire with a large contact area to provide the best traction
- A great performer on wet or dry surfaces
- Features a specially designed rim guard to keep debris from the bead seat area

| Catalog # | Tire Size | Design | TL/TT | Load Rating | Inflation Pressure (psi) | Max Load mph | Max Load (lbs) | Meas. Rim Width* (in) | Tire Width (in) | Overall Diameter (in) | Static Loaded Radius (in) | Rolling Circ. (in) | Flat Plate Area (in ²) | Weight (lbs) | Tread Depth 32nd in. |
|-----------|------------------|--------------|-------|-------------|--------------------------|--------------|----------------|-----------------------|-----------------|-----------------------|---------------------------|--------------------|------------------------------------|--------------|----------------------|
| 4743Q1 | 16x6.50-8NHS** | Multi Trac | TL | 8 | 58 | 10 | 950 | 5.375 | 6.8 | 16.5 | 7.5 | 50 | 14.1 | 11 | 9 |
| 481331 | 18x8.50-8NHS | Classic TX | TL | 4 | 22 | Highway | 815 | 7 | 8.1 | 17.8 | 7.8 | 51 | na | 13 | 11 |
| 483331 | 18x8.50-8NHS | Classic Rib | TL | 4 | 22 | Highway | 815 | 7 | 8.4 | 17.6 | 7.7 | 51 | na | 12 | 7 |
| 4233U1 | 18x8.50-10NHS | Tru Power II | TL | 4 | 22 | 10 | 830 | 7 | 7.8 | 18.5 | 8.8 | 56 | na | 15 | 16 |
| 4743U1 | 18x8.50-10NHS | Multi Trac | TL | 4 | 22 | 10 | 830 | 7 | 8.4 | 18.2 | 8.3 | 55 | 29.2 | 14 | 10 |
| 474318 | 20x8.00-10NHS | Multi Trac | TL | 4 | 24 | 10 | 895 | 6.5 | 8.3 | 19.9 | 9.1 | 61 | 36.3 | 19 | 10 |
| 4743X2 | 20x8.00-10NHS | Multi Trac | TL | 8 | 50 | 10 | 1,380 | 6.5 | 8.4 | 20.4 | 9.3 | 62 | 31.6 | 20 | 10 |
| 47L3X2 | 20x8.00-10NHS* | Multi Trac | TL | 10 | 62 | 10 | 1,570 | 6.5 | 8.3 | 19.8 | 8.8 | 59 | na | 20 | 10 |
| 47L4X2 | 20x8.00-10NHS* | Multi Trac | TL | 10 | 62 | 10 | 1,570 | 6.5 | 8.3 | 19.8 | 8.8 | 59 | na | 20 | 10 |
| 4743F1 | 22x9.00-12NHS** | Multi Trac | TL | 4 | 20 | 10 | 1,110 | 7 | 8.5 | 22.4 | 10 | 67 | 44 | 19 | 12 |
| 474353 | 23x10.50-12NHS** | Multi Trac | TL | 6 | 32 | 10 | 1,760 | 8.5 | 10.4 | 23.1 | 10.2 | 68 | 54.2 | 27 | 12 |
| 474301 | 23x8.50-12NHS** | Multi Trac | TL | 4 | 22 | 10 | 1,115 | 7 | 8.4 | 22.6 | 10.2 | 68 | 44 | 22 | 12 |
| 474372 | 23x8.50-12NHS** | Multi Trac | TL | 6 | 34 | 10 | 1,440 | 7 | 8.4 | 22.6 | 9.9 | 66 | 38 | 22 | 12 |

Titan

Bias & Radial HF-1/HF-2

| Catalog # | Tire Size | Design | TL/TT | Load Rating | Inflation Pressure (psi) | Max Load mph | Max Load (lbs) | Meas. Rim Width* (in) | Tire Width (in) | Overall Diameter (in) | Static Loaded Radius (in) | Rolling Circ. (in) | Flat Plate Area (in ²) | Weight (lbs) | Tread Depth 32nd in. |
|-----------|--------------------|---------------|-------|-------------|--------------------------|--------------|----------------|-----------------------|-----------------|-----------------------|---------------------------|--------------------|------------------------------------|--------------|----------------------|
| 4743K4 | 24x8.50-14NHS** | Multi Trac | TL | 8 | 44 | 10 | 1,870 | 7 | 8.5 | 24.2 | 10.2 | 72 | na | 23 | 11 |
| 4303N8 | 25x10.50LL-15NHS | Soft Turf | TL | 6 | 30 | 30 | 935 | 8.25 | 10.4 | 25.7 | 11.8 | 76 | na | 33 | 12 |
| 41F393 | 25x7.50-15NHS | Flo Trac Rib | TL | 4 | 30 | 30 | 960 | 5.5 | 7.8 | 24.9 | 11.6 | 74 | na | 23 | 8 |
| 41F378 | 25x7.50-15NHS | Flo Trac Rib | TL | 6 | 45 | 30 | 1,220 | 5.5 | 7.8 | 24.9 | 11.6 | 74 | na | 24 | 8 |
| 474339 | 25x8.50-14NHS | Multi Trac | TL | 4 | 22 | 10 | 1,320 | 7 | 8.7 | 25.4 | 11.7 | 78 | 47.3 | 26 | 11 |
| 474371 | 25x8.50-14NHS | Multi Trac | TL | 6 | 32 | 10 | 1,640 | 7 | 8.7 | 25.6 | 11.8 | 79 | 45.5 | 26 | 11 |
| 423361 | 26x12.00-12NHS | Tru Power II | TL | 4 | 20 | 10 | 1,780 | 10.5 | 12.3 | 25.6 | 12 | 77 | na | 42 | 20 |
| 423360 | 26x12.00-12NHS | Tru Power II | TL | 8 | 42 | 10 | 2,740 | 10.5 | 12.3 | 25.6 | 12 | 77 | na | 44 | 20 |
| 474361 | 26x12.00-12NHS | Multi Trac | TL | 4 | 20 | 10 | 1,780 | 10.5 | 12.2 | 25.2 | 10.9 | 73 | na | 38 | 12 |
| 474377 | 26x12.00-12NHS | Multi Trac | TL | 6 | 30 | 10 | 2,250 | 10.5 | 12.5 | 25.4 | 11.3 | 76 | 82 | 37 | 12 |
| 4743H6 | 27x10.50-15NHS** | Multi Trac | TL | 4 | 30 | 30 | 1,320 | 8 | 10.4 | 26.9 | 12.7 | 84 | 52 | 38 | 12 |
| 4743E0 | 27x10.50-15NHS** | Multi Trac | TL | 10 | 75 | 30 | 2,200 | 8 | 10.4 | 27.8 | 13 | 87 | 36.8 | 42 | 12 |
| 4303M7 | 27x12LL-15NHS | Soft Turf | TL | 6 | 30 | 30 | 1,320 | 10 | 12 | 27.5 | 12.2 | 85 | na | 36 | 10 |
| 474348 | 27x8.50-15NHS** | Multi Trac | TL | 4 | 30 | 30 | 1,230 | 7 | 8.4 | 26.9 | 12.5 | 83 | 38.4 | 30 | 11 |
| 474356 | 27x8.50-15NHS** | Multi Trac | TL | 6 | 45 | 30 | 1,570 | 7 | 8.6 | 27.5 | 12.8 | 85 | 47 | 29 | 11 |
| 41F395 | 27x9.50-15NHS | Flo Trac Rib | TL | 6 | 45 | 30 | 1,600 | 7 | 9.5 | 26.7 | 12.3 | 79 | na | 31 | 9 |
| 41F306 | 27x9.50-15NHS | Flo Trac Rib | TL | 8 | 60 | 30 | 1,900 | 7 | 9.5 | 26.7 | 12.3 | 79 | na | 33 | 9 |
| 474358 | 28x8.50-15NHS** | Multi Trac | TL | 4 | 30 | 30 | 1,430 | 7 | 8.5 | 27.6 | 12.6 | 84 | 48.1 | 23 | 11 |
| 4743L5 | 29x12.50-15NHS** | Multi Trac | TL | 4 | 20 | 30 | 1,320 | 10 | 12.6 | 29.5 | 13.5 | 90 | 61.3 | 42 | 12 |
| 4743D4 | 29x12.50-15NHS** | Multi Trac | TL | 6 | 30 | 30 | 1,710 | 10 | 12.6 | 29.5 | 13.6 | 90.6 | 57 | 45 | 12 |
| 423C20 | 29x12.50-15NHS | Tru Power II | TL | 6 | 30 | 10 | 1,710 | 10 | 12.5E | 29.E | 13.3E | 86E | na | 69 | 21 |
| 4748L5 | 29x12.50-15NHS | Multi Trac | TL | 8 | 45 | 30 | 2,150 | 10 | 12.2 | 29.1 | 13 | 87 | na | 48 | 12 |
| 47434A | 31x13.50-15NHS | Multi Trac | TL | 4 | 20 | 30 | 1,650 | 10 | 13.8 | 31.5 | 14.5 | 96 | 83.3 | 53 | 12 |
| 4743U2 | 31x13.50-15NHS | Multi Trac | TL | 8 | 45 | 30 | 2,600 | 10 | 13.9 | 31.5 | 14.5 | 96 | 66.8 | 56 | 12 |
| 4743U3 | 31x13.50-15NHS | Multi Trac | TL | 10 | 60 | 30 | 3,080 | 10 | 13.9 | 31.9 | 14.7 | 98 | 72 | 64 | 12 |
| 47L4U3 | 31x13.50-15NHS* | Multi Trac | TL | 12 | 75 | 30 | 3,520 | 10 | 13.6 | 32.1 | 14.3 | 95 | na | 70 | 12 |
| 41F396 | 31x13.50-15NHS | Flo Trac Rib | TL | 6 | 30 | 30 | 2,090 | 10 | 13.5 | 31.8 | 14.4 | 94 | na | 54 | 10 |
| 41N396# | 31x13.50-15NHS | Flo Trac Rib | TL | 6 | 30 | 30 | 2,090 | 10 | 13.5 | 31.8 | 14.4 | 94 | na | 54 | 10 |
| 41F397 | 31x13.50-15NHS | Flo Trac Rib | TL | 8 | 45 | 30 | 2,600 | 10 | 13.5 | 31.8 | 14.4 | 94 | na | 58 | 10 |
| 41N397 | 31x13.50-15NHS | Flo Trac Rib | TL | 8 | 45 | 30 | 2,600 | 10 | 13.5 | 31.8 | 14.4 | 94 | na | 58 | 10 |
| 41N307 | 31x13.50-15NHS | Flo Trac Rib | TL | 10 | 60 | 30 | 3,080 | 10 | 13.5 | 31.8 | 14.4 | 94 | na | 71 | 10 |
| 41N3U9 | 31x13.50-15NHS | Flo Trac Rib | TL | 14 | 90 | 30 | 3,960 | 10 | 13.5 | 31.8 | 14.4 | 94 | na | 76 | 10 |
| 41G3A4 | 31x15.50-15NHS | Flo Trac Lug | TL | 8 | 45 | 30 | 2,740 | 13 | 15.7 | 32.1 | 14.9 | 98 | 26 | 75 | 22 |
| 4233A4 | 31x15.50-15NHS | Tru Power II | TL | 8 | 45 | 30 | 2,760 | 13 | 15 | 31.9 | 14.3 | 96 | na | 72 | 24 |
| 41G3H1 | 33x12.50-15NHS | Flo Trac Lug | TL | 8 | 45 | 30 | 3,300 | 10 | 12.8 | 33.3 | 15 | 100 | na | 61 | 27 |
| 4743J0 | 33x12.50-16.5NHS** | Multi Trac | TL | 4 | 30 | 30 | 2,340 | 9.75 | 12.7 | 32.6 | 15 | 100 | 63.6 | 56 | 12 |
| 4743C4 | 33x14.50-15NHS | Multi Trac | TL | 4 | 20 | 30 | 2,090 | 10 | 14.5 | 33.2 | 15.4 | 101 | na | 55 | 12 |
| 4233L0 | 35x12.00-16.5NHS | Tru Power II | TL | 4 | 25 | 10 | 2,450 | 9.75 | 11.8 | 34.9 | 16.5 | 104 | na | 75 | 29 |
| 41G3G3 | 35x19.00-16.1NHS | Flo Trac Lug | TL | 12 | 55 | 30 | 4,180 | 16 | 17.8 | 35 | 16.4 | 104 | na | 100 | 40 |
| 474350 | 36x13.50-15NHS | Multi Trac | TL | 4 | 20 | 30 | 2,600 | 10 | 15 | 36 | 16.1 | 106 | na | 65 | 12 |
| 41G3F1 | 38x18.00-20NHS | Flo Trac Lug | TL | 10 | 45 | 30 | 3,430 | 14 | 17.7 | 40.6 | 18.4 | 121 | na | 134 | 40 |
| 41G3R6 | 38x18.00-20NHS | Flo Trac Lug | TL | 14 | 65 | 30 | 4,300 | 14 | 17.7 | 40.6 | 18.4 | 121 | na | 143 | 40 |
| 41G5R6 | 38x18.00-20NHS | Flo Trac Lug | TL | 16 | 75 | 30 | 4,680 | 14 | 17.7 | 40.6 | 18.4 | 121 | na | 145 | 40 |
| 474323 | 41x14.00-20NHS | Multi Trac | TL | 4 | 25 | 30 | 3,080 | 11 | 14.6 | 42 | 19.2 | 128 | 10.4 | 103 | 22 |
| 474342 | 44x18.00-20NHS** | Multi Trac | TL | 4 | 20 | 30 | 3,420 | 14 | 18.6 | 45.9 | 20.3 | 135 | 210 | 133 | 25 |
| 4743W1 | 44x18.00-20NHS** | Multi Trac | TL | 6 | 30 | 30 | 4,300 | 14 | 18.4 | 44.9 | 20.5 | 137 | 195 | 143 | 25 |
| G30573 | LSW305R343 | LSW 430 | TL | 121A3 | 52 | 10 | 3,200 | 229 | 11.5 | 25.8 | 11.7 | 78 | na | 33 | 8 |
| G3032K | LSW305-521 | LSW Soft Turf | TL | 6 | 30 | 30 | 2,340 | 210 | 12 | 33.5 | 14.7 | 98 | na | 55 | 10 |
| G303H4 | LSW570-648 | LSW Soft Turf | TL | 6 | 60 | 30 | 6,800 | 457 | 22.5 | 45.5 | 21 | 140 | na | 164 | 12 |
| G303P0 | LSW610R470 | LSW 430 | TL | 125A8 | 30 | 30 | 3,640 | 483 | 23.7 | 40 | 17.8 | 119 | na | 144 | 12 |

*See Approved Rim Contours section

#Minimum Order Quantity

* Stubble Guard Tread Compound

**ECE Certified

Bias Skid Steer

Titan



CONTRACTOR FWD



H/E

Titan Contractor FWD SS

- Excellent traction and wear are the benefits of the broad, curved lugs
- High strength construction gives it exceptional durability

Titan H/E SS

- The H/E is Titan's premium deep tread skid steer tire, designed for use in severe applications such as concrete planing, asphalt recycling, demolition areas, quarries, glass plants and scrap yards



HD2000



HD2000 II

Titan HD2000 SS

- Engineered with HD sidewalls to protect against abrasions, tears and punctures
- Improved dual tapered step lug wear and extended life

Titan HD2000 II SS

- Titan's premium conventional skid steer tire with deeper tread depth, premium compound, larger tread lugs, heavier sidewall and larger rim guard



TRAC LOADER



TRAC LOADER CHEVRON

Titan Trac Loader SS

- The tire preferred by major manufacturers of unloaders and skid steer equipment
- Center lug design adds extra traction

Titan Trac Loader Chevron SS

- Features a chevron tread pattern with nylon fabric construction
- Intended for skid steer use



MXL SS



ULTIMATE

Titan Ultimate

- Extra long life with up to twice the tread depth of conventional skid steer tires.
- Superior damage resistance due to extra heavy sidewall and large rim guard.
- Superior traction from high void-to-lug ratio.
- Lowest possible cost per hour delivered by specialty compound and industry leading tread depth.

Titan MXL SS

- Ultra deep tread provides exceptional service in hard service applications
- Directional tread design makes the tire a performer in the dirt.



SOFT TURF

Titan Soft Turf

- Designed for low ground pressure use on turf.
- Ideal for fine lawn maintenance and can be used in industrial applications.
- Less aggressive to minimize turf damage.

| Catalog # | Tire Size | Design | TL/TT | Load Rating | Inflation Pressure (psi) | Max Speed (mph) | Max Load (lbs) | Recom'd Rim Width* (in) | Tire Width (in) | Overall Diameter (in) | Static Loaded Radius (in) | Rolling Circ. (in) | Flat Plate Area (in ²) | Weight (lbs) | Tread Depth 32nd in. | Number of Lugs |
|-----------|---------------|----------------------|-------|-------------|--------------------------|-----------------|----------------|-------------------------|-----------------|-----------------------|---------------------------|--------------------|------------------------------------|--------------|----------------------|----------------|
| 4123C2 | 5.70-12NHS | Trac Loader Chevron | TL | 4 | 60 | 5 | 1,450 | 4.5 | 5.7 | 22.4 | 10.3 | 67 | na | 19 | 18 | 28 |
| 4123C5 | 7.00-15SS | Trac Loader Chevron | TL | 6 | 60 | 5 | 3,180 | 5.5 | 8 | 29.9 | 13.5 | 88 | na | 37 | 18 | 58 |
| 4127K5 | 8.25-15NHS | Trac Loader Chevron | TL | 6 | 50 | 5 | 3,860 | 6 | 9.4 | 33.2 | 14.9 | 98 | na | 53 | 18 | |
| 49E3D1TYL | 10-16.5NHS | HD2000II w/Tyrelyner | TL | 8 | 60 | 5 | 4,140 | 8.25 | 10.5 | 30.3 | 14.1 | 91 | na | 83 | 24 | 42 |
| 4393D1 | 10-16.5NHS | HD2000 | TL | 8 | 60 | 5 | 4,140 | 8.25 | 10.3 | 30.6 | 14.3 | 92 | na | 58 | 21 | 46 |
| 49E3D1 | 10-16.5NHS | HD2000II | TL | 8 | 60 | 5 | 4,140 | 8.25 | 10.5 | 30.3 | 14.1 | 91 | na | 58 | 24 | 42 |
| 49U3D1 | 10-16.5NHS | Ultimate | TL | 8 | 60 | 5 | 4,140 | 8.25 | 10.7 | 30.1 | 13.7 | 91 | na | 72 | 42 | 38 |
| 43H3R8 | 10-16.5NHS | H/E | TL | 10 | 75 | 5 | 4,710 | 8.25 | 10.4 | 30.6 | 13.7 | 89 | na | 79 | 44 | 44 |
| 4123C8 | 10-16.5NHS | Trac Loader | TL | 6 | 45 | 5 | 3,500 | 8.25 | 10.9 | 30.8 | 13.9 | 93 | 81 | 45 | 19 | 46 |
| 4393D1TYL | 10-16.5NHS | HD2000 w/Tyrelyner | TL | 8 | 60 | 5 | 4,140 | 8.25 | 10.3 | 30.6 | 14.3 | 92 | na | 74 | 21 | 46 |
| G9E3D1 | LSW10-19.5NHS | HD2000II | TL | 8 | 60 | 5 | 4140 | 8.25 | 10.4 | 30.6 | 13.9 | 93 | na | 59 | 24 | 42 |

Titan

Bias Skid Steer

| Catalog # | Tire Size | Design | TL/TT | Load Rating | Inflation Pressure (psi) | Max Speed (mph) | Max Load (lbs) | Recom'd Rim Width* (in) | Tire Width (in) | Overall Diameter (in) | Static Loaded Radius (in) | Rolling Circ. (in) | Flat Plate Area (in ²) | Weight (lbs) | Tread Depth 32nd in. | Number of Lugs |
|-----------|-------------------|----------------------|-------|-------------|--------------------------|-----------------|----------------|-------------------------|-----------------|-----------------------|---------------------------|--------------------|------------------------------------|--------------|----------------------|----------------|
| G9E3J7 | LSW12-19.5NHS | HD2000II | TL | 10 | 65 | 5 | 5600 | 9.75 | 12.1 | 32.7 | 14.7 | 98 | na | 79 | 24 | 42 |
| 4393J7YL | 12-16.5NHS | HD2000II w/Tyrelyner | TL | 10 | 65 | 5 | 5,600 | 9.75 | 12.2 | 32.7 | 15 | 97 | na | 99 | 26 | 42 |
| 4393C9 | 12-16.5NHS | HD2000 | TL | 6 | 40 | 5 | 4,220 | 9.75 | 12.8 | 32.7 | 15.3 | 99 | na | 75 | 23 | 46 |
| 49U3J7 | 12-16.5NHS | Ultimate | TL | 10 | 65 | 5 | 5,600 | 9.75 | 12.1 | 32.7 | 14.9 | 98 | na | 94 | 44 | 38 |
| 4123J7 | 12-16.5NHS | Trac Loader | TL | 10 | 65 | 5 | 5,600 | 9.75 | 12.2 | 33.6 | 15.1 | 101 | na | 69 | 23 | 46 |
| 4393J7 | 12-16.5NHS | HD2000 | TL | 10 | 65 | 5 | 5,600 | 9.75 | 12.8 | 32.7 | 15.3 | 99 | na | 77 | 23 | 46 |
| 49E3J7 | 12-16.5NHS | HD2000II | TL | 10 | 65 | 5 | 5,600 | 9.75 | 12.2 | 32.7 | 15 | 97 | na | 77 | 26 | 42 |
| 49E34R | 12-16.5NHS | HD2000II | TL | 14 | 90 | 5 | 6,780 | 9.75 | 12.2 | 32.7 | 15 | 97 | na | 83 | 26 | 42 |
| 43H34R | 12-16.5NHS | H/E | TL | 14 | 90 | 5 | 6,780 | 9.75 | 12 | 32.7 | 15 | 97 | na | 106 | 44 | 44 |
| 4123C9 | 12-16.5NHS | Trac Loader | TL | 6 | 40 | 5 | 4,220 | 9.75 | 12.1 | 33.6 | 15.1 | 101 | na | 68 | 23 | 46 |
| 4123D2 | 12-16.5NHS | Trac Loader | TL | 8 | 50 | 5 | 4,810 | 9.75 | 12.2 | 33.6 | 15.1 | 101 | na | 72 | 23 | 48 |
| 46C3J7 | 12-16.5NHS | Contractor FWD | TL | 10 | 65 | 5 | 5,600 | 9.75 | 11.8 | 33.1 | 14.9 | 98 | na | 77 | 23 | 46 |
| 4303J7 | 12-16.5NHS | Soft Turf | TL | 10 | 65 | 5 | 5,600 | 9.75 | 14.2 | 32.9 | 14.7 | 98 | na | 68 | 10 | na |
| 49E3J8# | 12-16.5NHS | HD2000II | TL | 12 | 80 | 5 | 6,320 | 9.75 | 12.2 | 32.7 | 15 | 97 | na | 78 | 26 | 42 |
| 430396 | 14-17.5NHS | Soft Turf | TL | 10 | 55 | 5 | 6,850 | 10.5 | 15.3 | 36.1 | 16 | 106 | na | 78 | 10 | na |
| 439396 | 14-17.5NHS | HD2000 | TL | 10 | 55 | 5 | 6,850 | 10.5 | 14.5 | 36.3 | 16.2 | 108 | na | 94 | 24 | 46 |
| 439349 | 14-17.5NHS | HD2000 | TL | 12 | 65 | 5 | 7,550 | 10.5 | 14.5 | 36.3 | 16.2 | 108 | na | 102 | 24 | 46 |
| 439384 | 14-17.5NHS | HD2000 | TL | 14 | 80 | 5 | 8,540 | 10.5 | 14.5 | 36.3 | 16.2 | 108 | na | 106 | 24 | 46 |
| 49E384 | 14-17.5NHS | HD2000II | TL | 14 | 80 | 5 | 8,540 | 10.5 | 15.2 | 35.7 | 16.4 | 107 | na | 121 | 26 | 42 |
| 43H384 | 14-17.5NHS | H/E | TL | 14 | 80 | 5 | 8,540 | 10.5 | 14.1 | 36.6 | 17 | 110 | na | 141 | 47 | 46 |
| 412334 | 14-17.5NHS | Trac Loader | TL | 6 | 30 | 5 | 4,820 | 10.5 | 14 | 36.9 | 16.3 | 109 | na | 91 | 24 | 46 |
| 412396 | 14-17.5NHS | Trac Loader | TL | 10 | 55 | 5 | 6,850 | 10.5 | 14 | 36.9 | 16.3 | 109 | na | 94 | 24 | 46 |
| 412384 | 14-17.5NHS | Trac Loader | TL | 14 | 80 | 5 | 8,540 | 10.5 | 14.3 | 36.4 | 16.4 | 107 | na | 106 | 24 | 46 |
| 46C3G9 | 14-17.5NHS | Contractor FWD | TL | 10 | 55 | 5 | 6,850 | 10.5 | 13.8 | 36.3 | 16.3 | 108 | na | 84 | 24 | 46 |
| 49U384 | 14-17.5NHS | Ultimate | TL | 14 | 80 | 5 | 8,540 | 10.5 | 15.2 | 35.7 | 16.4 | 107 | na | 148 | 44 | 42 |
| 439336 | 15-19.5NHS | HD2000 | TL | 12 | 60 | 5 | 9,190 | 11.75 | 15.7 | 40.5 | 19.2 | 123 | na | 136 | 26 | 46 |
| 439636 | 15-19.5NHS | HD2000 | TL | 16 | 85 | 5 | 11,270 | 11.75 | 15.7 | 40.5 | 19.2 | 123 | na | 150 | 26 | 46 |
| 412373 | 15-19.5NHS | Trac Loader | TL | 6 | 30 | 5 | 6,130 | 11.75 | 15.5 | 40.5 | 17.9 | 117 | na | 114 | 25 | 44 |
| 412336 | 15-19.5NHS | Trac Loader | TL | 12 | 60 | 5 | 9,190 | 11.75 | 15.5 | 40.5 | 17.9 | 117 | na | 136 | 25 | 44 |
| 46C3H9 | 15-19.5NHS | Contractor FWD | TL | 8 | 40 | 5 | 7,250 | 11.75 | 15.3 | 40.1 | 18 | 119 | na | 113 | 26 | 46 |
| 4123U1 | 18x8.50-10NHS | Trac Loader | TL | 4 | 22 | 5 | 830 | 7 | 7.5 | 17.7 | 8.1 | 53 | 38 | 18 | 16 | 32 |
| 49E3W8 | 20x8.00-10NHS | HD2000II | TL | 4 | 40 | 5 | 1,210 | 6 | 8.2 | 19.3 | 8.8 | 57 | na | 24 | 15 | 30 |
| 4393G8 | 23x8.50-12NHS | HD2000 | TL | 6 | 50 | 5 | 1,810 | 7 | 8.7 | 23.5 | 11 | 71 | na | 27 | 14 | 40 |
| 4123C3 | 23x8.50-12NHS | Trac Loader | TL | 4 | 35 | 5 | 1,470 | 7 | 8.3 | 23 | 10.2 | 68 | na | 27 | 14 | 40 |
| 4123G8 | 23x8.50-12NHS | Trac Loader | TL | 6 | 50 | 5 | 1,810 | 7 | 8.3 | 23 | 10.2 | 68 | na | 27 | 14 | 40 |
| 412388 | 23x8.50-14NHS | Trac Loader | TL | 4 | 35 | 5 | 1,490 | 7 | 7.8 | 23.8 | 10.7 | 71 | na | 25 | 14 | 44 |
| 412379 | 25x8.50-14NHS | Trac Loader | TL | 6 | 50 | 5 | 2,000 | 7 | 8.4 | 25.9 | 11.8 | 79 | na | 30 | 17 | 44 |
| 412361 | 26x12.0-12NHS | Trac Loader | TL | 4 | 20 | 5 | 1,780 | 10.5 | 12.2 | 25.5 | 11.3 | 77 | 84 | 40 | 16 | 40 |
| 439378 | 27x10.50-15NHS | HD2000 | TL | 8 | 60 | 5 | 3,100 | 8.5 | 10.2 | 27.1 | 12.8 | 82 | na | 47 | 15 | 42 |
| 4123H7 | 27x10.50-15NHS | Trac Loader | TL | 6 | 45 | 5 | 2,610 | 8.5 | 11 | 27.5 | 12.3 | 82 | na | 39 | 17 | 44 |
| 439377 | 27x8.50-15NHS | HD2000 | TL | 8 | 60 | 5 | 2,890 | 7 | 8.6 | 26.8 | 12.5 | 81 | na | 39 | 15 | 42 |
| 4123C6 | 27x8.50-15NHS | Trac Loader | TL | 4 | 30 | 5 | 1,940 | 7 | 8.8 | 27 | 12.1 | 81 | na | 39 | 17 | 44 |
| 412339 | 27x8.50-15NHS | Trac Loader | TL | 6 | 45 | 5 | 2,480 | 7 | 8.8 | 27 | 12.1 | 81 | na | 39 | 17 | 44 |
| 4122N7 | 27X12.5-15NHS | Trac Loader | TL | 4 | 25 | 5 | 2,340 | 10 | 11.2 | 28.2 | 12.6 | 83.7 | 105 | 45 | 17 | 44 |
| 4123R3 | 28x8.50-15NHS | Trac Loader | TL | 6 | 45 | 5 | 2,880 | 7 | 8.4 | 28 | 12.8 | 83 | na | 29 | 17 | 44 |
| 4123J9 | 33-14.50-16.5NHS | Trac Loader | TL | 8 | 40 | 5 | 4,690 | 12 | 14.5 | 33 | 14.9 | 98 | na | 72 | 23 | 46 |
| 439381 | 30.5x12.5-16.5NHS | HD2000 | TL | 8 | 45 | 5 | 3,840 | 9.75 | 12.5 | 30.8 | 14 | 91 | na | 74 | 21 | 46 |
| 49E3L8 | 31x15.50-16.5NHS | HD2000II | TL | 8 | 35 | 5 | 4,480 | 12 | 15.5 | 31 | 14.1 | 92 | na | 187 | 17 | 46 |
| 49E3L9 | 31X15.50-16.5NHS | HD2000II | TL | 12 | 60 | 5 | 6,150 | 12 | 15.5 | 31 | 14.1 | 92 | na | 90 | 24 | 42 |
| 49E3X3 | 33x15.5-16.5NHS | HD2000II | TL | 12 | 60 | 5 | 6,835 | 12 | 15.5 | 33 | 15 | 98 | na | 110 | 24 | 42 |
| 43H3X3 | 33x15.50-16.5NHS | H/E | TL | 12 | 60 | 5 | 6,835 | 12 | 14.5 | 33 | 14.7 | 99 | 135 | 120 | 48 | 44 |
| 49E3R9 | 33x15.5-16.5NHS | HD2000II | TL | 14 | 70 | 5 | 7,480 | 12 | 15.5 | 33 | 15 | 98 | na | 110 | 24 | 42 |
| 4123A5 | 43x16.00-20NHS | Trac Loader | TL | 4 | 20 | 5 | 4,540 | 14 | 16 | 43.5 | 19.3 | 129 | na | 135 | 26 | 44 |
| G9A3D1 | LSW256-521NHS | LSWG9A | TL | 10 | 60 | 5 | 4,720 | 210 | 10.2 | 30.6 | 14.2 | 92 | na | 56 | 24 | 42 |
| G9A3M1 | LSW305-546NHS | LSWG9A | TL | 10 | 65 | 5 | 5,600 | 248 | 12.1 | 32.8 | 15.1 | 98 | na | 73 | 24 | 21 |

*See Approved Rim Contours section
#Minimum Quantity Order **ECE Certified

ATV

Titan



Titan 489 X/T ATV

- This tire provides excellent all-around traction in 2WD and 4WD applications
- Includes dimpled tread elements and six ply rated construction

| Catalog # | Tire Size | Design | TL/TT | Load Rating | Inflation Pressure (psi) | Max Speed (mph) | Max Load (lbs) | Recom'd Rim Width* (in) | Tire Width (in) | Overall Diameter (in) | Static Loaded Radius (in) | Rolling Circ. (in) | Flat Plate Area (in ²) | Weight (lbs) | Tread Depth 32nd in. |
|-----------|------------|---------|-------|-------------|--------------------------|-----------------|----------------|-------------------------|-----------------|-----------------------|---------------------------|--------------------|------------------------------------|--------------|----------------------|
| 4113A5 | AT22x11-10 | 489 X/T | TL | 6 | 7 | 50 | 385 | 9 | 10.6 | 22.1 | 9.9 | 65 | -- | 22 | 19 |
| 411327 | AT23x10-10 | 489 X/T | TL | 6 | 7 | 50 | 375 | 8 | 9.8 | 23.1 | 10.5 | 68 | -- | 20 | 19 |
| 411330 | AT23x10-12 | 489 X/T | TL | 6 | 7 | 50 | 365 | 8 | 9.2 | 23.1 | 10.6 | 69 | -- | 21 | 19 |
| 411307 | AT23x7-10 | 489 X/T | TL | 6 | 7 | 50 | 275 | 5.5 | 7 | 23 | 10.4 | 67 | -- | 19 | 19 |
| 411304 | AT23x8-11 | 489 X/T | TL | 6 | 7 | 50 | 200 | 6.5 | 7.6 | 23.5 | 10.6 | 70 | -- | 18 | 19 |
| 411329 | AT23x8-12 | 489 X/T | TL | 6 | 7 | 50 | 280 | 6.5 | 7.4 | 23.2 | 10.6 | 69 | -- | 18 | 19 |
| 411328 | AT24x10-11 | 489 X/T | TL | 6 | 7 | 50 | 395 | 7 | 10.1 | 24.1 | 10.8 | 70 | -- | 24 | 19 |
| 411344 | AT24x11-12 | 489 X/T | TL | 6 | 7 | 50 | 430 | 9 | 10.3 | 24.3 | 10.9 | 71 | -- | 25 | 19 |
| 411332 | AT24x8-11 | 489 X/T | TL | 6 | 7 | 50 | 320 | 6.5 | 8 | 24 | 10.8 | 71 | -- | 21 | 19 |
| 411337 | AT24x8-12 | 489 X/T | TL | 6 | 7 | 50 | 310 | 6.5 | 7.5 | 24.2 | 10.5 | 69 | -- | 20 | 18 |
| 4113A9 | AT24x9-11 | 489 X/T | TL | 6 | 7 | 50 | 365 | 7 | 9.1 | 24.2 | 11.1 | 72 | -- | 21 | 19 |
| 411342 | AT24x9-12 | 489 X/T | TL | 6 | 7 | 50 | 355 | 8 | 9 | 23.8 | 10.8 | 68 | -- | 20 | 19 |
| 411321 | AT25x10-12 | 489 X/T | TL | 6 | 7 | 50 | 420 | 8 | 10.5 | 25.2 | 11.2 | 74 | -- | 26 | 19 |
| 411308 | AT25x11-10 | 489 X/T | TL | 6 | 7 | 50 | 455 | 9 | 10.9 | 25.3 | 11.3 | 74 | -- | 29 | 19 |
| 411346 | AT25x11-12 | 489 X/T | TL | 6 | 7 | 50 | 455 | 9 | 10.9 | 25.3 | 11.3 | 74 | -- | 31 | 19 |
| 411306 | AT25x8-12 | 489 X/T | TL | 6 | 7 | 50 | 340 | 6.5 | 7.5 | 25.1 | 11.2 | 74 | -- | 20 | 19 |
| 411355 | AT26x10-12 | 489 X/T | TL | 6 | 7 | 50 | 440 | 8 | 10.1 | 25.8 | 11.6 | 76 | -- | 25 | 19 |

*See Approved Rim Contours section



Titan 589 M/T ATV

- Building on the heritage of the popular AT589, this second generation tire is designed for the serious ATV enthusiast
- Stepped lugs provide lug strength and stability
- Features the deepest lug depth available
- Titan's exclusive LSW 589 M/T design is now available to enhance the ATV experience, redefining traction and stability

| Catalog # | Tire Size | Design | TL/TT | Load Rating | Inflation Pressure (psi) | Max Speed (mph) | Max Load (lbs) | Recom'd Rim Width* (in) | Tire Width (in) | Overall Diameter (in) | Static Loaded Radius (in) | Rolling Circ. (in) | Flat Plate Area (in ²) | Weight (lbs) | Tread Depth 32nd in. |
|-----------|------------|---------|-------|-------------|--------------------------|-----------------|----------------|-------------------------|-----------------|-----------------------|---------------------------|--------------------|------------------------------------|--------------|----------------------|
| 45X332 | AT24x8-11 | 589 M/T | TL | 6 | 7 | 50 | 320 | 6.5 | 8.1 | 24.3 | 11.1 | 73 | -- | 23 | 33 |
| 45X3V7 | AT25x10-11 | 589 M/T | TL | 6 | 7 | 50 | 355 | 7 | 9.8 | 25.4 | 11.3 | 74 | -- | 32 | 36 |
| 45X321 | AT25x10-12 | 589 M/T | TL | 6 | 7 | 50 | 340 | 8 | 9.8 | 25.4 | 11.5 | 75 | -- | 29 | 36 |
| 45X393 | AT25x12-10 | 589 M/T | TL | 6 | 7 | 50 | 495 | 8 | 11.5 | 25.4 | 11.3 | 74 | -- | 38 | 36 |
| 45X306 | AT25x8-12 | 589 M/T | TL | 6 | 7 | 50 | 420 | 6.5 | 7.9 | 24.9 | 11.2 | 75 | -- | 24 | 33 |
| 45X361 | AT26x12-12 | 589 M/T | TL | 6 | 7 | 50 | 410 | 8 | 11 | 26.3 | 11.9 | 79 | -- | 40 | 36 |
| 45X3P6 | AT26x9-12 | 589 M/T | TL | 6 | 7 | 50 | 520 | 7 | 9.2 | 26.3 | 11.9 | 79 | -- | 38 | 36 |
| 45X3U0 | AT27x11-12 | 589 M/T | TL | 6 | 7 | 50 | 495 | 8 | 10.2 | 27.5 | 12.4 | 82 | -- | 37 | 36 |
| 45X3T0 | AT27x9-12 | 589 M/T | TL | 6 | 7 | 50 | 440 | 6.5 | 8.9 | 27.4 | 12.4 | 82 | -- | 37 | 36 |
| 45X35A | AT28x11x12 | 589 M/T | TL | 6 | 7 | 50 | 535 | 8 | 10.1 | 28.2 | 12.7 | 84 | -- | 36 | 36 |
| 45X34N | AT28x9x12 | 589 M/T | TL | 6 | 7 | 50 | 465 | 6.5 | 8.8 | 28 | 12.7 | 84 | -- | 38 | 36 |

| Catalog # | Tire Size | Design | TL/TT | Load Rating | Inflation Pressure (psi) | Max Speed (mph) | Max Load (lbs) | Recom'd Rim Width* (in) | Tire Width (in) | Overall Diameter (in) | Static Loaded Radius (in) | Rolling Circ. (in) | Flat Plate Area (in ²) | Weight (lbs) | Tread Depth 32nd in. |
|-----------|-----------|--------|-------|-------------|--------------------------|-----------------|----------------|-------------------------|-----------------|-----------------------|---------------------------|--------------------|------------------------------------|--------------|----------------------|
|-----------|-----------|--------|-------|-------------|--------------------------|-----------------|----------------|-------------------------|-----------------|-----------------------|---------------------------|--------------------|------------------------------------|--------------|----------------------|

| LSW | | | | | | | | | | | | | | | |
|--------|--------------|-------------|----|---|---|----|-----|----------|-----|------|------|----|----|----|----|
| G5X3T0 | LSW230-394AT | LSW 589 M/T | TL | 6 | 7 | 50 | 440 | 152 (mm) | 8.8 | 27.3 | 12.5 | 81 | -- | 31 | 36 |
| G5X3U0 | LSW255-394AT | LSW 589 M/T | TL | 6 | 7 | 50 | 465 | 152 (mm) | 9.9 | 27.3 | 12.5 | 81 | -- | 32 | 36 |

*See Approved Rim Contours section



Titan Fast Trekker ATV

- Developed specifically to address the demands of maneuverability
- The center V-lug provides straight ahead traction, while the S-knob cleats offer side bite on loose pack surfaces

| Catalog # | Tire Size | Design | TL/TT | Load Rating | Inflation Pressure (psi) | Max Speed (mph) | Max Load (lbs) | Recom'd Rim Width* (in) | Tire Width (in) | Overall Diameter (in) | Static Loaded Radius (in) | Rolling Circ. (in) | Flat Plate Area (in ²) | Weight (lbs) | Tread Depth 32nd in. |
|-----------|------------|--------------|-------|-------------|--------------------------|-----------------|----------------|-------------------------|-----------------|-----------------------|---------------------------|--------------------|------------------------------------|--------------|----------------------|
| 46U3C3 | AT18x11-10 | Fast Trekker | TL | 3* | 7 | 50 | 280 | 9 | 10.2 | 17.4 | 7.6 | 50 | -- | 15 | 16 |
| 46U3Z4 | AT20x10-9 | Fast Trekker | TL | 3* | 7 | 50 | 300 | 8 | 9.9 | 19.8 | 8.9 | 58 | -- | 18 | 20 |
| 46U370 | AT20x7-8 | Fast Trekker | TL | 3* | 7 | 50 | 240 | 5.5 | 7.4 | 20.3 | 9.2 | 60 | -- | 15 | 16 |
| 46U3A1 | AT21x7-10 | Fast Trekker | TL | 3* | 7 | 50 | 235 | 5.5 | 7 | 20.4 | 9.5 | 61 | -- | 13 | 16 |
| 46U3B2 | AT21x8-9 | Fast Trekker | TL | 3* | 7 | 50 | 240 | 6.5 | 7.4 | 20.2 | 9.2 | 60 | -- | 15 | 16 |
| 46U3A5 | AT22x11-10 | Fast Trekker | TL | 3* | 7 | 50 | 385 | 9 | 11 | 22 | 9.9 | 64 | -- | 23 | 16 |
| 46U387 | AT22x11-8 | Fast Trekker | TL | 3* | 7 | 50 | 395 | 9 | 11 | 21.3 | 9.6 | 63 | -- | 23 | 16 |
| 46U3A8 | AT22x8-10 | Fast Trekker | TL | 3* | 7 | 50 | 275 | 6.5 | 8.2 | 21.8 | 10 | 65 | -- | 17 | 16 |

*See Approved Rim Contours section



Mud Monster



Raptor

Titan Radial Mud Monster ATV

- In mud or extremely difficult terrain, the Titan Radial Mud Monster offers maximum bite with a full 26" outside diameter
- A rounded profile maintains steer characteristics usually only associated with less aggressive designs

Titan Raptor ATV

- Just like its name implies, this tire is meant for the lost world
- Thick, talon-like lugs sink into gnarly terrain



Titan Sabre Tooth ATV

- If your idea of fun means pushing the envelope, then the Sabre Tooth is the tire for you
- The Sabre Tooth carries on the tradition of offering a general purpose tread design that gives outstanding performance

| Catalog # | Tire Size | Design | TL/TT | Load Rating | Inflation Pressure (psi) | Max Speed (mph) | Max Load (lbs) | Recom'd Rim Width* (in) | Tire Width (in) | Overall Diameter (in) | Static Loaded Radius (in) | Rolling Circ. (in) | Flat Plate Area (in ²) | Weight (lbs) | Tread Depth 32nd in. |
|-----------|--------------|-------------|-------|-------------|--------------------------|-----------------|----------------|-------------------------|-----------------|-----------------------|---------------------------|--------------------|------------------------------------|--------------|----------------------|
| 407306 | AT25x8-12 | Sabre Tooth | TL | 3* | 7 | 50 | 340 | 6.5 | 7.5 | 25.2 | 11.2 | 74 | -- | 19 | 19 |
| 407321 | AT25x10-12 | Sabre Tooth | TL | 3* | 7 | 50 | 420 | 8 | 9.1 | 25.2 | 11.2 | 74 | -- | 24 | 21 |
| 416336 | AT26x10.5-12 | Raptor | TL | 3* | 7 | 50 | 455 | 8 | 10 | 25.9 | 11.6 | 76 | -- | 26 | 24 |
| 4MM37ATTF | AT30x10R14 | Mud Monster | TL | 6pr | 7 | 50 | 535 | 8 | 9.8 | 29.7 | 14.1 | 93.7 | -- | 51 | 36 |

*See Approved Rim Contours section